

FIREPLAC® SE


FIREPLAC® SE consists of flame-retardant chipboard veneered with 0.6 mm oak and then UV varnished.



flame resistant core board



chemical resistance



Especially suitable for
ceilings; walls; furniture

FIREPLAC® SE

	Recommended configuration	Individualisation
CORE BOARD		
Core board:	Chipboard flame retardant	
Core board thickness:	19 mm	see core board table
FORMATS		
Formats:	2800 x 2070 mm	fixed dimensions possible
VENEER GLUING		
Veneer gluing:		
VISIBLE SIDE		
Veneer:	exclusively European oak (certificate)	
Quality:	A-First Quality	A-Pattern matching 5*, A, B, C:
Grading:	Half-crown cut	2 further grading types: see www.europlac.com/customisation
Bonding method:	Veneer book matched	6 further bonding methods see www.europlac.com/customisation
Veneer thickness:	approx. 0,6 mm (certificate)	
Surface processing:	Rough-ground (grain 120)	further surface processings: see www.europlac.com/customisation
Surface finishing:	UV-lacquered matt	5 further surface finishes: see www.europlac.com/customisation
REVERSE SIDE		
Veneer:	exclusively European oak (certificate)	
Quality:	B	A-First Quality, A, C, paper, factory selection:
Bonding method:	Veneer book matched	6 further bonding methods see www.europlac.com/customisation
Veneer thickness:	approx. 0,6 mm (certificate)	
Surface processing:	Rough-ground (grain 120)	further surface processings: see www.europlac.com/customisation
Surface finishing:	UV-lacquered matt	5 further surface finishes: see www.europlac.com/customisation

CERTIFICATES

FSC® / PEFC / E1 / E0.5: Certificate depending on the product version.

ADDITIONAL INFORMATION

Flame retardant in composite tested according to EN 13501-1:2019, test incl. veneer edge 0.5 mm.
Classification: C-s2, d0.

CONTACT OUR EXPERT TEAM

Röhr GmbH | Narzissenstr. 5
 88069 Tettnang | Deutschland

Tel. +49 7542 93660
info@europlac.com

VARIATIONS

Thickness	Standard format	Classification	Classification report
17mm	2800x2070mm	C-s2, d0	FIRES-CR-161-24-AUPS
19mm	2800x2070mm	C-sl, d0	FIRES-CR-161-24-AUPS
29mm	2655x2100mm	B-sl, d0	PK-18-090

Note: Please note that wood is a natural product. Irregularities in color and structure are a natural characteristic and are generally desirable. Please understand that samples and illustrations regarding color and structure can only be an indication.

CONTACT OUR EXPERT TEAM

Röhr GmbH | Narzissenstr. 5
88069 Tettnang | Deutschland

Tel. +49 7542 93660
info@europlac.com