


## G-PLEX®

### PLYWOOD OKOUME

High-quality OKOUME plywood – glued from OKOUME layers through and through – veneered with noblewood.



digital printing possible



Especially suitable for  
ceilings; walls; furniture; ship and yacht interior construction;  
vehicle expansion

## G-PLEX®

	Recommended configuration	Individualisation
<b>CORE BOARD</b>		
Core board:	Plywood OKOUME	
Core board thickness:	18 mm	see core board table
<b>FORMATS</b>		
Formats:	2500 x 1220 mm (strength tolerance according to EN 315)	see core board table, Customised format 2500 x 1830 mm, fixed dimensions possible
<b>VENEER GLUING</b>		
Veneer gluing:	D3 (NAF) according to EN 204	D4 according to EN 204
<b>VISIBLE SIDE</b>		
Veneer:	European oak	140 wood species see <a href="http://www.europlac.com/customisation">www.europlac.com/customisation</a>
Quality:	A-First Quality	A-Pattern matching 5*, A, B, C: <a href="http://www.europlac.com/customisation">www.europlac.com/customisation</a>
Grading:	Half-crown cut	2 further grading types: see <a href="http://www.europlac.com/customisation">www.europlac.com/customisation</a>
Bonding method:	Veneer book matched	6 further bonding methods see <a href="http://www.europlac.com/customisation">www.europlac.com/customisation</a>
Veneer thickness:	approx. 0,6 mm	hardwoods approx. 0,6 mm, softwoods approx. 0,9 mm
Surface processing:	Rough-ground (grain 120)	further surface processings: see <a href="http://www.europlac.com/customisation">www.europlac.com/customisation</a>
<b>REVERSE SIDE</b>		
Veneer:	European oak (also available as raw board without veneer)	140 wood species see <a href="http://www.europlac.com/customisation">www.europlac.com/customisation</a>
Quality:	B	A-Pattern matching 5*, A-First Quality, A, C, paper, factory selection: <a href="http://www.europlac.com/customisation">www.europlac.com/customisation</a>
Bonding method:	Veneer book matched	6 further bonding methods see <a href="http://www.europlac.com/customisation">www.europlac.com/customisation</a>
Veneer thickness:	approx. 0,6 mm	hardwoods approx. 0,6 mm, softwoods approx. 0,9 mm
Surface processing:	Rough-ground (grain 120)	further surface processings: see <a href="http://www.europlac.com/customisation">www.europlac.com/customisation</a>

## CERTIFICATES

E1 / E0.5: Certificate depending on the product version

Note: Please note that wood is a natural product. Irregularities in color and structure are a natural characteristic and are generally desirable. Please understand that samples and illustrations regarding color and structure can only be an indication.

## CONTACT OUR EXPERT TEAM

Röhr GmbH | Narzissenstr. 5  
 88069 Tettnang | Deutschland

Tel. +49 7542 93660  
[info@europlac.com](mailto:info@europlac.com)