

P-PLEX®


High-quality poplar plywood veneered with noblewood.



low weight



digital printing possible



Especially suitable for
ceilings; walls; furniture; shop fitting and exhibition stands;
vehicle expansion

P-PLEX®

	Recommended configuration	Individualisation
CORE BOARD		
Core board:	Poplar Plywood	
Core board thickness:	4 mm	see core board table
FORMATS		
Formats:	2540 x 1870 mm	see core board table, customised format and fixed dimensions possible
VENEER GLUING		
Veneer gluing:	D3 (NAF) according to EN 204	D4 according to EN 204
VISIBLE SIDE		
Veneer:	European oak	140 wood species see www.europlac.com/customisation
Quality:	A-First Quality	A-Pattern matching 5*, A, B, C: www.europlac.com/customisation
Grading:	Half-crown cut	2 further grading types: see www.europlac.com/customisation
Bonding method:	Veneer book matched	6 further bonding methods see www.europlac.com/customisation
Veneer thickness:	approx. 0,6 mm	hardwoods approx. 0,6 mm, softwoods approx. 0,9 mm, 1,5 mm, 2,5 mm nominal on request
Surface processing:	Rough-ground (grain 120)	further surface processings: see www.europlac.com/customisation
REVERSE SIDE		
Veneer:	European oak	140 wood species see www.europlac.com/customisation
Quality:	B	A-First Quality, A, C, paper, factory selection: www.europlac.com/customisation
Bonding method:	Veneer book matched	6 further bonding methods see www.europlac.com/customisation
Veneer thickness:	approx. 0,6 mm	hardwoods approx. 0,6 mm, softwoods approx. 0,9 mm, 1,5 mm, 2,5 mm nominal on request
Surface processing:	Rough-ground (grain 120)	further surface processings: see www.europlac.com/customisation

CERTIFICATES

FSC® / PEFC / E1 / E0.5: Certificate depending on the product version

ADDITIONAL INFORMATION

Strength Tolerance according to DIN EN 315.
Good screw, pin, and clamp retention.
Low weight: 450 kg/m².
Waterproof: available upon request.

Note: Please note that wood is a natural product. Irregularities in color and structure are a natural characteristic and are generally desirable. Please understand that samples and illustrations regarding color and structure can only be an indication.

CONTACT OUR EXPERT TEAM

Röhr GmbH | Narzissenstr. 5
88069 Tettnang | Deutschland

Tel. +49 7542 93660
info@europlac.com