


RUSTICA®

INTERO

The veneer in the INTERO grade consists of domestic wood types. Cracks, branches, discolorations, wide cracks, fancy branches and strong discolorations – exactly these are deliberately sought and deliberately used with a low level of wastage, to create a wonderful and simply natural surface.



RUSTICA® INTERO

	Recommended configuration	Individualisation
CORE BOARD		
Core board:	MDF	
Core board thickness:	18 mm	
Core board surface	black coloured	red, brown, blue, green, other
FORMATS		
Formats:	2800 x 2070 mm	see core board table, customised format and fixed dimensions possible
VENEER GLUING		
Veneer gluing:	D3 (NAF) according to EN 204	D4 according to EN 204
VISIBLE SIDE		
Veneer:	European oak	140 wood species see www.europlac.com/customisation
Quality:	A	A-Pattern matching 5*, A-First Quality, B, C see www.europlac.com/customisation
Bonding method:	Random matched MIXED	6 further bonding methods see www.europlac.com/customisation
Veneer thickness:	approx. 0,6 mm	hardwoods approx. 0,6 mm, softwoods approx. 0,9 mm, 1,5 mm, 2,5 mm nominal on request
Surface processing:	Rough-ground (grain 120)	further surface processings: see www.europlac.com/customisation
REVERSE SIDE		
Veneer:	European oak	140 wood species see www.europlac.com/customisation
Quality:	B	A-First Quality, A, C, paper, factory selection: see www.europlac.com/customisation
Bonding method:	Random matched MIXED	6 further bonding methods see www.europlac.com/customisation
Veneer thickness:	approx. 0,6 mm	hardwoods approx. 0,6 mm, softwoods approx. 0,9 mm, 1,5 mm, 2,5 mm nominal on request
Surface processing:	Rough-ground (grain 120)	further surface processings: see www.europlac.com/customisation

CERTIFICATES

FSC® / PEFC / E1 / E0.5: Certificate depending on the product version.

Note: Please note that wood is a natural product. Irregularities in color and structure are a natural characteristic and are generally desirable. Please understand that samples and illustrations regarding color and structure can only be an indication.

CONTACT OUR EXPERT TEAM

Röhr GmbH | Narzissenstr. 5
88069 Tettnang | Deutschland

Tel. +49 7542 93660
info@europlac.com