


RUSTICA® SCRATCH

As a special variant of our RUSTICA® series, with RUSTICA® SCRATCH the veneers are laid by hand with open joints on the core board and then brushed.



Especially suitable for
ceilings; walls; furniture; shop fitting and exhibition stands; table tops

RUSTICA® SCRATCH

	Recommended configuration	Individualisation
CORE BOARD		
Core board:	MDF	
Core board thickness:	18 mm	see core board table
Core board surface:	black coloured	red, brown, blue, green, other
FORMATS		
Formats:	3050 x 1220 mm	see core board table, customised format and fixed dimensions possible, Breite max. 1250 mm
VENEER GLUING		
Veneer gluing:	D3 (NAF) according to EN 204	D4 according to EN 204
VISIBLE SIDE		
Veneer:	Historic oak natural	140 wood species see www.europlac.com/customisation
Quality:	A-First Quality	A-Pattern matching 5*, A, B, C: see www.europlac.com/customisation
Bonding method:	Random matched NATUR	6 further bonding methods see www.europlac.com/customisation
Veneer thickness:	0,9 mm and up	
Surface processing:	Rough-ground (grain 120)	further surface processings: see www.europlac.com/customisation
Processing:	SCRATCH technic (trimmed and parallel joint 1-6 mm wide)	
REVERSE SIDE		
Veneer:	Historic oak natural	140 wood species see www.europlac.com/customisation
Quality:	B	A-First Quality, A, C, paper, factory selection: see www.europlac.com/customisation
Bonding method:	Random matched NATUR	6 further bonding methods see www.europlac.com/customisation
Veneer thickness:	approx. 0,9 mm	hardwoods approx. 0,9 mm, softwoods approx. 0,9 mm
Surface processing:	Rough-ground (grain 120)	further surface processings: see www.europlac.com/customisation
CERTIFICATES		
FSC® / PEFC / E1 / E0.5: Certificate depending on the product version.		
Note: Please note that wood is a natural product. Irregularities in color and structure are a natural characteristic and are generally desirable. Please understand that samples and illustrations regarding color and structure can only be an indication.		