

NOBLEWOOD ON LIGHT CHIPBOARD


Light chipboard Lisopac or lightweight chipboard veneered with noblewood.



low weight



digital printing possible



Especially suitable for
ceilings; walls; furniture; shop fitting and exhibition stands;
vehicle expansion

Noblewood on light chipboard

	Recommended configuration	Individualisation
CORE BOARD		
Core board:	Light chipboard Lisoplac	lightweight chipboard
Core board thickness:	49 mm	on request
FORMATS		
Formats:	2800 x 2070 mm	customised format and fixed dimensions possible
VENEER GLUING		
Veneer gluing:	D3 (NAF) according to EN 204	D4 according to EN 204
VISIBLE SIDE		
Veneer:	European oak	140 wood species see www.europlac.com/customisation
Quality:	A-First Quality	A-Pattern matching 5*, A, B, C:
Grading:	Half-crown cut	2 further grading types: see www.europlac.com/customisation
Bonding method:	Veneer book matched	6 further bonding methods see www.europlac.com/customisation
Veneer thickness:	approx. 0,6 mm	hardwoods approx. 0,6 mm, softwoods approx. 0,9 mm, 1,5 mm, 2,5 mm nominal on request
Surface processing:	Rough-ground (grain 120)	further surface processings: see www.europlac.com/customisation
REVERSE SIDE		
Veneer:	European oak	140 wood species see www.europlac.com/customisation
Quality:	B	A-First Quality, A, C, paper, factory selection:
Bonding method:	Veneer book matched	6 further bonding methods see www.europlac.com/customisation
Veneer thickness:	approx. 0,6 mm	hardwoods approx. 0,6 mm, softwoods approx. 0,9 mm, 1,5 mm, 2,5 mm nominal on request
Surface processing:	Rough-ground (grain 120)	further surface processings: see www.europlac.com/customisation
CERTIFICATES		
FSC® / E1 / E0.5: Certificate depending on the product version		
Note: Please note that wood is a natural product. Irregularities in color and structure are a natural characteristic and are generally desirable. Please understand that samples and illustrations regarding color and structure can only be an indication.		