

NOBLEWOOD on MDF

High-quality MDF core board veneered with noblewood.



moisture-resistant core board possible




high strength



formaldehyde-free



flame-resistant core board possible



Especially suitable for
ceilings; walls; furniture; shop fitting and exhibition stands

Noblewood on MDF

CORE BOARD		Recommended configuration	Individualisation
Core board:	MDF		MDF H (moisture resistant) / MDF FR (flame retardant) / MDF NAF see core board table
Core board thickness:	18 mm		see core board table
FORMATS			
Formats:	2800 x 2070 mm		see core board table, customised format and fixed dimensions possible
VENEER GLUING			
Veneer gluing:	D3 (NAF) according to EN 204. Test certification for E1 is available.		D4 according to EN 204
VISIBLE SIDE			
Veneer:	European oak		140 wood species see www.europlac.com/customisation
Quality:	A-First Quality		A-Pattern matching 5*, A, B, C: see www.europlac.com/customisation
Grading:	Half-crown cut		2 further grading types: see www.europlac.com/customisation
Bonding method:	Veneer book matched		6 further bonding methods see www.europlac.com/customisation
Veneer thickness:	approx. 0,6 mm		hardwoods approx. 0,6 mm, softwoods approx. 0,9 mm 1,5 mm, 2,5 mm nominal on request
Surface processing:	Rough-ground (grain 120)		further surface processings: see www.europlac.com/customisation
REVERSE SIDE			
Veneer:	European oak		140 Wood species see www.europlac.com/customisation
Quality:	B		A-First Quality, A, C, paper, factory selection: see www.europlac.com/customisation
Bonding method:	Veneer book matched		6 further bonding methods see www.europlac.com/customisation
Veneer thickness:	approx. 0,6 mm		hardwoods approx. 0,6 mm, softwoods approx. 0,9 mm 1,5 mm, 2,5 mm nominal on request
Surface processing:	Rough-ground (grain 120)		further surface processings: see www.europlac.com/customisation

CERTIFICATES

FSC® / PEFC / E1 / E0.5: Certificate depending on the product version

ADDITIONAL INFORMATION

The homogeneous structure makes it ideal for all types of processing: milling, drilling, doweling, stapling.

Moisture resistant: Carrier MDF H, MDF NAF

Flame retardant possible: MDF FR core: in accordance with EN 13501-1 before veneering, no testing in the combination.

Core boards lose their approval due to finishing.

Note: Please note that wood is a natural product. Irregularities in color and structure are a natural characteristic and are generally desirable. Please understand that samples and illustrations regarding color and structure can only be an indication.

CONTACT OUR EXPERT TEAM

Röhr GmbH | Narzissenstr. 5
88069 Tettnang | Deutschland

Tel. +49 7542 93660
info@europlac.com