europlac

RUSTICA® BASIS

Our RUSTICA® series impresses with its expressive look. Only veneer with unique characteristics such as cracks, knots, colour and texture differences are carefully selected and expertly processed.





Especially suitable for ceilings; walls; furniture; shop fitting and exhibition stands; table tops



RUSTICA®

BASIS

CORE BOARD	Recommended configuration	Individualisation
CORE BOARD	DO abiaba and	
Core board:	P2 chipboard	
Core board thickness:	18 mm	see core board table
FORMATS		
Formats:	2800 x 2070 mm	customised format and fixed dimensions possible
VENEER GLUING		
Veneer gluing:	D3 (NAF) according to EN 204	D4 according to EN 204
VISIBLE SIDE		
Veneer:	European oak	140 wood species see www.europlac.com/customisation
Quality:	A-First Quality	A-Pattern matching 5*, A, B, C: see www.europlac.com/customisation
Bonding method:	Random matched NATUR	6 further bonding methods see www.europlac.com/customisation
Veneer thickness:	approx. 0,6 mm	hardwoods approx. 0,6 mm, softwoods approx. 0,9 mm, 1,5 mm, 2,5 mm nominal on request
Surface processing:	Rough-ground (grain 120)	further surface processings: see www.europlac.com/customisation
REVERSE SIDE		
Veneer:	European oak	140 wood species see www.europlac.com/customisation
Quality:	В	A-First Quality, A, C, paper, factory selection: see www.europlac.com/customisation
Bonding method:	Random matched NATUR	6 further bonding methods see www.europlac.com/customisation
Veneer thickness:	approx. 0,6 mm	hardwoods approx. 0,6 mm, softwoods approx. 0,9 mm, 1,5 mm, 2,5 mm nominal on request
Surface processing:	Rough-ground (grain 120)	further surface processings: see www.europlac.com/customisation

CERTIFICATES

FSC® / PEFC / E1 / E0.5: Certificate depending on the product version.

Note: Please note that wood is a natural product. Irregularities in color and structure are a natural characteristic and are generally desirable. Please understand that samples and illustrations regarding color and structure can only be an indication.

