

eurolacBALKEN

The eurolacBALKEN is the smart alternative to solid wood beams.




eurolac®

low weight



digital printing possible



Especially suitable for
furniture; shop fitting and exhibition stands

europlacBALKEN

	Recommended configuration	Individualisation
CORE BOARD		
Core board:	3-layer spruce board glued several times	
FORMATS		
Length:	3000 mm	customised format and fixed dimensions possible
Dimension beam:	116 x 116 mm (veneer thickness 0,6 mm)	84 x 84 mm, 64 x 64 mm (veneer thickness 0,6 mm), customised format possible
VENEER GLUING		
Veneer gluing:	D3 (NAF) according to EN 204	D4 according to EN 204
VISIBLE SIDE		
Veneer:	European oak	140 wood species see www.europlac.com/customisation
Quality:	A-First Quality	A-Pattern matching 5*, A, B, C: see www.europlac.com/customisation
Grading:	Half-crown cut	2 further grading types: see www.europlac.com/customisation
Bonding method:	Veneer book matched	6 further bonding methods: see www.europlac.com/customisation
Veneer thickness:	approx. 0,6 mm	hardwoods approx. 0,6 mm, softwoods approx. 0,9 mm 1,5 mm, 2,5 mm nominal on request
Surface processing:	Rough-ground (grain 120)	further surface processings: see www.europlac.com/customisation

CERTIFICATES

FSC® / PEFC / E1 / E0.5: Certificate depending on the product version

ADDITIONAL INFORMATION

End panels with end grain available on request.

europlacBALKEN UND VERZUG

In the event of climatic fluctuations and due to the natural swelling and shrinkage of the wood, the europlacBALKEN may develop warping. When used in damp areas such as kitchens and bathrooms, this is more likely to occur.

It is crucial that the material is allowed to reach an equilibrium moisture content. This means that it must be processed under the same climatic conditions under which it will be used at a later date. Furthermore, when choosing the surface treatment, care must be taken to ensure that no moisture is added.

Please understand that we will not recognize a warping of the europlacBALKEN as a possible complaint. Our products are optimally manufactured and packaged. Please make sure that at the respective storage locations (retailers and processors) that the boards are stored correctly (especially in humid seasons).

Note: Please note that wood is a natural product. Irregularities in color and structure are a natural characteristic and are generally desirable. Please understand that samples and illustrations regarding color and structure can only be an indication.

CONTACT OUR EXPERT TEAM

Röhr GmbH | Narzissenstr. 5
 88069 Tettnang | Deutschland

Tel. +49 7542 93660
info@europlac.com