

BLACK WIDOW AMT

DYNAMIC RESOLUTION 3.9 mm | 7.8 mm

SPECS SHEET

	Actual	Dynamic	Transparent
Pitch	3.9mm	7.8mm	7.8mm
Pixel Density	65536 Pixels /m2	16384 Pixels /m2	16384 Pixels /m2
LED Configuration	SMD 1515 Blackface	SMD 1515 Blackface	SMD 1515 Blackface
Module Resolution	128 x 64	64 x 32	64 x 32
Control System	Brompton	Brompton	Brompton
Resolution	256 x 256	128 x 128	128 x 128
Panel Size (WxH)	1000mm x 1000mm 1000mm x 500mm 500mm x 1000mm 500mm x 500mm	1000mm x 1000mm 1000mm x 500mm 500mm x 1000mm 500mm x 500mm	1000mm x 1000mm 1000mm x 500mm 500mm x 1000mm 500mm x 500mm
Weight w/ Out	24 kg / 52.8 lb	24 kg / 52.8 lb	22.5 kg / 49.6 lb
Weight with Wind Brace	29.5 kg / 65 lb	29.5 kg / 65 lb	28 kg / 61.6 lb
Transparency	/	/	/
Contrast	10000/1	5000/1	5000/1
Brightness	4000 Nits	2500 Nits	3600 Nits
Max Power Consumption	660 Watts	570 Watts	570 Watts
Avg. Power Consumption	220 Watts	190 Watts	190 Watts
Viewing Angle	160 / 160	160 / 160	160 / 160
Operating Power Source	100-240V AC 50-60Hz	100-240V AC 50-60Hz	100-240V AC 50-60Hz
Max Refresh Rate	7680 Hz	7680 Hz	7680 Hz
Avg. Refresh Rate	3840 Hz	3840 Hz	3840 Hz
IP Rating	IP 65	IP 65	IP 65
Power Connector	Neutrik powerCON TRUE1	Neutrik powerCON TRUE1	Neutrik powerCON TRUE1
Data Connector	Neutrik etherCON	Neutrik etherCON	Neutrik etherCON
GrayScale	16 bits	16 bits	16 bits
Curving+	+2.5°, +5°, 7.5°, 10	+2.5°, +5°, 7.5°, 10	+2.5°, +5°, 7.5°, 10
Curving-	-10°, -7.5°, -5°, -2.5°	-10°, -7.5°, -5°, -2.5°	-10°, -7.5°, -5°, -2.5°
Max Hanging	26M	26M	26M
Max Stacking	6M	6M	6M



BLACK WIDOW **AMT**

DYNAMIC RESOLUTION 3.9 mm | 7.8 mm

APPLICATION PHOTOS

