



Fluid[™]
MARINE

SWR 13

Featuring an aluminum hull, optional Rescue Pro Engine, carrying handles, and weighing only 181 lbs., the Fluid Boats Swift Water Rescue 13 (SWR 13) is a durable, lightweight, easy-to-launch boat for river and flood rescues. Fluid's military grade ORCA Hypalon Tubes withstand the elements and are tear and puncture resistant. The aluminum hull won't get damaged when stored or used in water with tree branches, rocks or other debris. The optional Rescue Pro Engine's enclosed rotor protects people and the engine from accidental impacts with the propeller.

Law enforcement, Fire Departments, Space Programs and Commercial Organizations trust Fluid Boats because they're **Made for Any Mission[™]**.



Swift Water Rescue 13

SPECIFICATIONS	US	METRIC
LOA (Length Overall)	13' 1"	4 m
Length inside	9' 6"	3 m
Beam	5' 8"	1.5 m
Beam internal	2' 8"	812 mm
Tube Diameter	19"	482 mm
No. of Chambers	3 chambers	
Weight Capacity	2,020 lbs	916 kg
Person Capacity	7 persons	
Boat Weight	181 lbs	82 kg
Engine Weight	170 lbs	77 kg
Boat and Engine Weight	350 lbs	159 kg
Shaft single/twin	20"	508 mm
Horsepower	30 hp	22 kw
Fuel Capacity	5 gal	20 L
Hull Material	Aluminum	
Tube Material	1670dtx Hypalon Neoprene	
Transom Height	20"	508 mm
Deadrise	5°	

STANDARD EQUIPMENT

HULL

- » Aluminum Hull
- » 10mm EVA decking
- » 4" Elephant Trunk Deck Drains
- » Bow/Stern Eyes (Lifting & Towing)
- » SS Bow/Stern Eyes (Lifting & Towing)

TUBES

- » 1670dtx Military Grade Hypalon Tubes
- » Heavy-Duty Inflation and Pressure Relief Valves
- » Non-Slip Rubber Applied to Tubes
- » Heavy-Duty EPDM Rubbing Strake
- » Lifelines
- » 9 Carry Handles
- » 2 Righting Lines

NAVIGATION AND SAFETY

- » Tube Repair Kit with Pump
- » Paddles (2)

OPTIONS

- » 30 hp Engine with Piranha Props

- » 5 gal Flexible Fuel Tank

- » Trailer

