

TECHNICAL FEATURES UNGLAZED PORCELAIN TILES
CONFORMING TO EUROPEAN STANDARDS EN 14411 ISO 13006 APP. G (Group BIA UGL Eb ≤ 0,5%)

 sizes EN ISO 10545-2 compliant	 water absorption EN ISO 10545-3 compliant	 breaking strength EN ISO 10545-4 compliant	 abrasion resistance EN ISO 10545-6 average <150mm³	 thermal expansion coefficient EN ISO 10545-8 ≤9 MK-1	 thermal shock resistance EN ISO 10545-9 resistant
 frost resistance EN ISO 10545-12 resistant	 chemicals resistance EN ISO 10545-13 from ULA to ULB from UHA to UHB UA	 stains resistance EN ISO 10545-14 class 5	 colors resistance to light DIN 51094 no alteration after testing	 friction coefficient DIN 51130 ANSI A 1371 (DCOF) R10 R11 matt antislip > 0,42	



DOWNLOAD
A R E A

Terratinta Group Srl SB
Via Viazza Il Tronco 45, 41042 Fiorano Modenese (MO) - Italy
www.terratintagroup.com  /Terratinta Group  /terratintagroup
Printed in March 2025



Wald /

ceramica
magica

WOOD DESIGN

Wald /



ceramica
magica



Rovere

matt



Miele

matt



Boiserie **Acero**

matt



Acero

matt



Noce

antislip



matt



Boiserie **Noce**

matt