





Light 6 mm

WHITE 120x260cm matt (floor)

GREY 120x260cm matt (wall)

± 10,5mm

Light_{6mm}

120x260* - 48"x102"



120x120* - 48"x48"



60x120* - 24"x48"



* WHITE | GREY MATT

90x90 - 36"x36"



15x60
6"x24"



10x60
4"x24"



60x60 - 24"x24"
60x60 lappato



30x60 - 12"x24"
30x60 lappato



5x60
2"x24"



20x20
8"x8"



10x10
4"x4"



PORCELAIN STONEWARE
GRES PORCELLANATO

RECTIFIED AND MODULAR
RETTIFICATI E MODULARI


MOSAIC

30x30 (2,5x5) - 12"x12" (1"x2")
30x30 (2,5x5) LAPPATO



SPECIAL PIECES

STEP 30x60 - 12"x24"



SKIRTING 5x60 - 2"x24"

SKIRTING 5x90 - 2"x36"



Technical features unglazed porcelain stoneware

Conforming to European Standards EN 14411 ISO 13006 App. G (Group BIa UGL Eb ≤ 0,5%)

CARATTERISTICHE TECNICHE GRES PORCELLANATO NON SMALTATO Conformi a Norme Europee EN 14411 ISO 13006 App. G (Gruppo BIa UGL Eb ≤ 0,5%)



sizes
EN ISO 10545-2

compliant



frost resistance
EN ISO 10545-12

resistant



water absorption
EN ISO 10545-3

compliant



chemical resistance
EN ISO 10545-13

from ULA to ULB
from UHA to UHB
UA



breaking strength
EN ISO 10545-4

compliant



stains resistance
EN ISO 10545-14

class 5



abrasion resistance
EN ISO 10545-6

average
< 150mm³



colors resistance
to light
DIN 51094

no alteration
after testing



thermal expansion
coefficient
EN ISO 10545-8

≤9 MK-1



friction coefficient
DIN 51130
ANSI A 137.1 (DCOF)

R10 matt
>0,42 matt



thermal shock resistance
EN ISO 10545-9

resistant



Light 6 mm

WHITE 120X260cm matt