

Norse
Packaging

	BOX			PALLET		
	PZ PCS	SQ.MT.	KG	BOXES	SQ.MT.	KG
120x120 – 48"x48" matt Fog Powder Clay Ash	2	2,88	59,04	18	51,84	1080
60x120 – 24"x48" matt	2	1,44	30,00	32	46,08	980
90x90 – 36"x36" matt	2	1,62	35,00	20	32,40	720
90x90 – 36"x36" ultra matt TH/CK ₁₀₀₀ Powder Clay Ash	1	0,81	35,50	21	17,01	766
60x60 – 24"x24" matt	3	1,08	22,00	40	43,20	900
30x60 – 12"x24" matt	6	1,08	22,00	40	43,20	900
30x30 – 12"x12" matt	11	1,00	21,80	48	48,00	1066
20x60 – 8"x24" matt	8	0,96	20,95	48	46,08	1026
10x60 – 4"x24" matt	15	0,90	19,65	40	36,00	806
15x15 – 6"x6" matt	44	1,00	21,80	48	48,00	1066
10x10 – 4"x4" matt	50	0,50	10,20	50	25,00	530
mosaic 30x30 (5x5) 12"x12" (2"x2") matt	11	1,00	21,50	30	30,00	665
mosaic 30x60 12"x24" matt	6	1,08	23,25	30	32,40	718
Hyper 30x30 – 12"x12" glossy White	5	0,45	7,00	60	27,00	440
Roller 10x30 4"x12" matt	16	0,48	10,00	42	20,16	440
Roller End 10x10 4"x4" matt	13	0,13	2,68	115	14,95	330
Knit 30x30 12"x12" matt	7	0,63	9,00	42	26,46	398
skirting 5x60 – 2"x24" matt	12	7,20ml	8,00	-	-	-
skirting 5x90 – 2"x36" matt	12	10,80ml	12,00	-	-	-
step 30x60 – 12"x24" matt	6	-	26	-	-	-
step tread 34x90 14"x36" matt	2	-	17,50	-	-	-



terratin^{100%}_{ceramiche}^{made in Italy}

#notaclassicstory

brand of Terratinta Group Srl SB
// 45, via Viazza II Tronco 41042
Fiorano Modenese (MO) Italy
T +39 0536911408
W terratintagroup.com
@ Terratinta Group
t terratintagroup //
Printed in March 2025
#terratinstyle

valid for **NORSE** matt | ultra matt

TECHNICAL FEATURES UNGLAZED PORCELAIN STONEWARE

CONFORMING TO EUROPEAN STANDARDS EN 14411 ISO 13006 APP. G (GROUP BIA UGL EB ≤ 0,5%)

sizes	water absorption	thermal expansion coefficient	frost resistance	thermal shock resistance	abrasion resistance
EN ISO 10545-2	EN ISO 10545-3	EN ISO 10545-8	EN ISO 10545-12	EN ISO 10545-9	EN ISO 10545-6
compliant	compliant	≤9 MK-1	resistant	resistant	compliant
modulus of rupture	breaking strength	chemical resistance	stains resistance	colors resistance to light	friction coefficient (slipperiness)
EN ISO 10545-4	EN ISO 10545-4	EN ISO 10545-13	EN ISO 10545-14	DIN 51094	DIN 51130 ANSI A 137.1 (DCOF)
compliant	compliant sp. < 7,5 mm MIN 700N sp. ≥ 7,5 mm MIN 1300N Thick20mm ≥ 4000N	from ULA to ULB from UHA to UHB UA	class 5	no alteration after testing	R10 matt > 0,42 R11 Thick20mm

valid for **HYPER** glossy | **ROLLER** | **KNIT** matt

TECHNICAL SPECIFICATIONS FOR EXTRUDED CERAMIC TILES

CONFORMING TO EN 14411 ISO 13006 STANDARDS ANNEX F (GROUP AIII GL WITH EB > 10%)

water absorption	breaking strength	glaze crazing resistance	chemical resistance
EN ISO 10545-3	UNI EN ISO 10545-4	UNI EN ISO 10545-11	UNI EN ISO 10545-14 UNI EN ISO 10545-13
Eb > 10%	compliant	resistant	Min. class 3 Min. class B

The tone of the samples is purely indicative and may vary between production runs.
Il tono presentato nelle campionature è puramente indicativo e può variare da produzione a produzione.

DOWNLOAD
A R E A

TERRATINTA^{group}

Certified

Corporation

A company part of

ITALCER^{GROUP}

DESIGN SURFACES

Norse



Norse





Fog



Ash



Clay



Powder



Earth



Mud



Crete