



The STONE concept has been created to combine the basic perfection of the natural stone with the latest technologies and styles: Stonedesign is a project designed for indoor and outdoor spaces with a sophisticated and modern identity, and it is suitable also for heavy traffic areas. Stonedesign is also available in the brand new LIGHT technology, in two new and bigger sizes, 120x120cm and 60x120cm, in 7,3mm thickness. Fine porcelain unglazed tiles at their very best.



**Chalk** 60x60cm matt



**Rope** 60x120cm wall matt *light*  
120x120cm floor matt *light*

*light*  
7,3mm

 **STRONG:** 7,3mm thick with an average breaking strength of 1.587 newton, twice as much as the standards requirements.

 **LIGHT:** the reduced weight of 17,50kg/sqm gives "Light" huge advantages in terms of transport and handling.

 **SELF-LEVELLING:** the special mix of raw materials used in "Light" gives elasticity to the product itself, as a result of this "Light" ensures excellent installation results in any kind of applications.

 **GREEN:** "Light" is made using high percentage of recycled raw materials and is certified as a product made with at least 40% pre consumer recycled content.



**Chalk**





**Rope**



**Cinnamon**



**Ash**

PACKAGING						
	PCS	SQ.MT.	KG	BOXES	SQ.MT.	KG
 <b>120x120cm</b> <i>light</i> matt rectified	2	2,88	50,40	22	63,36	1.129
 <b>60x120cm</b> <i>light</i> matt rectified	3	2,16	36	27	58,32	992
 <b>60x60cm</b> matt/chiselled rectified	4	1,44	29,70	30	43,20	911
 <b>30x60cm</b> matt/chiselled rectified	8	1,44	28,90	32	46,08	945
 <b>15x60cm</b> matt/chiselled rectified	12	1,08	21,85	40	43,20	895
 <b>10x60cm</b> matt/chiselled rectified	15	0,90	18	40	36	740
 <b>5x60cm</b> matt/chiselled rectified	34	1,02	20	40	40,80	820
 <b>10x10cm</b> matt/chiselled rectified	50	0,50	10	50	25	495
 <b>Mosaic 30x30cm (5x5)</b> matt rectified	11	1	20	30	30	620
 <b>Mosaic 30x30cm (2,5x5)</b> matt/chiselled rectified	11	1	20	30	30	620
 <b>Mosaic 30x60cm</b> matt/ chiselled rectified	6	1,08	20	30	32,40	620
 <b>Step 30x60cm</b> matt/ chiselled rectified	6	1,08	22,20	-	-	-
 <b>Skirting 7x60cm</b> matt/ chiselled rectified	14	8,40ml	12,60	-	-	-
 <b>60x60cm TH CKN</b> * chiselled rectified	2	0,72	31,72	32	23,04	1.035

TECHNICAL FEATURES UNGLAZED PORCELAIN STONEWARE  
CONFORMING TO EUROPEAN STANDARDS EN 14411 ISO 13006 APP. G (GRUPPO BIA UGL CON  $E_B \leq 0,5\%$ )\*available in **Cinnamon** and **Ash** colors only


 <b>sizes</b> EN ISO 10545-2	compliant	 <b>frost resistance</b> EN ISO 10545-12	resistant
 <b>water absorption</b> EN ISO 10545-3	compliant	 <b>chemicals resistance</b> EN ISO 10545-13	from ULA to ULB from UHA to HUB UA
 <b>breaking strength</b> EN ISO 10545-4	compliant	 <b>stain resistance</b> EN ISO 10545-14	classe 5
 <b>abrasion resistance</b> EN ISO 10545-6	average $<150\text{mm}^3$	 <b>colors resistance to light</b> DIN 51094	no alteration after testing
 <b>thermal expansion coefficient</b> EN ISO 10545-8	$\leq 9\text{ MK-1}$	 <b>friction coefficient</b> DIN 51130 ANSI A 137.1 (DCOF)	R10 matt R11 chiselled $>0,42$
 <b>thermal shock resistance</b> EN ISO 10545-9	resistant		

