

TECHNICAL FEATURES UNGLAZED PORCELAIN TILES
 CONFORMING TO EUROPEAN STANDARDS EN 14411 ISO 13006 APP. G (Group BIA UGL Eb ≤ 0,5%)

					
sizes	water absorption	breaking strength	abrasion resistance	thermal expansion coefficient	thermal shock resistance
EN ISO 10545-2	EN ISO 10545-3	EN ISO 10545-4	EN ISO 10545-7	EN ISO 10545-8	EN ISO 10545-9
compliant	compliant	compliant	from 4 to 5	≤9 MK-1	resistant
					
frost resistance	chemicals resistance	stains resistance	colors resistance to light	friction coefficient	
EN ISO 10545-12	EN ISO 10545-13	EN ISO 10545-14	DIN 51094	DIN EN 16165 (AN. "B") ANSI A 1371 (DCOF)	
resistant	from GLA to GLB from GHA to GHB GA	class 5	no alteration after testing	R10 matt > 0,42	

Oakbricks /

WOOD DESIGN
 Oakbricks /



DOWNLOAD
 AREA

TERRATINTA
 group Certified
 (B)
 Corporation

A company part of

ITAL CER
 GROUP
 DESIGN SURFACES

ceramica
 magica

ceramica
 magica

Terratinta Group Srl SB

Via Viazza Il Tronco 45, 41042 Fiorano Modenese (MO) - Italy
www.terratintagroup.com [/Terratinta Group](https://www.facebook.com/TerratintaGroup) [/terratintagroup](https://www.instagram.com/terratintagroup)

Printed in March 2025



Birch



Natural



Honey



Walnut



Brown



Burnt