

# HK9600 Series POS Terminal

The HK968 is one of the most robust POS Terminals on the market. With its all-in-one space-saving form factor and sleek design, it is functional and appealing.

The HK968's 15.6" widescreen and dual hinge stand make it easy for any operator to use in any setting.



# Built for the hospitality industry powerful and space-saving



Deep starry-style metal appearance makes the counter more fashionable.



A 15.6" widescreen for a more comfortable operating experience.



Dual hinge stand for flexible adjustment; Dual LAN port for dual network application scenarios.

# **HK9600**

| Technical specs      | HK9600   |  |
|----------------------|--|--|
| Processor            | Intel Tiger Lake UP3, Intel 11th Gen CPU 13-11GEN CPU  |  |
| Operating system     | Windows 10   |  |
| Memory               | SO-DIMM DDR4 3200MHz 8GB, up to 16GB   |  |
| Storage              | M.2 SSD 128GB, up to 512GB   |  |
| Display panel        | 15.6" TFT LCD (LED back light ) / 16:9 / resolution: 1920 x 1080   |  |
| Touch screen         | True flat capacitive touch screen  |  |
| Power supply         | 24V 120W (standard)  |  |
| Speaker              | 2*2W Speaker   |  |
| I/O Ports            | 2* USB 3.0; 1* USB 3.1; 1*24V Powered USB; 1*24V DC-IN Port; 3* RJ50 Serial Ports; 2* RJ45 100M/1000M Gigabit LAN; 1*Type-C USB+PD; 1*HDMI; 1*Audio, 3.5mm; 1*24V RJ11 for Cash drawer, support Dual cash draw |  |
| Dimensions (LxWxH)   | 369*303*204 mm   |  |
| Weight               | 7.9 KG   |  |
| Optional peripherals | Card reader  | MSR only 3 tracks MSR; MSR+RFID (Supports MIFARE one and MIFARE CPU card)        |
|                      | Fingerprint reader   | Fingerprint reader   |
|                      | Stand  | Dual hinge stand   |
|                      | Second display   | 10:1" second screen / resolution: 1280x800 (Touch/non-Touch) 2x20 characters VFD |
|                      | Wireless   | Dual-band Wi Fi® 802.tla/b/g/n/ac 2.4GHz/5GHz                                    |
| Environment          | Operating  | 0°C - 40°C/20% - 80% RH non-condensing   |
|                      | Storage  | -20°C - 60°C/10% - 90% RH non-condensing   |
| EMC & Safety         | FCC /CE / RoHS Pending   |  |
| Tilt Adjustment      | 0º - 82º Vertical  |  |
| Colour               | Gray   |  |

# 24/7 global support



With support teams in the Americas, Europe, Middle East and Asia Pacific we provide individual software and hardware support; as well as remote troubleshooting. Already serving 7,000+ outlets in the world, we understand the importance of support and what it takes to keep your business running non-stop.

## **Contact us**

Europe & Africa

sales-eu@shijigroup.com Tel: +49 8941207171

Middle East

sales-me@shijigroup.com Tel: +971 45786947

### **Greater China**

Tel: +86 10593253882

### **Asia Pacific**

sales-ap@shijigroup.com Tel: +65 62407400

### **United States**

sales-us@shijigroup.com Tel: +1 4049484001

### Canada & Latam

sales-can.list@shijigroup.com sales-latam@shijigroup.com



shijigroup.com



in Shiji Group