

HM628N Tablet POS

Featuring an embedded high-performance, low-power CPU, the HM628N delivers seamless operation in a sleek, bezel-free 10.1" PCAP multi-touch display. With optional features like a barcode reader, 4G connectivity, and a multifunctional docking station—complete with an integrated printer—the HM628N adapts effortlessly to mobile, desktop, or wall-mounted use, making it ideal for dynamic service scenarios.



Built for the hospitality industry powerful and space-saving



Embedded CPU platform with high performance and low power consumption



Bezel-free, flat and PCAP multi-touch 10.1" wide screen display that optimizes viewing;



Docking station with various ports, integrated printer optional

Technical specs	HM628N
Tablet Features	Processor Intel Celeron N4120 @ Quad-core ,1.1GHz, up to 2.6Ghz
	Operating system Windows 10 - OS
	Memory 4GB
	Storage 64GB eMMC
	Display panel 10.1" TFT LCD(LED back light) wide screen standard resolution: 1280 x 800
	Battery 7.6V , 5500mAh
	Speaker 2*1W Speaker
	Wireless connection Dual-band Wi-Fi® 802.11a/b/g/n/ac 2.4GHz/5GHz , BT V4.1
	Touch screen True flat capacitive touch screen/10 point touch
	Default peripherals Integrated MSR card reader (3 tracks MSR); 5MP AF rear-facing camera; 2MP AF front-facing camera; 1*GPS 1*G-sensor; 1* hand strap(standard)
	I/O Ports 1* USB3.0; 1* micro USB; 1*Micro HDMI; 1* Standard TF, Up to 32G; 1*SIM slot for Nano card; 1*DC jack, 12V 2A; 1*Audio jack ,3.5mm
	Power supply 12V 2A
	Buttons Power button , volume +/-, Barcode scanner
	Optional Peripherals Integrated Magtek Encrypted MSR; Integrated 3 tracks MSR & RFID(OPOS) 1D barcode scanner; 2D barcode scanner; 4G module; VESA mounting plate; Shoulder strap
Charging docking station Features (charging only)	DC jack 12V 2A
Smart docking station Features	I/O ports 2*USB 2.0
	Adapter 24V 90W
	Optional Peripherals 2"printer; MPOS bracket
	I/O ports 3*USB 2.0 1*100M LAN Ethernet port; 1*RJ11 24V cash drawer port; 2*RS232 Serial Ports
EMC & Safety	CE/FCC/RoHS
Operating Environment	5°C-40°C/40%-90% RH non-condensing
Storage Environment	-20°C-60°C/10%-90% RH non-condensing
Color	Black
Tilt Adjustment	Top hinge 0°-180°, Bottom hinge 0°-75°
Dimensions (L x W x H)	PAD : 282 x198 x18 mm; Charging dock : 151 x121 x92 mm; Smart dock : 236 x218 x150-370 mm
Weight	PAD : 1Kg, Charging dock : 325g, Smart dock : 2.82Kg

24/7 global support



With support teams in the Americas, Europe, Middle East and Asia Pacific we provide individual software and hardware support; as well as remote troubleshooting. Already serving 7,000+ outlets in the world, we understand the importance of support and what it takes to keep your business running non-stop.

Contact us

Europe & Africa
sales-eu@shijigroup.com
Tel: +49 8941207171

Middle East
sales-me@shijigroup.com
Tel: +971 45786947

Greater China
sales@shijigroup.com
Tel: +86 10593253882

Asia Pacific
sales-ap@shijigroup.com
Tel: +65 62407400

United States
sales-us@shijigroup.com
Tel: +1 4049484001

Canada & Latam
sales-can.list@shijigroup.com
sales-latam@shijigroup.com

 shijigroup.com

 Shiji Group