

LED downlight



Cira-Stellar

The Cira-Stellar LED downlight is designed to create a clean, comfortable, and visually appealing lighting environment for modern interiors. Featuring a minimalist design and compact form, it integrates seamlessly into ceilings while delivering soft, evenly distributed light that enhances the overall atmosphere of the space.

Cira-Stellar downlight offers stable, high-quality illumination with excellent consistency and low glare, making it well suited for areas where visual comfort is essential. Carefully designed optics ensure smooth and uniform light distribution, helping to reduce eye strain and create a calm, welcoming ambiance.

Inspired by Yuji's health-oriented lighting philosophy, Cira-Stellar configured a biologically considerate spectrum that supports comfortable, everyday use. Combining refined design, reliable performance, and a human-centered approach to lighting, Cira-Stellar downlight is an ideal choice for projects that prioritize quality, comfort, and long-term lighting performance.

Specification

(3000K)	Ø 90mm	Ø 106mm	Ø 140mm	Ø 106mm
Wattage	6 W	10 W	20 W	27 W
Luminous flux	400 lm	700 lm	1400 lm	1800 lm
CRI	98	98	98	98
UGR	< 16	< 16	< 16	< 16
Size	Ø90*55 mm	Ø106*65 mm	Ø140*73 mm	Ø178*92 mm
Cut-out	Ø 75 mm	Ø 95 mm	Ø 125 mm	Ø 150 mm
m-DER	0.48			
Color consistency	< 3-SDCM			
Timing	Relax, Entertainment			
Flicker free	Yes			
Biological Safety	RG0			
Mounting options	Recessed-mounted			
Control options	2.4G panel, App, DALI※, CASAMBI			
IP options	IP20, IP44			
Lifetime	50000h - L70 - B10			

Catalog Number

Example: L8427791.1210

Series	Subseries	Wattage	Beam angle	Control options	Finish	System Separator	Lighting options / CCT Range
L8	1 2.5"	06 6 W	7 70°	4 DALI ※ 5 CASAMBI 9 2.4G & App	1 Black	·	OP1: 27 2700K 65 6500K
	2 3"	10 10 W					OP2: 12 1250K 30 3000K
	3 4"	20 20 W					OP3: 12 1250K 65 6500K
	4 6"	27 27 W					OP4: 12 1250K 10 10000K+

※ DALI control supports CCT modes only for Option 1 and Option 2.