



WED-22 ET2

High spin washers



EASY TOUCH 2

7" touch screen, user-friendly and fully programmable
Connection USB. Free software online for programming, telemetry, data analysis...
Videos display (ads, instructions...)
37 available languages
8 dosing signals as standard



G FACTOR

High G factor: reduced residual moisture, reduced drying time, energy savings



EFFICIENCY

Optimized consumption: automatic or manual adjustment of water levels and detergents according to the load
Water Saving system: 3 configurable levels of savings
Ready for water recovery tanks AQUABAC



VERSATILITY

ELECTRIC <> HOT WATER
MAKE TO ORDER: possibility to customize
WET CLEANING as standard



CONNECTIVITY

Communication Danube Online - IoT as standard
Remote technical service
Management of laundry
Multi-payment system



ERGONOMICS

Big aluminium door
Easy door lock system




MAINTENANCE

Hinged panel: easy access to parts
Technical menu: statistics, errors...



OTHERS

Free standing: no anchoring to the floor
Stainless steel vat and drum, skinplate outer casing
3 water inlets
Detergents box with compartments
Imbalance controlled by frequency inverter
CE standards and KIWA for REG4 standards



OPTIONS


- Dosing pumps kit DQ-2
- RT Ready for AQUABAC XL conn. 3/4" for washers WEN/WED-11/14/18/22/28
- Additional dosing pump DB-1
- DD Double drain kit WED-14-18-22
- NC Normally closed valve WED-18/22
- Kit WATERMARK Australia
- RC AQUA FLOW water recirculation kit WED-22 (not available with AQUABAC)
- LG Level feet kit WED-11 to 28
- WS weighing system WED-11 to 45C (additional 6 dosing signals included)
- XD 6 extra dosing signals card WED-11-45C
- SG Silicon gasket WED-18-22-28
- RD reverse door opening
- TR Protected board ET2 for WED-11-45C (standard on 60 to 120 kg models)
- Steam kit WED-11 to 22 (to transform E or HW models to steam)
- Mops plinth stainless steel WED-18/22
- Mops plinth skinplate WED-18/22
- Self plinth same height of machine stainless steel WED-18/22
- Self plinth same height of machine skinplate WED-18/22
- Ergonomic plinth stainless steel WED-18/22
- Ergonomic plinth skinplate WED-18/22
- 440V 3~ (No N) 50/60 Hz 22
- SSC Stainless steel outer casing WED-22
- SSF Stainless steel front panel WED-22
- IoT licence - Danube Online
- Several payment systems for self-service
- UD Kit temporized door opening WED-WEN

DRUM		UNIT.		WED-22 ET2	
Capacity 1/9		Kg		25	
Capacity 1/10		Kg		22	
Volume		l		220	
Diameter		mm		700	
Depth		mm		560	
GENERAL DETAILS					
Washing speed / Spining speed		r.p.m.		47 / 1.071	
G Factor		-		450	
Maximum force transmitted		KN		4,12 ±1,4	
Frequency-dynamic force		Hz		16	
Noise level		dB		< 70	
Coin laundry version		-		YES	
Double drain		-		OPT.	
Weighing system		-		OPT.	
Tilting system		-		NO	
DOOR					
Height door bottom		mm		450	
Diameter		mm		460	
POWER					
Motor		kW		2,2	
Electric heating power		kW		12	
Total electric power (electric model)		kW		12,75	
Total electric power (hw, steam model)		barG		2,2	
CONNECTIONS				E	HW/S
Tension 110V - I + N + T		Nº x mm² / A		-	-
Tension 230V - I + N + T		Nº x mm² / A		2x16+T - 63A	2x1,5+T - 16A
Tension 230V - III + T		Nº x mm² / A		3X6+T - 40A	-
Tension 400V - III + N + T		Nº x mm² / A		4x4+T - 32A	-
Steam inlet (Steam model)		inch		1/2"	1/2"
Maximum steam consumption (Steam model)		Kg/h		12	
Water inlet		inch		3/4"	
Water main pressuer		Kgs/cm²		2-4	
Maximum water consumption*		Lit/h		118,3*	
Drain		mm/inch		3"	
Drainage capacity		Lit/min		200	
DIMENSIONS / PACKING DIMENSIONS					
Net Width/Gross width		mm		884 / 945	
Net Depth/Gross depth		mm		1.003 / 1.115	
Net Height / Gross height		mm		1.405 / 1.680	
Net weight / Gross weight		kg		360 / 403,5	
Volume		m³		1,77	

* Program number 20: WED-11 to WED-80C at 75% load /WED-100C and 120C at 100% load.

** 400V version / 230V version





1. Soap dispenser
2. Emergency stop
3. USB port
4. Drain
5. Electric connection to liquid soap pumps
6. Electrical connection
7. Main switch
8. Auxiliar water inlet
9. Hot water inlet
10. Equipotential connection
11. Cold water inlet
12. Blur output / water overload
13. Liquid soap connection
14. Steam connection
15. Ethernet port

		A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	CGY	CGZ
WED-18	mm	884	913	1 405	450	460	95	380	1 135	1 303	1 138	1 322	1 207	61	74	101	429	509	802	640	348	814	772	1 303	569	1 297	464	702
WED-22	mm	884	1 003	1 405	450	460	95	380	1 135	1 303	1 138	1 322	1 207	61	74	101	429	509	802	640	348	814	772	1 303	569	1 297	464	747