

Model	CE	US - MY	CSA	AGA
Heating area per unit (m ²)	230 - 370	255 - 409	230 - 370	255 - 409
Heat output				
Direct spark ignition (kW)	66.6	73.3	66.0 (LP) 59.0 (NG)	73.3
Gas consumption (maximum) direct spark ignition				
LP gas (m ³ /h)	2.46	2.71	2.40	7.13
Natural gas m ³ /h	6.41	6.68	6.05	6.57
Gas pressure requirements (measured at pressure tap on valve with unit running)				
LP gas (mbar)	37.0	27.5	27.5	27.5
Natural gas (mbar)	20.0	17.5	17.5	17.5
Heater size, weight & assembly information*				
Weight per complete unit (kg)	57	57	57	57
Height (cm)	76	76	76	76
Length (cm)	62	62	62	62
Width (cm)	48	48	48	48
Minimum clearance to combustibles				
Sides of heater (cm)	50	50	50	50
Above heater (cm)	50	50	50	50
Below heater (cm)	50	50	50	50
Exhaust outlet (cm)	300	300	300	300
Control options (electrical requirements - Direct spark)				
Electrical requirements	230 V AC, 50 Hz	120/220/240 V AC, 50 or 60 Hz		230 AC, 50 Hz

*Shen Turbo CE Outdoor: inclusive Outside mounting kit: 76 kg

The policy of Roxell is one of continuous product improvement. We reserve the right to alter specifications without prior notice. Heating products should be installed only in accordance with local laws, codes and regulations.

These products are not for residential use, for agricultural use only. Gas pipe layout assistance is available to customers through authorized distributors. Specific, certified models are available for various countries, where required. Customer / distributor need to check if Roxell has a certified model for the country of installation.

All models meet stringent standards for low carbon monoxide.