



Cost-effective solution for single-path connectivity.

<b>Housing Material:</b>	ABS Plastic – Green
<b>Dimensions:</b>	108mm (h) x 15.5mm (d) x 80mm (w)
<b>Weight:</b>	80g
<b>Operating Environment:</b>	Operating Temperature: 0 - 50 °C Operating Humidity: 15% to 85% non-condensing
<b>Communication Options:</b>	Dual SIM 4G CAT M1
<b>Supported 4G LTE Bands:</b>	CAT M1 – B3(1800), B28(700)
<b>Antenna:</b>	1 x Triple Band 4G
<b>Power:</b>	8-15V DC Terminal Supply Standby Consumption: 0.04A @ 13.8VDC Transmitting Consumption: 0.19A @ 13.8VDC
<b>Dial Capture Modem:</b>	Alarm Panel Dialler supporting DTMF tone dialling and line fault detection
<b>Serial Port:</b>	High-speed RS232 Interface
<b>Auxiliary Input:</b>	3 x 24hr inputs – state change detection every second EOL 3.3K
<b>Auxiliary Output:</b>	3 x Open-Collector outputs @ 50mA (max) Function control using Atlas Web Portal and/or Pocket Secure Mobile App
<b>Data Security:</b>	AES128 Encryption, ISO27001:2022
<b>Mounting:</b>	Magnets DIN Rail Mount Kit (Sold Separately)
<b>Warranty:</b>	2 years (from date of activation)



### Contact Us:

T: 1300 55 66 43  
E: [sales@permaconn.com](mailto:sales@permaconn.com)  
W: [permaconn.com](http://permaconn.com)