



|                                                                                                                    |                                                      |
|--------------------------------------------------------------------------------------------------------------------|------------------------------------------------------|
| <b>APPLICATION</b> ANWENDUNG / APPLICATION / TOEPASSING                                                            | <b>LANDSCAPING</b>                                   |
| <b>PRODUCTION METHOD</b> HERSTELLUNGSVERFAHREN / MODE DE FABRICATION / PRODUCTIEPROCES                             | <b>TUFTED</b>                                        |
| <b>FIBRE</b> FASER / FIBRE / VEZEL / FIBRA / FIBRA                                                                 | <b>67% PE &amp; 33% PP   DTEX PE 4500 + PP 2200</b>  |
| <b>PILE HEIGHT</b> POLHÖHE / HAUTEUR DU VELOURS / POOLHOOGTE                                                       | <b>±35 MM</b>                                        |
| <b>TOTAL HEIGHT</b> GESAMTHÖHE / HAUTEUR TOTALE / TOTALE HOOGTE                                                    | <b>±37 MM</b>                                        |
| <b>PILE WEIGHT</b> POLEINSATZGEWICHT / POIDS DU VELOURS / POOLGEWICHT                                              | <b>± 992 GR/M<sup>2</sup></b>                        |
| <b>TOTAL WEIGHT</b> GESAMTGEWICHT / POIDS TOTAL / TOTAALGEWICHT                                                    | <b>± 1772 GR/M<sup>2</sup></b>                       |
| <b>GAUGE</b> TUFTTEILUNG / JAUGE / TUFTDELING                                                                      | <b>3/8"</b>                                          |
| <b>STITCHES (10 CM')</b> STICHZAHL / NOMBRE DE POINTS / STEKENAANTAL                                               | <b>± 18 /10CM'</b>                                   |
| <b>STITCHES (M<sup>2</sup>)</b> STICHZAHL / NOMBRE DE POINTS / STEKENAANTAL                                        | <b>± 18900 /M<sup>2</sup></b>                        |
| <b>PRIMARY BACKING</b> TRÄGER / DOSSIER PRIMAIRE / TUFTDOEK                                                        | <b>PP + MESH SCRIM INLAY   ±130 GR/M<sup>2</sup></b> |
| <b>SECONDARY BACKING</b> RÜCKEN / DOSSIER SECONDAIRE / SECUNDAIRE BACKING                                          | <b>LATEX   ±650 GR/M<sup>2</sup></b>                 |
| <b>WATER PERMEABILITY</b> WASSERDURCHLASSIGKEIT / PERMÉABILITÉ / WATERDOORLATENDHEID                               | <b>&gt; 2000 MM/H</b>                                |
| <b>UV-STABILITY</b>                                                                                                | <b>UVB 3000H</b>                                     |
| <b>COLORFASTNESS</b>                                                                                               | <b>GREY SCALE 4-5</b>                                |
| <b>CHLORINE RESISTANCE</b>                                                                                         | <b>GRADE 4 (ISO 105-E03-2010)</b>                    |
| <b>FIRE SAFETY CERTIFICATE + NORM</b>                                                                              | <b>EFL   EN 13501-1:2018</b>                         |
| <b>ROLL WIDTH</b> ROLLBREITE / LARGEUR DES ROULEAUX / ROLBREEDTE                                                   | <b>2 M / 4 M</b>                                     |
| <b>ROLL LENGTH</b> ROLLÄNGE / LONGUEUR DES ROULEAUX / ROLLENGTE                                                    | <b>±30 M</b>                                         |
| <b>UV-WARRANTY   NORTH EUROPE ABOVE PARIS, SOUTH EUROPE BELOW PARIS</b><br>UV-GARANTIE / GARANTIE UV / UV GARANTIE | <b>5</b>                                             |
| <b>PRODUCT WARRANTY</b> PRODUKTGARANTIE / GARANTIE DU PRODUIT / PRODUCTGARANTIE                                    | <b>5 YEARS</b>                                       |

