



APPLICATION ANWENDUNG / APPLICATION / TOEPASSING	LANDSCAPING
PRODUCTION METHOD HERSTELLUNGSVERFAHREN / MODE DE FABRICATION / PRODUCTIEPROCES	TUFTED
FIBRE FASER / FIBRE / VEZEL / FIBRA / FIBRA	66% PE & 34% PP DTEX PE 10900 & PP 5500
PILE HEIGHT POLHÖHE / HAUTEUR DU VELOURS / POOLHOOGTE	±45 MM
TOTAL HEIGHT GESAMTHÖHE / HAUTEUR TOTALE / TOTALE HOOGTE	±47 MM
PILE WEIGHT POLEINSATZGEWICHT / POIDS DU VELOURS / POOLGEWICHT	± 2110 GR/M²
TOTAL WEIGHT GESAMTGEWICHT / POIDS TOTAL / TOTAALGEWICHT	± 3370 GR/M²
GAUGE TUFTTEILUNG / JAUGE / TUFTDELING	3/8"
STITCHES (10 CM') STICHZAHL / NOMBRE DE POINTS / STEKENAANTAL	± 12 / 10CM'
STITCHES (M²) STICHZAHL / NOMBRE DE POINTS / STEKENAANTAL	± 12600 / M²
PRIMARY BACKING TRÄGER / DOSSIER PRIMAIRE / TUFTDOEK	PP + FLEECE ±160 GR/M²
SECONDARY BACKING RÜCKEN / DOSSIER SECONDAIRE / SECUNDAIRE BACKING	LATEX ±1100 GR/M²
WATER PERMEABILITY WASSERDURCHLASSIGKEIT / PERMÉABILITÉ / WATERDOORLATENDHEID	> 2000 MM/H
UV-STABILITY	UVB 3000H
COLORFASTNESS	GREY SCALE 4-5
CHLORINE RESISTANCE	GRADE 4 (ISO 105-E03-2010)
FIRE SAFETY CERTIFICATE + NORM	
ROLL WIDTH ROLLBREITE / LARGEUR DES ROULEAUX / ROLBREEDTE	2M / 4 M
ROLL LENGTH ROLLÄNGE / LONGUEUR DES ROULEAUX / ROLLENGTE	±25 M
UV-WARRANTY NORTH EUROPE ABOVE PARIS, SOUTH EUROPE BELOW PARIS UV-GARANTIE / GARANTIE UV / UV GARANTIE	NORTHERN EUROPE: 8 YEARS / SOUTHERN EUROPE: 5 YEARS
PRODUCT WARRANTY PRODUKTGARANTIE / GARANTIE DU PRODUIT / PRODUCTGARANTIE	10 YEARS

