



APPLICATION ANWENDUNG / APPLICATION / TOEPASSING	LANDSCAPING
PRODUCTION METHOD HERSTELLUNGSVERFAHREN / MODE DE FABRICATION / PRODUCTIEPROCES	TUFTED
FIBRE FASER / FIBRE / VEZEL / FIBRA / FIBRA	74% PE 26% PP DTEX PE 9200 & PP 3300
PILE HEIGHT POLHÖHE / HAUTEUR DU VELOURS / POOLHOOGTE	±42 MM
TOTAL HEIGHT GESAMTHÖHE / HAUTEUR TOTALE / TOTALE HOOGTE	±44 MM
PILE WEIGHT POLEINSATZGEWICHT / POIDS DU VELOURS / POOLGEWICHT	± 1316 GR/M²
TOTAL WEIGHT GESAMTGEWICHT / POIDS TOTAL / TOTAALGEWICHT	± 2246 GR/M²
GAUGE TUFTTEILUNG / JAUGE / TUFTDELING	3/8"
STITCHES (10 CM') STICHZAHL / NOMBRE DE POINTS / STEKENAANTAL	± 10,5 / 10CM'
STITCHES (M²) STICHZAHL / NOMBRE DE POINTS / STEKENAANTAL	± 11025 / M²
PRIMARY BACKING TRÄGER / DOSSIER PRIMAIRE / TUFTDOEK	PP+ MESH SCRIM INLAY ±130 GR/M²
SECONDARY BACKING RÜCKEN / DOSSIER SECONDAIRE / SECUNDAIRE BACKING	LATEX ±800 GR/M²
WATER PERMEABILITY WASSERDURCHLASSIGKEIT / PERMÉABILITÉ / WATERDOORLATENDHEID	>2000 MM/H
UV-STABILITY	UVB 3000H
COLORFASTNESS	GREY SCALE 4-5
CHLORINE RESISTANCE	GRADE 4 (ISO 105-E03-2010)
FIRE SAFETY CERTIFICATE + NORM	EFL EN 13501-1:2018
ROLL WIDTH ROLLBREITE / LARGEUR DES ROULEAUX / ROLBREEDTE	2 M / 4 M
ROLL LENGTH ROLLÄNGE / LONGUEUR DES ROULEAUX / ROLLENGTE	±ON REQUEST M
UV-WARRANTY NORTH EUROPE ABOVE PARIS, SOUTH EUROPE BELOW PARIS UV-GARANTIE / GARANTIE UV / UV GARANTIE	NORTHERN EUROPE: 8 YEARS / SOUTHERN EUROPE: 5 YEARS
PRODUCT WARRANTY PRODUKTGARANTIE / GARANTIE DU PRODUIT / PRODUCTGARANTIE	8 YEARS

