

WORLD CLASS SOLUTIONS**19" RACK MOUNT
NEMA 4X - UL LISTED
NETWORK ENCLOSURES****304 & 316L Stainless Steel
Washdown / Weatherproof
Climate Control Options****NEMACO**
EXCELLENT ENCLOSURES**19" RACKMOUNT APPLICATIONS:**

NEMACO offers exceptional and rugged indoor & outdoor server rack network enclosures with industry standard 19" EIA adjustable rack rails for electronic equipment modules. The 19" rackmount enclosures and cabiners are designed for indoor & outdoor all weather conditions including the hot desert sun, heavy wet rain and freezing cold weather snow storms. Nemaco 19" rack mount enclosures have been installed for security, surveillance, radar systems, SCADA control systems, satellite telecom, power plants, fiber optic systems and data acquisition systems for many industries, commercial and military applications.

INDUSTRY STANDARDS:

- UL 50 and UL 50E; File Number E507642
- cUL listed per CSA C22.2 No. 94; File Number E507642
- CSA C22.2 No. 94.1-15 and 94.2-15
- NEMA/IEE: Types 4, 4X, and 12
- IEC 60529 Type IP66

**STANDARD FEATURES:**

- Easy access front and rear doors provide great quick access for maintenance, replace, and repair of equipment.
- 2-post rackrails are standard for front door enclosure.
- 4-post rackrails are standard for front and rear door enclosure.
- 19" rackrails are designed to be fully adjustable in sliding tracks given flexibility setup.
- 19" rackrails come standard with #10-32 tapped holes.
- 3PT latch SS padlock handles are easy for everyday use.
- All seams are fully welded and ground smooth.
- Ground studs come standard on enclosure's door and body providing proper bonding and grounding.
- White, 61 Gray, 70 Gray, and Black powdercoat colors are standard colors.
- Standard 1/2" thick (R3.2) Radiant Barrier Insulation provides good thermal protection.

ENCLOSURE SPECIFICATIONS:

- NEMA 4X Gasket Door Seal for Water Resistance
- NEMA 4X Rated Door Hardware & Latches
- Precision Fit Door for Gasket Seal & Easy Turn Latch
- Continuous Welded Enclosure Corner Seams
- 12 gauge steel used on 60" tall and above enclosures
- 14 gauge steel used on below 60" tall enclosures
- EIA Standard Rack rails made of coated 12 gauge steel
- #10-32 tapped holes on rack rails (powder coated)
- 1/4-20 ground studs on enclosure's door and body
- Foam-in-place gasket with 1.25" extra wide
- Heavy duty 3pt. latch padlock handle
- Heavy duty lifting pads welded top

ACCESSORIES and MODIFICATIONS:

- 1,000 to 20,000 BTUH SS air-conditioned units
- 92 to 350 CFM SS filter fans
- A/C service hatch door
- Top and side sunshield cover
- Removable lifting pads
- Removable door hinge
- SS Key lockable handle
- Heavy duty Stainless rackrails
- 3/8 Square mounting rack holes
- 3/4" thk. (R5) and 1" thk. (R6) Radiant Insulation
- Rack shelves, Drawers, and supports
- Rack hardware, high point screw and cage nuts
- 19" Rack copper busbar
- Vertical rack PDU
- Custom powder coat colors
- Clear window kit (Non-UL option)
- Access cover plate with holes and cutouts
- Quad outlet box with receptacles
- Door stopper, 135 degree opening
- Door tamper switch
- Print pocket
- External mounting brackets
- Floor leg kit and caster wheels

NEMA 4X - 316 STAINLESS STEEL ENCLOSURES**Sample Enclosure specification**

Part# N4X422430-FS2DS619
 UL listed - NEMA 4X Outdoor Enclosure
 Enclosure type: Free-Standing Cabinet
 Dim. 42" H x 24" W x 36" D, 22U
 Material: 316 Stainless Steel
 Material Thickness: 14 ga.
 Front and rear hinged door, cont. hinge
 (2) Lifting eyes, welded
 (2) Pad lockable handles, 3 pt latch
 (4) 19" adjustable rails, SS, #10-32 tapped
 1/2" (R3.2) Radiant Barrier Insulation
 2" Floor mounting kit, welded
 NEMA 4 - 4,000 BTUH 110V 60 Hz
 Part# NE0401264XL1C6, 5-Year Warranty.
 (L1) 316SS Unit Shell
 (C6) C-Level Corrosion Protection

**316 STAINLESS ENCLOSURE STANDARD****FEATURES:**

- Heavy duty 316SS lifting pads
- NEMA 4X gasket door seal for water resistance
- NEMA 4X rated door latch padlock handle
- Continuous welded enclosure corner seams
- Continuous 316SS door hinge
- 19" EIA 12 ga. standard rack rails
- #10-32 tapped holes on rack rails (powder coated)
- 1/4-20 ground studs on enclosure's door and body

ACCESSORIES:

- A/C service hatch door
- Top and side sunshield cover
- SS Key lockable handle
- Heavy duty Stainless rackrails
- Door stopper, 135 degree opening
- External mounting brackets

Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front	16D	N4X242416-FS1DS619	24	24	16	14.5	19" EIA	12 RU	316SS	14 ga.	#4 Grain	83.19
Front		N4X302416-FS1DS619	30	24	16	14.5	19" EIA	15 RU	316SS	14 ga.	#4 Grain	94.56
Front		N4X362416-FS1DS619	36	24	16	14.5	19" EIA	18 RU	316SS	14 ga.	#4 Grain	106.71
Front		N4X422416-FS1DS619	42	24	16	14.5	19" EIA	22 RU	316SS	14 ga.	#4 Grain	119.2
Front		N4X482416-FS1DS619	48	24	16	14.5	19" EIA	25 RU	316SS	14 ga.	#4 Grain	134.65
Front		N4X542416-FS1DS619	54	24	16	14.5	19" EIA	29 RU	316SS	14 ga.	#4 Grain	145.17
Front		N4X602416-FS1DS619	60	24	16	14.5	19" EIA	32 RU	316SS	14 ga.	#4 Grain	157.32
Front		N4X662416-FS1DS619	66	24	16	14.5	19" EIA	36 RU	316SS	12 ga.	#4 Grain	226.52
Front		N4X722416-FS1DS619	72	24	16	14.5	19" EIA	39 RU	316SS	12 ga.	#4 Grain	240.17
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front	20D	N4X242420-FS1DS619	24	24	20	18.5	19" EIA	12 RU	316SS	14 ga.	#4 Grain	95
Front		N4X302420-FS1DS619	30	24	20	18.5	19" EIA	15 RU	316SS	14 ga.	#4 Grain	107.46
Front		N4X362420-FS1DS619	36	24	20	18.5	19" EIA	18 RU	316SS	14 ga.	#4 Grain	120.7
Front		N4X422420-FS1DS619	42	24	20	18.5	19" EIA	22 RU	316SS	14 ga.	#4 Grain	134.27
Front		N4X482420-FS1DS619	48	24	20	18.5	19" EIA	25 RU	316SS	14 ga.	#4 Grain	150.8
Front		N4X542420-FS1DS619	54	24	20	18.5	19" EIA	29 RU	316SS	14 ga.	#4 Grain	162.41
Front		N4X602420-FS1DS619	60	24	20	18.5	19" EIA	32 RU	316SS	14 ga.	#4 Grain	175.64
Front		N4X662420-FS1DS619	66	24	20	18.5	19" EIA	36 RU	316SS	12 ga.	#4 Grain	252.54
Front		N4X722420-FS1DS619	72	24	20	18.5	19" EIA	39 RU	316SS	12 ga.	#4 Grain	267.7
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front	24D	N4X242424-FS1DS619	24	24	24	22.5	19" EIA	12 RU	316SS	14 ga.	#4 Grain	108.25
Front		N4X302424-FS1DS619	30	24	24	22.5	19" EIA	15 RU	316SS	14 ga.	#4 Grain	121.79
Front		N4X362424-FS1DS619	36	24	24	22.5	19" EIA	18 RU	316SS	14 ga.	#4 Grain	136.11
Front		N4X422424-FS1DS619	42	24	24	22.5	19" EIA	22 RU	316SS	14 ga.	#4 Grain	150.77
Front		N4X482424-FS1DS619	48	24	24	22.5	19" EIA	25 RU	316SS	14 ga.	#4 Grain	168.38
Front		N4X542424-FS1DS619	54	24	24	22.5	19" EIA	29 RU	316SS	14 ga.	#4 Grain	181.07
Front		N4X602424-FS1DS619	60	24	24	22.5	19" EIA	32 RU	316SS	14 ga.	#4 Grain	195.39
Front		N4X662424-FS1DS619	66	24	24	22.5	19" EIA	36 RU	316SS	12 ga.	#4 Grain	279.99
Front		N4X722424-FS1DS619	72	24	24	22.5	19" EIA	39 RU	316SS	12 ga.	#4 Grain	296.68
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front	30D	N4X242430-FS1DS619	24	24	30	28.5	19" EIA	12 RU	316SS	14 ga.	#4 Grain	125.97
Front		N4X302430-FS1DS619	30	24	30	28.5	19" EIA	15 RU	316SS	14 ga.	#4 Grain	141.14
Front		N4X362430-FS1DS619	36	24	30	28.5	19" EIA	18 RU	316SS	14 ga.	#4 Grain	157.09
Front		N4X422430-FS1DS619	42	24	30	28.5	19" EIA	22 RU	316SS	14 ga.	#4 Grain	173.37
Front		N4X482430-FS1DS619	48	24	30	28.5	19" EIA	25 RU	316SS	14 ga.	#4 Grain	192.6
Front		N4X542430-FS1DS619	54	24	30	28.5	19" EIA	29 RU	316SS	14 ga.	#4 Grain	206.92
Front		N4X602430-FS1DS619	60	24	30	28.5	19" EIA	32 RU	316SS	14 ga.	#4 Grain	222.87
Front		N4X662430-FS1DS619	66	24	30	28.5	19" EIA	36 RU	316SS	12 ga.	#4 Grain	319.03
Front		N4X722430-FS1DS619	72	24	30	28.5	19" EIA	39 RU	316SS	12 ga.	#4 Grain	337.99

NEMA 4X - 19" Rackmount - Free Standing Enclosures**304 / 316L Stainless Steel - 1 or 2 Door Cabinet Design**

Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front/Rear	24D	N4X242424-FS2DS619	24	24	24	21	19" EIA	12 RU	316SS	14 ga.	#4 Grain	118.22
Front/Rear		N4X302424-FS2DS619	30	24	24	21	19" EIA	15 RU	316SS	14 ga.	#4 Grain	133.12
Front/Rear		N4X362424-FS2DS619	36	24	24	21	19" EIA	18 RU	316SS	14 ga.	#4 Grain	148.8
Front/Rear		N4X422424-FS2DS619	42	24	24	21	19" EIA	22 RU	316SS	14 ga.	#4 Grain	164.95
Front/Rear		N4X482424-FS2DS619	48	24	24	21	19" EIA	25 RU	316SS	14 ga.	#4 Grain	187.21
Front/Rear		N4X542424-FS2DS619	54	24	24	21	19" EIA	29 RU	316SS	14 ga.	#4 Grain	201.4
Front/Rear		N4X602424-FS2DS619	60	24	24	21	19" EIA	32 RU	316SS	14 ga.	#4 Grain	217.07
Front/Rear		N4X662424-FS2DS619	66	24	24	21	19" EIA	36 RU	316SS	12 ga.	#4 Grain	306.34
Front/Rear		N4X722424-FS2DS619	72	24	24	21	19" EIA	39 RU	316SS	12 ga.	#4 Grain	324.6
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front/Rear	30D	N4X242430-FS2DS619	24	24	30	27	19" EIA	12 RU	316SS	14 ga.	#4 Grain	135.95
Front/Rear		N4X302430-FS2DS619	30	24	30	27	19" EIA	15 RU	316SS	14 ga.	#4 Grain	152.47
Front/Rear		N4X362430-FS2DS619	36	24	30	27	19" EIA	18 RU	316SS	14 ga.	#4 Grain	169.77
Front/Rear		N4X422430-FS2DS619	42	24	30	27	19" EIA	22 RU	316SS	14 ga.	#4 Grain	187.55
Front/Rear		N4X482430-FS2DS619	48	24	30	27	19" EIA	25 RU	316SS	14 ga.	#4 Grain	211.43
Front/Rear		N4X542430-FS2DS619	54	24	30	27	19" EIA	29 RU	316SS	14 ga.	#4 Grain	227.25
Front/Rear		N4X602430-FS2DS619	60	24	30	27	19" EIA	32 RU	316SS	14 ga.	#4 Grain	244.54
Front/Rear		N4X662430-FS2DS619	66	24	30	27	19" EIA	36 RU	316SS	12 ga.	#4 Grain	345.38
Front/Rear		N4X722430-FS2DS619	72	24	30	27	19" EIA	39 RU	316SS	12 ga.	#4 Grain	365.91
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front/Rear	36D	N4X242436-FS2DS619	24	24	36	33	19" EIA	12 RU	316SS	14 ga.	#4 Grain	153.67
Front/Rear		N4X302436-FS2DS619	30	24	36	33	19" EIA	15 RU	316SS	14 ga.	#4 Grain	171.82
Front/Rear		N4X362436-FS2DS619	36	24	36	33	19" EIA	18 RU	316SS	14 ga.	#4 Grain	190.74
Front/Rear		N4X422436-FS2DS619	42	24	36	33	19" EIA	22 RU	316SS	14 ga.	#4 Grain	210.15
Front/Rear		N4X482436-FS2DS619	48	24	36	33	19" EIA	25 RU	316SS	14 ga.	#4 Grain	235.66
Front/Rear		N4X542436-FS2DS619	54	24	36	33	19" EIA	29 RU	316SS	14 ga.	#4 Grain	253.1
Front/Rear		N4X602436-FS2DS619	60	24	36	33	19" EIA	32 RU	316SS	14 ga.	#4 Grain	272.02
Front/Rear		N4X662436-FS2DS619	66	24	36	33	19" EIA	36 RU	316SS	12 ga.	#4 Grain	384.41
Front/Rear		N4X722436-FS2DS619	72	24	36	33	19" EIA	39 RU	316SS	12 ga.	#4 Grain	407.22
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front/Rear	42D	N4X242442-FS2DS619	24	24	42	39	19" EIA	12 RU	316SS	14 ga.	#4 Grain	171.39
Front/Rear		N4X302442-FS2DS619	30	24	42	39	19" EIA	15 RU	316SS	14 ga.	#4 Grain	191.17
Front/Rear		N4X362442-FS2DS619	36	24	42	39	19" EIA	18 RU	316SS	14 ga.	#4 Grain	211.72
Front/Rear		N4X422442-FS2DS619	42	24	42	39	19" EIA	22 RU	316SS	14 ga.	#4 Grain	232.75
Front/Rear		N4X482442-FS2DS619	48	24	42	39	19" EIA	25 RU	316SS	14 ga.	#4 Grain	259.88
Front/Rear		N4X542442-FS2DS619	54	24	42	39	19" EIA	29 RU	316SS	14 ga.	#4 Grain	278.95
Front/Rear		N4X602442-FS2DS619	60	24	42	39	19" EIA	32 RU	316SS	14 ga.	#4 Grain	299.5
Front/Rear		N4X662442-FS2DS619	66	24	42	39	19" EIA	36 RU	316SS	12 ga.	#4 Grain	423.44
Front/Rear		N4X722442-FS2DS619	72	24	42	39	19" EIA	39 RU	316SS	12 ga.	#4 Grain	448.53



**EASY ACCESS - NEMA 4X SERVER RACK ENCLOSURE WITH
29RU AIR-CONDITIONED NEMACO PART# N4X542430-FS2DS619**

NEMA 4X - 304 STAINLESS STEEL ENCLOSURES**Sample Enclosure specification**

Part# N4X603036-FS2DS419

UL listed - NEMA 4X Outdoor Enclosure

Enclosure type: Free-Standing Cabinet

Dim. 60" H x 30" W x 36" D, 32U Height

Material: 304 Stainless Steel

Material Thickness: 12 ga.

Front and rear hinged door, cont. hinge

(2) Lifting eyes, welded

(2) Pad lockable handles, 3 pt latch

(4) 19" adjustable rails, #10-32 tapped

1/2" (R3.2) Radiant Barrier Insulation

(1) 8x16 Access cover plate, 6x4 cutout

NEMA 4 - 6,000 BTUH 230V 60 Hz

Part# NE0602364XB1C6, 5-Year Warranty.

(B1) Remote Controller, Low Voltage

(C6) C-Level Corrosion Protection

**316 STAINLESS ENCLOSURE STANDARD****FEATURES:**

- Heavy duty 316SS lifting pads
- NEMA 4X gasket door seal for water resistance
- NEMA 4X rated door latch padlock handle
- Continuous welded enclosure corner seams
- Continuous 316SS door hinge
- 19" EIA 12 ga. standard rack rails
- #10-32 tapped holes on rack rails (powder coated)
- 1/4-20 ground studs on enclosure's door and body

ACCESSORIES:

- A/C service hatch door
- Top and side sunshield cover
- SS Key lockable handle
- Heavy duty Stainless rackrails

Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front	16D	N4X242416-FS1DS419	24	24	16	14.5	19" EIA	12 RU	304SS	14 ga.	#4 Grain	83.19
Front		N4X302416-FS1DS419	30	24	16	14.5	19" EIA	15 RU	304SS	14 ga.	#4 Grain	94.56
Front		N4X362416-FS1DS419	36	24	16	14.5	19" EIA	18 RU	304SS	14 ga.	#4 Grain	106.71
Front		N4X422416-FS1DS419	42	24	16	14.5	19" EIA	22 RU	304SS	14 ga.	#4 Grain	119.2
Front		N4X482416-FS1DS419	48	24	16	14.5	19" EIA	25 RU	304SS	14 ga.	#4 Grain	134.65
Front		N4X542416-FS1DS419	54	24	16	14.5	19" EIA	29 RU	304SS	14 ga.	#4 Grain	145.17
Front		N4X602416-FS1DS419	60	24	16	14.5	19" EIA	32 RU	304SS	14 ga.	#4 Grain	157.32
Front		N4X662416-FS1DS419	66	24	16	14.5	19" EIA	36 RU	304SS	12 ga.	#4 Grain	226.52
Front		N4X722416-FS1DS419	72	24	16	14.5	19" EIA	39 RU	304SS	12 ga.	#4 Grain	240.17
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front	20D	N4X242420-FS1DS419	24	24	20	18.5	19" EIA	12 RU	304SS	14 ga.	#4 Grain	95
Front		N4X302420-FS1DS419	30	24	20	18.5	19" EIA	15 RU	304SS	14 ga.	#4 Grain	107.46
Front		N4X362420-FS1DS419	36	24	20	18.5	19" EIA	18 RU	304SS	14 ga.	#4 Grain	120.7
Front		N4X422420-FS1DS419	42	24	20	18.5	19" EIA	22 RU	304SS	14 ga.	#4 Grain	134.27
Front		N4X482420-FS1DS419	48	24	20	18.5	19" EIA	25 RU	304SS	14 ga.	#4 Grain	150.8
Front		N4X542420-FS1DS419	54	24	20	18.5	19" EIA	29 RU	304SS	14 ga.	#4 Grain	162.41
Front		N4X602420-FS1DS419	60	24	20	18.5	19" EIA	32 RU	304SS	14 ga.	#4 Grain	175.64
Front		N4X662420-FS1DS419	66	24	20	18.5	19" EIA	36 RU	304SS	12 ga.	#4 Grain	252.54
Front		N4X722420-FS1DS419	72	24	20	18.5	19" EIA	39 RU	304SS	12 ga.	#4 Grain	267.7
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front	24D	N4X242424-FS1DS419	24	24	24	22.5	19" EIA	12 RU	304SS	14 ga.	#4 Grain	108.25
Front		N4X302424-FS1DS419	30	24	24	22.5	19" EIA	15 RU	304SS	14 ga.	#4 Grain	121.79
Front		N4X362424-FS1DS419	36	24	24	22.5	19" EIA	18 RU	304SS	14 ga.	#4 Grain	136.11
Front		N4X422424-FS1DS419	42	24	24	22.5	19" EIA	22 RU	304SS	14 ga.	#4 Grain	150.77
Front		N4X482424-FS1DS419	48	24	24	22.5	19" EIA	25 RU	304SS	14 ga.	#4 Grain	168.38
Front		N4X542424-FS1DS419	54	24	24	22.5	19" EIA	29 RU	304SS	14 ga.	#4 Grain	181.07
Front		N4X602424-FS1DS419	60	24	24	22.5	19" EIA	32 RU	304SS	14 ga.	#4 Grain	195.39
Front		N4X662424-FS1DS419	66	24	24	22.5	19" EIA	36 RU	304SS	12 ga.	#4 Grain	279.99
Front		N4X722424-FS1DS419	72	24	24	22.5	19" EIA	39 RU	304SS	12 ga.	#4 Grain	296.68
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front	30D	N4X242430-FS1DS419	24	24	30	28.5	19" EIA	12 RU	304SS	14 ga.	#4 Grain	125.97
Front		N4X302430-FS1DS419	30	24	30	28.5	19" EIA	15 RU	304SS	14 ga.	#4 Grain	141.14
Front		N4X362430-FS1DS419	36	24	30	28.5	19" EIA	18 RU	304SS	14 ga.	#4 Grain	157.09
Front		N4X422430-FS1DS419	42	24	30	28.5	19" EIA	22 RU	304SS	14 ga.	#4 Grain	173.37
Front		N4X482430-FS1DS419	48	24	30	28.5	19" EIA	25 RU	304SS	14 ga.	#4 Grain	192.6
Front		N4X542430-FS1DS419	54	24	30	28.5	19" EIA	29 RU	304SS	14 ga.	#4 Grain	206.92
Front		N4X602430-FS1DS419	60	24	30	28.5	19" EIA	32 RU	304SS	14 ga.	#4 Grain	222.87
Front		N4X662430-FS1DS419	66	24	30	28.5	19" EIA	36 RU	304SS	12 ga.	#4 Grain	319.03
Front		N4X722430-FS1DS419	72	24	30	28.5	19" EIA	39 RU	304SS	12 ga.	#4 Grain	337.99

NEMA 4X - 19" Rackmount - Free Standing Enclosures**304 / 316L Stainless Steel - 1 or 2 Door Cabinet Design**

Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front/Rear	24D	N4X242424-FS2DS419	24	24	24	21	19" EIA	12 RU	304SS	14 ga.	#4 Grain	118.22
Front/Rear		N4X302424-FS2DS419	30	24	24	21	19" EIA	15 RU	304SS	14 ga.	#4 Grain	133.12
Front/Rear		N4X362424-FS2DS419	36	24	24	21	19" EIA	18 RU	304SS	14 ga.	#4 Grain	148.8
Front/Rear		N4X422424-FS2DS419	42	24	24	21	19" EIA	22 RU	304SS	14 ga.	#4 Grain	164.95
Front/Rear		N4X482424-FS2DS419	48	24	24	21	19" EIA	25 RU	304SS	14 ga.	#4 Grain	187.21
Front/Rear		N4X542424-FS2DS419	54	24	24	21	19" EIA	29 RU	304SS	14 ga.	#4 Grain	201.4
Front/Rear		N4X602424-FS2DS419	60	24	24	21	19" EIA	32 RU	304SS	14 ga.	#4 Grain	217.07
Front/Rear		N4X662424-FS2DS419	66	24	24	21	19" EIA	36 RU	304SS	12 ga.	#4 Grain	306.34
Front/Rear		N4X722424-FS2DS419	72	24	24	21	19" EIA	39 RU	304SS	12 ga.	#4 Grain	324.6
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front/Rear	30D	N4X242430-FS2DS419	24	24	30	27	19" EIA	12 RU	304SS	14 ga.	#4 Grain	135.95
Front/Rear		N4X302430-FS2DS419	30	24	30	27	19" EIA	15 RU	304SS	14 ga.	#4 Grain	152.47
Front/Rear		N4X362430-FS2DS419	36	24	30	27	19" EIA	18 RU	304SS	14 ga.	#4 Grain	169.77
Front/Rear		N4X422430-FS2DS419	42	24	30	27	19" EIA	22 RU	304SS	14 ga.	#4 Grain	187.55
Front/Rear		N4X482430-FS2DS419	48	24	30	27	19" EIA	25 RU	304SS	14 ga.	#4 Grain	211.43
Front/Rear		N4X542430-FS2DS419	54	24	30	27	19" EIA	29 RU	304SS	14 ga.	#4 Grain	227.25
Front/Rear		N4X602430-FS2DS419	60	24	30	27	19" EIA	32 RU	304SS	14 ga.	#4 Grain	244.54
Front/Rear		N4X662430-FS2DS419	66	24	30	27	19" EIA	36 RU	304SS	12 ga.	#4 Grain	345.38
Front/Rear		N4X722430-FS2DS419	72	24	30	27	19" EIA	39 RU	304SS	12 ga.	#4 Grain	365.91
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front/Rear	36D	N4X242436-FS2DS419	24	24	36	33	19" EIA	12 RU	304SS	14 ga.	#4 Grain	153.67
Front/Rear		N4X302436-FS2DS419	30	24	36	33	19" EIA	15 RU	304SS	14 ga.	#4 Grain	171.82
Front/Rear		N4X362436-FS2DS419	36	24	36	33	19" EIA	18 RU	304SS	14 ga.	#4 Grain	190.74
Front/Rear		N4X422436-FS2DS419	42	24	36	33	19" EIA	22 RU	304SS	14 ga.	#4 Grain	210.15
Front/Rear		N4X482436-FS2DS419	48	24	36	33	19" EIA	25 RU	304SS	14 ga.	#4 Grain	235.66
Front/Rear		N4X542436-FS2DS419	54	24	36	33	19" EIA	29 RU	304SS	14 ga.	#4 Grain	253.1
Front/Rear		N4X602436-FS2DS419	60	24	36	33	19" EIA	32 RU	304SS	14 ga.	#4 Grain	272.02
Front/Rear		N4X662436-FS2DS419	66	24	36	33	19" EIA	36 RU	304SS	12 ga.	#4 Grain	384.41
Front/Rear		N4X722436-FS2DS419	72	24	36	33	19" EIA	39 RU	304SS	12 ga.	#4 Grain	407.22
Door Access	Encl. Depth	Part Number	H	W	D	Max. Span	Rack Type	Rack U	Material	Matl. Thk.	Std. finish	Encl. Weight
Front/Rear	42D	N4X242442-FS2DS419	24	24	42	39	19" EIA	12 RU	304SS	14 ga.	#4 Grain	171.39
Front/Rear		N4X302442-FS2DS419	30	24	42	39	19" EIA	15 RU	304SS	14 ga.	#4 Grain	191.17
Front/Rear		N4X362442-FS2DS419	36	24	42	39	19" EIA	18 RU	304SS	14 ga.	#4 Grain	211.72
Front/Rear		N4X422442-FS2DS419	42	24	42	39	19" EIA	22 RU	304SS	14 ga.	#4 Grain	232.75
Front/Rear		N4X482442-FS2DS419	48	24	42	39	19" EIA	25 RU	304SS	14 ga.	#4 Grain	259.88
Front/Rear		N4X542442-FS2DS419	54	24	42	39	19" EIA	29 RU	304SS	14 ga.	#4 Grain	278.95
Front/Rear		N4X602442-FS2DS419	60	24	42	39	19" EIA	32 RU	304SS	14 ga.	#4 Grain	299.5
Front/Rear		N4X662442-FS2DS419	66	24	42	39	19" EIA	36 RU	304SS	12 ga.	#4 Grain	423.44
Front/Rear		N4X722442-FS2DS419	72	24	42	39	19" EIA	39 RU	304SS	12 ga.	#4 Grain	448.53



ALL RACKMOUNT SERVER ENCLOSURES PROVIDE FULL ACCESS
39RU SS AIR-CONDITIONED NEMA 4X ENCLOSURE
NEMACO PART# N4X722442-FS2DS419