

## **ENERGY SWITCH**

**Battery-free Wireless Switch** 

for Knowing Act Automatic Swing Door Applications



Generate ENERGY with a push! These wireless and battery-free push plates from OPTEX feature Energy Harvesting Technology. The energy captured from pushing the plate powers the transmitter, which sends a wireless signal to the re- ceiver to open the swing doors. You will never again have to replace a battery or run a wire for your door switch. The Eco Friendly OPTEX Energy Switch combines the best features of wired and wireless switches.

www.optexamerica.com



## **Features & Benefits**






- Less maintenance
- No battery
- Don't need to wire
- Cut installation time
- Eco friendly

Model	4SHSS	4RHSS	11100	1/1100
		6RHSS	JHSS	VHSS
Size	4 1/2" (114 mm) Square	4 1/2" (114 mm) Round	1 1/2" x 4 1/4" (38 x 108 mm)	4 1/2" x 4 1/2" (114 x 114 mm)
		6" (153 mm) Round		
Design	PRESS TO OPERATE DOOR	PRESS TO OPERATE DOOR	PUSH TO OPEN	PUSH PUSH OPEN OPEN

<sup>\*</sup> Each above design without text. (4SWSS, 4RWSS, 6RWSS, JWSS, VWSS)

## **Dimensions**



## **Specifications**

Model	NRG-TX1	
Detection method	Radio frequency receiver	
Frequency	2.4 GHz	
Radiated power	+2.0 dBm	
Power supply	Energy harvesting	
Operating temperature	-13°F to +140°F (-25°C to 80°C)	
Accessories	Manual, 2 Mounting screws	
<b>RX</b> Model	S-COR-O	
Detection method	Radio frequency receiver	
requency	2.4 GHz	
Power supply	12 to 24V AC/DC	
Current draw	<1.0 W	
Output	Form C Relay	
Output hold time	0.5 sec. to 30 sec. (Adjustable)	
Operating temperature	-22°F to +158°F (-30°C to 70°C)	
Programmable transmitters	Max. 10 units	
Veight	4 oz. (113 g)	
Accessories	Manual, 2 Mounting screws,	
	1 velcro supplied (2")	

Parts list	Description	
NRG-4SHSS(K)	4" sq. Stainless Steel NRG Switch, Blue Handicapped Logo w/ text. Kit includes: (2) NRG-4SHSS, (1) NRG-RX	
NRG-JHSS(K)	2" x 4" Stainless Steel NRG Switch, Blue Handicapped Logo w/ text. Kit includes: (2) NRG-JHSS, (1) NRG-RX	
NRG-4RHSS(K)	4" round Stainless Steel NRG Switch, Blue Handicapped Logo w/ text. Kit includes: (2) NRG-4RHSS, (1) NRG-RX	
NRG-6RHSS(K)	6" round NRG Switch with Blue Handicapped Logo w/ text. Kit includes: (2) NRG-6RHSS, (1) NRG-RX	
NRG-VHSS(K)	4" sq. Vestibule NRG Switch with Blue Handicapped Logo and "Push to Open" text with opposing arrows.  Includes: (1) NRG-VHSS, (2) NRG-4HSS, (2) NRG-RX (Pairing required)	
NRG-4SWSS(K)	4" sq. Stainless Steel NRG Switch, Blue Handicapped Logo. Kit includes: (2) NRG-4SWSS, (1) NRG-RX	
NRG-JWSS(K)	2" x 4" Stainless Steel NRG Switch, Blue Handicapped Logo. Kit includes: (2) NRG-JWSS, (1) NRG-RX	
NRG-4RWSS(K)	4" round Stainless Steel NRG Switch, Blue Handicapped Logo. Kit includes: (2) NRG-4RWSS, (1) NRG-RX	
NRG-6RWSS(K)	6" round NRG Switch with Blue Handicapped Logo. Kit includes: (2) NRG-6RWSS, (1) NRG-RX	
NRG-VWSS(K)	4" sq. Vestibule NRG Switch with Blue Handicapped Logo with opposing arrows. Includes: (1) NRG-VWSS, (2) NRG-4WSS, (2) NRG-RX (Pairing Required)	

F© IC (E









