

## CLEANING &amp; MAINTENANCE · LIVING CERAMICS PORCELAIN

Once placed and grout cleaning equipment is mandatory. Improper cleaning may leave traces of products used in the placement or the protection of the tiles, as cements, resins epoxilicas, grout, waxes or fats. For optimal cleaning after placement for cases of intense and stubborn dirt accumulated over time, and for maintenance, required to use the right products. The following table shows some of the recommendations.

| PRODUCT NAME                                | USEFUL FOR                                                           |
|---------------------------------------------|----------------------------------------------------------------------|
| <u>ACTICHEM PRO NEUTRO</u>                  | Maintenance in general.                                              |
| <u>ACTICHEM POWERSTRIP</u>                  | Waste epoxy, vitrified or resin board.                               |
| <u>ACTICHEM CRETE CLEAN *</u>               | Waste concrete placement, limescale, metals stripes, oxide deposits. |
| <u>LITHOFIN WAX-OFF</u>                     | Candle wax, tree resins, tape residue, tar residue.                  |
| <u>ACTICHEM POWERSTRIP</u>                  | Painted graffiti, spray acrylic, alkyd and synthetic nitros.         |
| <u>ACTICHEM TILE &amp; GROUT CLEANER LF</u> | Drinks, food, fats, oils, rubber, dyes, marker, acrylic paint drops. |

\* Crete Clean: test on a small area first and confirm suitability before use on honed finishes. Always test any product in an inconspicuous area before full application.

## CARING FOR THE WASHBASINS AND BATHROOM UNITS

Ceramic washbasins and countertops, must be cleaned on a regular basis. They are swift and simple to clean, using just a moist microfibre cloth. Detergent can also be used, as per the amount indicated by the manufacturer. Take special care with all joints and follow the instructions of the manufacturer of the grouting material. To make the washbasins easier to clean, there is an opening in the underside, providing access to the channel where the drain is. This facilitates the fitting process and the cleaning of this concealed area. The drainage channel must be more carefully cleaned, using a damp cloth and, if appropriate, a detergent as described above.