

Dry Chemical Powder

Technical Specification

Model	:	GA Series
Brand	:	SIBCA
Approval	:	BSI - Kitemark
Design Standard	:	EN 3
Working Pressure	:	12 Bar
Cylinder Structure	:	Deep-Drawn
Temperature Range	:	-30°C to 60°C
Agent	:	40% ABC Powder (EN615)
Fire Class	:	A, B, and C
Kitemark Certificate No.	:	KM 795300



Features

- Manufacturing in accordance with BS EN3 Standards
- Highly effective on class A, B, C & Electrical fires
- Cylinders are 100% factory tested to 30 bar.
- Squeeze grip valve for comfortable operation
- Nickel plated Brass Valve with reliability and long life.
- Rugged PVC pick up tube enables smooth flow of the extinguishing agent.
- Precision built mechanical pressure gauge.
- Electrostatic powder painting after shot blasting ensures maximum corrosion resistance.

General Technical Information

Model	GA0011	GA0013	GA0015	GA0016	GA0017
Capacity	1Kg	2Kg	4Kg	6Kg	9Kg
Fire Rating	8A 34B C	13A 89B C	27A 183B C	43A 233B C	55A 233B C
Discharge Time	8 Sec	10 Sec	17 Sec	17 Sec	22 Sec

Application

- ABC Dry Powder Extinguishers are used on the different Class of fires
- Class A - Combustible Materials (Wood, Paper & Fabric)
- Class B - Flammable liquids (Gasoline, Oils, Paints, Alcohol)
- Class C - Flammable Gases (Hydrogen, Butane, Methane, Ethylene)
- Electrical Equipment's

Note: Subject to change without prior notice due to products optimization