

Foam

Technical Specification

Model	:	GA Series
Brand	:	SIBCA
Approval	:	BSI - Kitemark
Design Standard	:	EN 3
Working Pressure	:	12 Bar
Cylinder Structure	:	Deep-Drawn
Temperature Range	:	+5°C to 60°C
Agent	:	97% Water & 3% AFFF
Fire Class	:	A and B
Kitemark Certificate No.	:	KM 795300



Features

- Manufacturing in accordance with BS EN3 Standards.
- Highly effective on class A & B fires.
- Cylinders are 100% factory tested to 30 bar.
- Squeeze grip valve for comfortable operation
- Nickel plated Brass Valve with reliability and long life.
- Rugged PVC pick up tube enables smooth flow of the extinguishing agent.
- Precision built mechanical pressure gauge.
- Electrostatic powder painting after shot blasting ensures maximum corrosion resistance.

General Technical Information

Model	GA0031	GA0032
Capacity	6L	9L
Fire Rating	27A / 183 B	34A / 233B
Discharge Time	22 Sec	30 Sec

Application

- Foam Extinguishers are used on the different Class of fires
- Class A - Combustible Materials (Wood, Paper & Fabric)
- Class B - Flammable liquids (Gasoline, Oils, Paints, Alcohol)

Note: Subject to change without prior notice due to products optimization