

Water

Technical Specification

Model	:	GA Series
Brand	:	SIBCA
Approval	:	BSI - Kitemark
Design Standard	:	EN 3
Working Pressure	:	12 Bar
Cylinder Structure	:	Deep-Drawn
Temperature Range	:	+5°C to 60°C
Agent	:	Water
Fire Class	:	A
Kitemark Certificate No.	:	KM 795300

Features

- Simple operation and maintenance.
- Ready for instant use.
- Exceptionally effective on class A fires.
- Cylinder made of special steel to withstand high pressures.
- Cylinders are 100% factory tested to 30 bar.
- Nickel plated brass valve with reliability and long life.
- Precision built mechanical pressure gauges.
- Rugged PVC pick up tube enables smooth flow of the agent.
- Electrostatic powder painting after shot blasting ensures maximum corrosion resistance.
- Internally coated with Polyolefin & thermosetting polymer powder using whirl sintering process.
- Manufacturing in accordance with BS EN3 Standards.
- Highly effective on class A fires.

General Technical Information

Model	GA0041	GA0042
Capacity	6L	9L
Fire Rating	13A	21A
Discharge Time	40 Sec	65 Sec

Application

Water Extinguishers are used on the different Class of fires
Class A - Combustible Materials (Wood, Paper & Fabric)

Note: Subject to change without prior notice due to products optimization

