

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: White ACR EXT Sealer
Trade code: **BA93C01**
UFI: SRXA-Q0YU-J009-5WHE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Surface coating
Uses advised against: N.A.

1.3. Details of the supplier of the safety data sheet

Company: Sirca S.p.A.
Viale Roma, 85
35010 Sandono di Massanzago (PD) - ITALY
Tel. +39 0499322311
Email: safety@sirca.it

1.4. Emergency telephone number

National Poisons Information Service - Medical Toxicology Unit - London - Tel. 0171/6359191
Scottish Poisons Information Bureau - The Royal Infirmary - Edinburgh - Tel. 01/315362298
Welsh National Poisons Unit - Ward West 5 - Llandough Hospital Penarth - Cardiff - Tel. 012/22709901
Poisons Information Centre - Royal Victoria Hospital - Belfast - Tel. 012/32240503
Poisons Information centre - Beaumont Hospital - Dublin - Tel. 0103531/8379964
CAV Policlinico "Umberto I". Roma V.le del Policlinico, 155 161 Telefono 06-49978000
Osp. Niguarda Ca' Granda. Milano Piazza Ospedale Maggiore,3 20162 Telefono 02-66101029

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Flam. Liq. 2	Highly flammable liquid and vapour.
Eye Irrit. 2	Causes serious eye irritation.
Skin Sens. 1A	May cause an allergic skin reaction.
Carc. 2	Suspected of causing cancer.
STOT SE 3	May cause drowsiness or dizziness.
Aquatic Chronic 3	Harmful to aquatic life with long lasting effects.

Adverse physicochemical, human health and environmental effects:
No other hazards

2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

Pictograms and Signal Words



Danger

Hazard statements

H225 Highly flammable liquid and vapour.

H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...
P370+P378	In case of fire: Use CO2, Foam, Chemical powders For extinction.
P403+P235	Store in a well-ventilated place. Keep cool.

Contains

n-butyl acetate	
butanone	
maleic anhydride	
toluene	
Fatty acids, C14-18 and C16-18-unsatd., maleated	May produce an allergic reaction.
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	May produce an allergic reaction.
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	May produce an allergic reaction.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%.

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: White ACR EXT Sealer

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
12.5-20 %	n-butyl acetate	CAS:123-86-4 EC:204-658-1 Index:607-025-00-1	Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	01-2119485493-29-xxxx
3-5 %	butanone	CAS:78-93-3 EC:201-159-0 Index:606-002-00-3	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	01-2119457290-43-xxxx
3-5 %	2-butoxyethyl acetate; butylglycol acetate	CAS:112-07-2 EC:203-933-3 Index:607-038-00-2	Acute Tox. 4, H312; Acute Tox. 4, H332	
3-5 %	xylene [isomer mixture]	CAS:1330-20-7 EC:215-535-7 Index:601-022-00-9	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Eye Irrit. 2, H319; STOT SE 3, H335; STOT RE 2, H373; Skin Irrit. 2, H315; Acute Tox. 4, H312; Acute Tox. 4, H332	01-2119488216-32-xxxx

2.5-3 %	toluene	CAS:108-88-3 EC:203-625-9 Index:601-021-00-3	Flam. Liq. 2, H225; Repr. 2, H361d; Asp. Tox. 1, H304; STOT RE 2, H373; Skin Irrit. 2, H315; STOT SE 3, H336	01-2119471310-51-xxxx
1-2 %	4-methylpentan-2-one; isobutyl methyl ketone	CAS:108-10-1 EC:203-550-1 Index:606-004-00-4	Flam. Liq. 2, H225; Carc. 2, H351; Acute Tox. 4, H332; STOT SE 3, H336; Eye Irrit. 2, H319	01-2119473980-30-xxxx
0.5-1 %	ethyl acetate	CAS:141-78-6 EC:205-500-4 Index:607-022-00-5	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	01-2119475103-46-xxxx
0.5-1 %	ethylbenzene	CAS:100-41-4 EC:202-849-4 Index:601-023-00-4	Flam. Liq. 2, H225; Acute Tox. 4, H332; Asp. Tox. 1, H304; STOT RE 2, H373	01-2119489370-35-xxx
0.5-1 %	2-methoxy-1-methylethyl acetate	CAS:108-65-6 EC:203-603-9 Index:607-195-00-7	Flam. Liq. 3, H226	01-2119475791-29-xxxx
0.25-0.5 %	Fatty acids, C14-18 and C16-18-unsatd., maleated	CAS:85711-46-2 EC:288-306-2	Skin Irrit. 2, H315; Skin Sens. 1, H317	01-2119976378-19-xxxx
0.25-0.5 %	Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	CAS:41556-26-7 EC:255-437-1	Skin Sens. 1, H317, H400; Aquatic Acute 1, H410; Aquatic Chronic 1, H410	
0.1-0.2 %	Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	CAS:82919-37-7 EC:280-060-4	Skin Sens. 1, H317, H400; Aquatic Acute 1, H410; Aquatic Chronic 1, H410	
0.0015-0.05 %	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	CAS:80-62-6 EC:201-297-1 Index:607-035-00-6	Flam. Liq. 2, H225; STOT SE 3, H335; Skin Irrit. 2, H315; Skin Sens. 1, H317	01-2119452498-28-xxxx
0.0015-0.05 %	maleic anhydride	CAS:108-31-6 EC:203-571-6 Index:607-096-00-9	Acute Tox. 4, H302 Eye Dam. 1, H318 STOT RE 1, H372 Skin Corr. 1B, H314 Skin Sens. 1A, H317 Resp. Sens. 1, H334	01-2119472428-31-xxxx
			Specific Concentration Limits: C ≥ 0,001%: Skin Sens. 1A H317	
0.0015-0.05 %	phosphoric acid ... %, orthophosphoric acid ... %	CAS:7664-38-2 EC:231-633-2 Index:015-011-00-6	Met. Corr. 1, H290, H314 Skin Corr. 1B, H314 Eye Dam. 1, H318	
			Specific Concentration Limits: 10% ≤ C < 25%: Skin Irrit. 2 H315 10% ≤ C < 25%: Eye Irrit. 2 H319 25% ≤ C < 100%: Skin Corr. 1B H314	

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

Do not use eyewash or ointment of any kind (before obtaining an examination or advice from an eye specialist).

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Eye damages

Skin Irritation

Contact a poisons centre

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

In case of fire: Use CO₂, Foam, Chemical powders For extinction.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Cool the containers exposed to the fire with water.

5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

Wear personal protection equipment.

Remove all sources of ignition.

Collect the spilled product with no-sparking tools.

Remove persons to safety.

See protective measures under point 7 and 8.

For emergency responders:

Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Eliminate all unguarded flames and possible sources of ignition. Do not smoke.

Collect spilled material with non-sparking equipment.

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from flame and sparks. Avoid accumulating electrostatic charge.

Place recipients on the ground whilst decanting, and wear anti-static clothing and shoes.

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

Do not smoke while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Store at below 30 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Incompatible materials:
None in particular.

Instructions as regards storage premises:
Cool and adequately ventilated.

7.3. Specific end use(s)
No further recommendations. Refer to point 1.2

Recommendation(s)
None in particular

Industrial sector specific solutions:
None in particular

SECTION 8: Exposure controls/personal protection
8.1. Control parameters

Community Occupational Exposure Limits (OEL)

	OEL Type	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Notes
butanone CAS: 78-93-3	ACGIH	300	200	600	300	
2-butoxyethyl acetate; butylglycol acetate CAS: 112-07-2	EU	133	20	333	50	Skin
	ACGIH		20			A3 - Hemolysis
xylene [isomer mixture] CAS: 1330-20-7	ACGIH	50	100	100	150	A4, BEI - URT and eye irr, CNS impair
toluene CAS: 108-88-3	ACGIH	50	20			A4, BEI - Visual impair, female repro, pregnancy loss
4-methylpentan-2-one; isobutyl methyl ketone CAS: 108-10-1	EU	83	20	208	50	
	ACGIH		20		75	
ethyl acetate CAS: 141-78-6	EU	734,000	200	1468,000	400,000	
ethylbenzene CAS: 100-41-4	ACGIH	100,000	20,000	150,000		A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair
	EU					Skin
2-methoxy-1-methylethyl acetate CAS: 108-65-6	EU	275	50	550	100	Skin
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate CAS: 80-62-6	EU		50		100	
	ACGIH		50		100	
phosphoric acid ... %, orthophosphoric acid ... % CAS: 7664-38-2	EU	1		2		
	ACGIH	1		3		

Predicted No Effect Concentration (PNEC) values

	PNEC Limit	Exposure Route	Exposure Frequency	Remark
n-butyl acetate CAS: 123-86-4	0,18 mg/l	Fresh Water		
	0,018 mg/l	Marine water		
	0,981 mg/kg	Freshwater sediments		
	0,098 mg/kg	Marine water sediments		
	0,09 mg/kg	Soil (agricultural)		

butanone CAS: 78-93-3	35,6 mg/l	STP	
	55,8 mg/l	Marine water	
2-butoxyethyl acetate; butylglycol acetate CAS: 112-07-2	55,8 mg/l	Fresh Water	
	55,8 mg/l	occasional emission	
	709 mg/l	STP	
	284,7 mg/kg dwt	Freshwater sediments	
	284,7 mg/kg dwt	Marine water sediments	
	22,5 mg/kg	Soil (agricultural)	
	1000 mg/kg	orally (secondary poisoning)	
	0,304 mg/l	Fresh Water	
	0,03 mg/l	Marine water	
	2,03 mg/kg	Freshwater sediments	
xylene [isomer mixture] CAS: 1330-20-7	0,203 mg/kg	Marine water sediments	
	90 mg/l	STP	
	0,68 mg/kg	Soil	
	0,327 mg/l	Fresh Water	
	0,327 mg/l	Fresh Water	
	0,327 mg/l	occasional emission	
	6,58 mg/l	Microorganisms in sewage treatments	
	2,31 mg/kg	Soil (agricultural)	dry
	12,46 mg/kg	Marine water sediments	dry
	12,46 mg/kg	Freshwater sediments	dry
toluene CAS: 108-88-3	0,68 mg/l	Fresh Water	
	0,68 mg/l	Marine water	
	2,89 mg/kg	Soil (agricultural)	
	16,39 mg/l	Marine water sediments	
	16,39 mg/l	Freshwater sediments	
	13,61 mg/l	STP	
	0,6 mg/l	Fresh Water	
	0,06 mg/l	Marine water	
	8,27 mg/kg	Freshwater sediments	
	0,83 mg/kg	Marine water sediments	
4-methylpentan-2-one; isobutyl methyl ketone CAS: 108-10-1	1,3 mg/kg	Soil (agricultural)	
	0,26 mg/l	Fresh Water	
	0,026 mg/l	Marine water	
	1,25 mg/kg	Freshwater sediments	
	0,125 mg/kg	Marine water sediments	
	0,24 mg/kg	Soil (agricultural)	
	200 mg/kg	orally (secondary poisoning)	
	650 mg/l	STP	
	0,1 mg/l	Fresh Water	
	0,01 mg/l	Marine water	
ethyl acetate CAS: 141-78-6	13,7 mg/l	Freshwater sediments	
	13,7 mg/l	Marine water sediments	
	0,026 mg/l	Marine water	
	1,25 mg/kg	Freshwater sediments	
	0,125 mg/kg	Marine water sediments	
	0,24 mg/kg	Soil (agricultural)	
	200 mg/kg	orally (secondary poisoning)	
	650 mg/l	STP	
	0,1 mg/l	Fresh Water	
	0,01 mg/l	Marine water	
ethylbenzene CAS: 100-41-4	13,7 mg/l	Freshwater sediments	
	13,7 mg/l	Marine water sediments	
	13,7 mg/l	Marine water sediments	

	0,1 mg/l	occasional emission	
2-methoxy-1-methylethyl acetate CAS: 108-65-6	0,635 mg/l	Fresh Water	
	0,064 mg/l	Marine water	
	0,329 mg/kg	Marine water sediments	dry
	3,29 mg/kg	Freshwater sediments	dry
	0,29 mg/kg	Soil (agricultural)	dry
	100 mg/l	STP	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate CAS: 80-62-6	0,94 mg/l	Fresh Water	
	0,094 mg/l	Marine water	
	5,74 mg/kg	Freshwater sediments	
	1,47 mg/kg	Soil (agricultural)	
	0,94 mg/l	occasional emission	
	10 mg/l	Microorganisms in sewage treatments	
maleic anhydride CAS: 108-31-6	0,043 mg/l	Fresh Water	
	0,004 mg/l	Marine water	
	0,334 mg/kg	Freshwater sediments	
	0,033 mg/kg	Marine water sediments	
	0,042 mg/kg	Soil (agricultural)	
	0,428 mg/l	occasional emission	
	44,6 mg/l	STP	

Derived No Effect Level (DNEL) values

	Worker Industry	Worker Professional	Consumer	Exposure Route	Exposure Frequency	Remark
n-butyl acetate CAS: 123-86-4		600 mg/m3		Human Inhalation	Short Term, local effects	
		300 mg/m3		Human Inhalation	Long Term, local effects	
		11 mg/kg		Human Dermal	Long Term, systemic effects	
		11 mg/kg		Human Dermal	Short Term, systemic effects	
			300 mg/kg	Human Inhalation	Short Term, local effects	
			35,7 mg/m3	Human Inhalation	Long Term, local effects	
			6 mg/kg	Human Dermal	Short Term, systemic effects	
			2 mg/kg	Human Oral	Long Term, systemic effects	
			2 mg/kg	Human Oral	Short Term, systemic effects	
butanone CAS: 78-93-3	1161 mg/Kg-bw/day			Human Dermal	Long Term, systemic effects	
	600 mg/m3			Human Inhalation	Long Term, systemic effects	
			412 mg/Kg-bw/day	Human Dermal	Long Term, systemic effects	
			106 mg/m3	Human Inhalation	Long Term, systemic effects	
			31 mg/Kg-bw/day	Human Oral	Long Term, systemic effects	
2-butoxyethyl acetate; butylglycol acetate CAS: 112-07-2	4,3 mg/kg/day			Human Oral	Long Term, systemic effects	
	333 mg/m3		166 mg/m3	Human Inhalation	Short Term, local effects	
	133 mg/m3			Human Inhalation	Long Term, systemic effects	
	102 mg/kg/day		36	Human Dermal	Short Term, systemic effects	

xylene [isomer mixture] CAS: 1330-20-7	180 mg/Kg-bw/day		Human Dermal	Long Term, systemic effects
	77 mg/m3		Human Inhalation	Long Term, systemic effects
		108 mg/Kg-bw/day	Human Dermal	Long Term, systemic effects
		1872 mg/m3	Human Inhalation	Long Term, local effects
toluene CAS: 108-88-3		12,5 mg/Kg-bw/day	Human Oral	Long Term, systemic effects
		226 mg/m3	Human Inhalation	Short Term, systemic effects
		226 mg/m3	Human Inhalation	Short Term, local effects
		226 mg/m3	Human Dermal	Long Term, systemic effects
4-methylpentan-2-one; isobutyl methyl ketone CAS: 108-10-1		56,5 mg/m3	Human Inhalation	Long Term, systemic effects
		8,13 mg/Kg-bw/day	Human Oral	Long Term, systemic effects
	384 mg/kg/day		Human Dermal	Long Term, systemic effects
	384 mg/m3		Human Inhalation	Short Term, systemic effects
	192 mg/m3		Human Inhalation	Long Term, systemic effects
	208 mg/m3		Human Inhalation	Short Term (acute)
	208 mg/m3		Human Inhalation	Short Term, local effects
	11,8 mg/kg		Human Dermal	Long Term (repeated)
	83 mg/m3		Human Inhalation	Long Term (repeated)
	83 mg/m3		Human Inhalation	Long Term, local effects
		155,2 mg/m3	Human Inhalation	Short Term (acute)
		155,2 mg/m3	Human Inhalation	Short Term, local effects
ethyl acetate CAS: 141-78-6		4,2 mg/kg	Human Dermal	Long Term (repeated)
		14,7 mg/m3	Human Inhalation	Long Term (repeated)
		4,2 mg/kg	Human Oral	Long Term (repeated)
	1468 mg/m3	734 mg/m3	Human Inhalation	Short Term, systemic effects
	1468 ppm		Human Inhalation	Short Term (acute)
	63 mg/Kg-bw/day		Human Dermal	Long Term, systemic effects
	734 mg/m3		Human Inhalation	Long Term, local effects
	734 mg/m3		Human Inhalation	Long Term, systemic effects
		4,5 mg/Kg-bw/day	Human Oral	Long Term, systemic effects
		734 mg/m3	Human Inhalation	Short Term (acute)
		734 mg/m3	Human Inhalation	Long Term, systemic effects
		37 mg/Kg-bw/day	Human Dermal	Long Term, local effects
ethylbenzene CAS: 100-41-4		367 mg/m3	Human Inhalation	Short Term, local effects
		367 mg/m3	Human Inhalation	Long Term, systemic effects
	180 mg/kg/day		Human Dermal	Long Term, systemic effects
	293 mg/m3		Human Inhalation	Short Term, local effects
2-methoxy-1-methylethyl acetate CAS: 108-65-6	77 mg/m3		Human Inhalation	Long Term, systemic effects
		153,5 mg/kg	Human Dermal	Long Term, systemic effects
		275 mg/m3	Human Inhalation	Long Term, systemic effects

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate CAS: 80-62-6	54,8 mg/kg/day	Human Dermal	Long Term, systemic effects
	33 mg/m3	Human Inhalation	Long Term, systemic effects
	1,67 mg/kg/day	Human Oral	Long Term, systemic effects
		Human Inhalation	Long Term, local effects
	1,5 mg/cm2	Human Dermal	Long Term, local effects
	210 mg/m3	Human Inhalation	Long Term, systemic effects
	13,67 mg/Kg-bw/day	Human Dermal	Long Term, systemic effects
	1,5 mg/cm2	Human Dermal	Short Term, local effects
	74,3 mg/m3	Human Inhalation	Long Term, systemic effects
	105 mg/m3	Human Inhalation	Long Term, local effects
maleic anhydride CAS: 108-31-6	1,5 mg/cm2	Human Dermal	Short Term, local effects
	8,2 mg/Kg-bw/day	Human Dermal	Long Term, systemic effects
	0,8 mg/m3	Human Inhalation	Short Term, local effects
	0,4 mg/m3	Human Inhalation	Long Term, local effects
	0,04 mg/cm2	Human Dermal	Short Term, local effects
	0,04 mg/cm2	Human Dermal	Long Term, local effects
	0,8 mg/m3	Human Inhalation	Short Term, systemic effects
	0,4 mg/m3	Human Inhalation	Long Term, systemic effects
	1 mg/m3	Human Inhalation	Long Term, local effects
	2 mg/m3	Human Inhalation	Short Term, local effects
phosphoric acid ... %, orthophosphoric acid ... % CAS: 7664-38-2	0,75 mg/m3	Human Inhalation	Long Term, local effects

8.2. Exposure controls

Eye protection:

Use eye protection devices. Example: closed safety visors, goggles with side protection. Do not wear contact lenses.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Due to the synergistic effect of the substances contained in the formulation it is not possible to identify a single material capable of resisting their combination. Multilayer protective gloves for mixtures of substances may be suitable. Always refer to the protection degree and permeation rate data provided by the glove manufacturer with regard to the substances listed in point 3 of this sheet.

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment.

Use adequate protective respiratory equipment, e.g. A2 or A2P2 or A2P3.

Thermal Hazards:

N.A.

Environmental exposure controls:

None known

Hygienic and Technical measures

N.A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State Liquid

Appearance and colour: Liquid white

Odour: characteristic

pH: Not Relevant

Kinematic viscosity: N.A.
Melting point / freezing point: > 1 °C / < 0 °C
Initial boiling point and boiling range: > 55 °C
Flash point: < 23°C
Upper/lower flammability or explosive limits: N.A.
Vapour density: N.A.
Vapour pressure: N.A.
Relative density: 1.17 kg/l
Solubility in water: N.A.
Solubility in oil: N.A.
Partition coefficient (n-octanol/water): N.A.
Auto-ignition temperature: 250 °C
Decomposition temperature: N.A.
Flammability: The product is classified Flam. Liq. 2 H225

Particle characteristics:

Particle size: N.A.

9.2. Other information

Viscosity: 125.00 s (" Din cup # 4)

No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Avoid accumulating electrostatic charge.

Vapours can form explosive mixtures with air.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

vapours potentially dangerous to health may be released.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Preparation

a) acute toxicity	Not classified Based on available data, the classification criteria are not met
b) skin corrosion/irritation	Not classified Based on available data, the classification criteria are not met
c) serious eye damage/irritation	The product is classified: Eye Irrit. 2(H319)
d) respiratory or skin sensitisation	The product is classified: Skin Sens. 1A(H317)
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	The product is classified: Carc. 2(H351)
g) reproductive toxicity	Not classified Based on available data, the classification criteria are not met
h) STOT-single exposure	The product is classified: STOT SE 3(H336)
i) STOT-repeated exposure	Not classified Based on available data, the classification criteria are not met
j) aspiration hazard	Not classified Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

n-butyl acetate	a) acute toxicity	LC50 Inhalation Rat > 21 mg/l 4h LD50 Oral Rat = 10736 mg/kg
-----------------	-------------------	---

Method OECD linee guide 402

		LD50 Skin Rabbit > 14000 mg/kg	
butanone	a) acute toxicity	LD50 Oral Rat = 2737 mg/kg LD50 Skin Rabbit = 6480 mg/kg LC50 Inhalation Rat = 23,5 mg/l 8h	
	b) skin corrosion/irritation	Skin Corrosive Rabbit Negative	moderatamente irritante
2-butoxyethyl acetate; butylglycol acetate	a) acute toxicity	LD50 Oral Rat 1880 mg/kg body weight LD50 Skin Rabbit 1500 mg/kg body weight LC50 Inhalation Rat > 400 Ppm 4h	
xylene [isomer mixture]	a) acute toxicity	LD50 Inhalation Rat = 27 mg/l 4h LD50 Oral Rat = 3523 mg/kg LD50 Skin Rabbit = 12126 mg/kg	
toluene	a) acute toxicity	LD50 Oral Rat 5000 mg/kg 24h LD50 Skin Rabbit 12267 mg/kg LC50 Inhalation Rat 25,7 mg/l 4h	
4-methylpentan-2-one; isobutyl methyl ketone	a) acute toxicity	LC50 Inhalation Rat = 23,29 g/m3 LD50 Oral Rat = 2080 mg/kg LC50 Inhalation Rat = 8,2 mg/l 4h LD50 Skin Rabbit = 2000 mg/kg	
ethyl acetate	a) acute toxicity	LD50 Skin Rabbit > 20000 mg/kg LD50 Oral Rat = 5620 mg/kg LC50 Inhalation Rat > 29,3 mg/l 4h LD50 Oral Rabbit = 4934 mg/kg body weight	
	b) skin corrosion/irritation	Skin Irritant Skin Rabbit Negative	
	e) germ cell mutagenicity	Genotoxicity Negative	
	j) aspiration hazard	Respiratory Tract Corrosive Inhalation Positive	
ethylbenzene	a) acute toxicity	LD50 Oral Rat = 3500 mg/kg LD50 Oral Rat = 4710 mg/kg body weight LD50 Skin Rabbit = 15400 mg/kg DZSR_004 Inhalation Rat = 4000 Ppm 4h	
	d) respiratory or skin sensitisation	Skin Sensitization Skin Cavia porcellus Negative	
2-methoxy-1-methylethyl acetate	a) acute toxicity	LD50 Oral Rat = 8532 mg/kg LC50 Skin Rat > 5000 mg/kg LC50 Inhalation Mist Rat > 23,8 mg/l 6h	
	b) skin corrosion/irritation	Skin Irritant Skin Rabbit Negative	
	c) serious eye damage/irritation	Eye Irritant Rabbit Negative	
	d) respiratory or skin sensitisation	Skin Sensitization Skin Cavia porcellus Negative	
Fatty acids, C14-18 and C16-18-unsatd., maleated	a) acute toxicity	LD50 Oral Rat Female > 2000 mg/kg	

b) skin corrosion/irritation	Skin Irritant	Yes
	Eye Irritant	Rabbit No
d) respiratory or skin sensitisation	Skin Sensitization	Mouse Yes

methyl methacrylate;
methyl 2-methylprop-2-
enoate; methyl 2-
methylpropenoate

a) acute toxicity	LD50 Oral Rat > 7900 mg/kg
	LC50 Inhalation Rat = 29,8 mg/l 4h
	LD50 Skin Rabbit = 5000 mg/kg

maleic anhydride

a) acute toxicity	LD50 Oral Rat = 1090 mg/kg body weight
	LD50 Skin Rabbit = 2620 mg/kg body weight
	LD50 Inhalation Rat = 4,35 mg/l 1h

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration >= 0.1%

11.2 Information on other hazards

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar preparations, this preparation may be a skin sensitiser and an irritant.

It contains low molecular epoxy constituents which are irritating to eyes, mucous me

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

Harmful to aquatic life with long lasting effects.

List of Eco-Toxicological properties of the product

The product is classified: Aquatic Chronic 3(H412)

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
n-butyl acetate	CAS: 123-86-4 - EINECS: 204- 658-1 - INDEX: 607-025-00-1	a) Aquatic acute toxicity : LC50 Fish = 64 mg/l 48
		a) Aquatic acute toxicity : EC50 Daphnia = 73 mg/l 24
		a) Aquatic acute toxicity : EC50 Algae = 674 mg/l 72
butanone	CAS: 78-93-3 - EINECS: 201- 159-0 - INDEX: 606-002-00-3	a) Aquatic acute toxicity : LC50 Fish > 3220 mg/l 96
		a) Aquatic acute toxicity : EC50 Daphnia > 520 mg/l 48
2-butoxyethyl acetate; butylglycol acetate	CAS: 112-07-2 - EINECS: 203- 933-3 - INDEX: 607-038-00-2	a) Aquatic acute toxicity : LC50 Fish 28 mg/l 96
		a) Aquatic acute toxicity : EC50 Daphnia 37 mg/l 48
		a) Aquatic acute toxicity : EC50 Algae 1570 mg/l 72
xylene [isomer mixture]	CAS: 1330-20-7 - EINECS: 215- 535-7 - INDEX: 601-022-00-9	a) Aquatic acute toxicity : EC50 Daphnia = 1 mg/l 48
		a) Aquatic acute toxicity : LC50 Fish = 3,2 mg/l 96
		a) Aquatic acute toxicity : LC50 Algae = 2,6 mg/l 73
toluene	CAS: 108-88-3 - EINECS: 203-	a) Aquatic acute toxicity : LC50 Fish = 5,5 ml/l 96

	625-9 - INDEX: 601-021-00-3	
		a) Aquatic acute toxicity : EC50 Algae > 134 mg/l 72 b) Aquatic chronic toxicity : EC50 Daphnia = 3,78 mg/l 48
4-methylpentan-2-one; isobutyl methyl ketone	CAS: 108-10-1 - EINECS: 203-550-1 - INDEX: 606-004-00-4	a) Aquatic acute toxicity : LC50 Fish > 100 mg/l 96
		a) Aquatic acute toxicity : EC50 Daphnia > 100 mg/l 48 a) Aquatic acute toxicity : EC50 Algae > 100 mg/l
ethyl acetate	CAS: 141-78-6 - EINECS: 205-500-4 - INDEX: 607-022-00-5	a) Aquatic acute toxicity : LC50 Fish = 454,7 mg/l 96
		a) Aquatic acute toxicity : EC50 Daphnia = 154 mg/l 48 a) Aquatic acute toxicity : EC50 Algae = 3300 mg/l 48 b) Aquatic chronic toxicity : NOEC Algae > 100 mg/l 72
ethylbenzene	CAS: 100-41-4 - EINECS: 202-849-4 - INDEX: 601-023-00-4	a) Aquatic acute toxicity : LC50 Fish = 42,3 mg/l 96
2-methoxy-1-methylethyl acetate	CAS: 108-65-6 - EINECS: 203-603-9 - INDEX: 607-195-00-7	a) Aquatic acute toxicity : LC50 Fish > 100 mg/l 96 - Method OECD linee guide 203
		a) Aquatic acute toxicity : EC50 Daphnia > 500 mg/l 48 - „Method Direttiva 67/548CEE allegato V,C.2 a) Aquatic acute toxicity : ErC50 Algae > 1000 mg/l 72 - Method OECD TG 209
Fatty acids, C14-18 and C16-18-unsatd., maleated	CAS: 85711-46-2 - EINECS: 288-306-2	a) Aquatic acute toxicity : LC50 Fish > 150 mg/l 48
		a) Aquatic acute toxicity : EC50 Daphnia > 100 mg/l 48 a) Aquatic acute toxicity : ErC50 Algae > 100 mg/l 72 a) Aquatic acute toxicity : EC50 Active mud > 1000 mg/l 3
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	CAS: 80-62-6 - EINECS: 201-297-1 - INDEX: 607-035-00-6	a) Aquatic acute toxicity : LC50 Fish = 191 mg/l 96
		a) Aquatic acute toxicity : EC50 Daphnia = 69 mg/l 48 a) Aquatic acute toxicity : EC50 Algae > 110 mg/l 72
maleic anhydride	CAS: 108-31-6 - EINECS: 203-571-6 - INDEX: 607-096-00-9	a) Aquatic acute toxicity : LC50 Fish = 75 mg/l 96
		a) Aquatic acute toxicity : LC0 Fish = 115 mg/l 48 a) Aquatic acute toxicity : EC50 Algae = 29 mg/l 72 a) Aquatic acute toxicity : EC50 Daphnia = 84 mg/l 24 a) Aquatic acute toxicity : EC50 Daphnia 42,8 mg/l 48 a) Aquatic acute toxicity : EC0 Eisenia foetica 44,6 mg/l 17
phosphoric acid ... %, orthophosphoric acid ... %	CAS: 7664-38-2 - EINECS: 231-633-2 - INDEX: 015-011-00-6	a) Aquatic acute toxicity : EC50 Daphnia > 100 mg/l 48
		a) Aquatic acute toxicity : ErC50 Algae > 100 mg/l 72

No endocrine disruptor substances present in concentration >= 0.1%

12.2. Persistence and degradability

None known

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$.

12.6 Endocrine disrupting properties

12.6 Endocrine disrupting properties

12.7 Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

14.1. UN number or ID number

1263

14.2. UN proper shipping name

ADR-Shipping Name: PAINT

IATA-Technical name: PAINT

IMDG-Technical name: PAINT

14.3. Transport hazard class(es)

ADR-Class: 3

IATA-Class: 3

IMDG-Class: 3

14.4. Packing group

ADR-Packing Group: II

IATA-Packing group: II

IMDG-Packing group: II

14.5. Environmental hazards

Toxic Ingredients Qty: 0.00

High Toxicity Ingredients Qty: 0.00

Marine pollutant: No

Environmental Pollutant: No

14.6. Special precautions for user

Road and Rail (ADR-RID) :

ADR exempt: No

ADR-Label: 3

ADR - Hazard identification number: 33

ADR-Special Provisions: 163 367 640C 650

ADR-Transport category (Tunnel restriction code): 2 (D/E)

Air (IATA) :

IATA-Passenger Aircraft: 353

IATA-Cargo Aircraft: 364

IATA-Label: 3

IATA-Subsidiary hazards: -

IATA-Erg: 3L

IATA-Special Provisioning: A3 A72 A192

Sea (IMDG) :

IMDG-Stowage Code: Category B

IMDG-Stowage Note: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisioning: 163 367

IMDG-Page: N/A

IMDG-Label: N/A

IMDG-MFAG: N/A

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/699 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2020/878

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3, 40 3, 40

Restrictions related to the substances contained: 28, 29, 30, 48, 75 28, 29, 30, 48, 75

Provisions related to directive EU 2012/18 (Seveso III):

N.A.

Regulation (EU) No 649/2012 (PIC regulation)

No substances listed

German Water Hazard Class.

Class 3: extremely hazardous.

SVHC Substances:

No data available

Dir. 2010/75/EC (VOC directive) ; Dir. 2004/42/EC (VOC directive)

Total solid content: 62 - 64 %

Volatile Organic compounds - VOCs = 37 %

Volatile Organic compounds - VOCs = 435 g/L

Of which reactive monomers: 0 %

Total Volatile Organic Carbon (typical value): 25 %

Of which reactive monomers: 0 %

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Code	Description
EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.

H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
2.16/1	Met. Corr. 1	Substance or mixture corrosive to metals, Category 1
2.6/2	Flam. Liq. 2	Flammable liquid, Category 2
2.6/3	Flam. Liq. 3	Flammable liquid, Category 3
3.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4
3.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
3.10/1	Asp. Tox. 1	Aspiration hazard, Category 1
3.2/1B	Skin Corr. 1B	Skin corrosion, Category 1B
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/1	Eye Dam. 1	Serious eye damage, Category 1
3.3/2	Eye Irrit. 2	Eye irritation, Category 2
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.4.2/1A	Skin Sens. 1A	Skin Sensitisation, Category 1A
3.6/2	Carc. 2	Carcinogenicity, Category 2
3.7/2	Repr. 2	Reproductive toxicity, Category 2
3.8/3	STOT SE 3	Specific target organ toxicity — single exposure, Category 3
3.9/2	STOT RE 2	Specific target organ toxicity — repeated exposure, Category 2
4.1/A1	Aquatic Acute 1	Acute aquatic hazard, category 1
4.1/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1
4.1/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
2.6/2	On basis of test data
3.3/2	Calculation method
3.4.2/1A	Calculation method
3.6/2	Calculation method
3.8/3	Calculation method
4.1/C3	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.
This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ATE: Acute Toxicity Estimate
ATEmix: Acute toxicity Estimate (Mixtures)
BCF: Biological Concentration Factor
BEI: Biological Exposure Index
BOD: Biochemical Oxygen Demand
CAS: Chemical Abstracts Service (division of the American Chemical Society).
CAV: Poison Center
CE: European Community
CLP: Classification, Labeling, Packaging.
CMR: Carcinogenic, Mutagenic and Reprotoxic
COD: Chemical Oxygen Demand
COV: Volatile Organic Compound
CSA: Chemical Safety Assessment
CSR: Chemical Safety Report
DMEL: Derived Minimal Effect Level
DNEL: Derived No Effect Level.
DPD: Dangerous Preparations Directive
DSD: Dangerous Substances Directive
EC50: Half Maximal Effective Concentration
ECHA: European Chemicals Agency
EINECS: European Inventory of Existing Commercial Chemical Substances.
ES: Exposure Scenario
GefStoffVO: Ordinance on Hazardous Substances, Germany.
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
IARC: International Agency for Research on Cancer
IATA: International Air Transport Association.
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
IC50: half maximal inhibitory concentration
ICAO: International Civil Aviation Organization.
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG: International Maritime Code for Dangerous Goods.
INCI: International Nomenclature of Cosmetic Ingredients.
IRCCS: Scientific Institute for Research, Hospitalization and Health Care
KAFH: KAFH
KSt: Explosion coefficient.
LC50: Lethal concentration, for 50 percent of test population.
LD50: Lethal dose, for 50 percent of test population.
LDLo: Leathal Dose Low
N.A.: Not Applicable
N/A: Not Applicable
N/D: Not defined/ Not available
NA: Not available
NIOSH: National Institute for Occupational Safety and Health
NOAEL: No Observed Adverse Effect Level
OSHA: Occupational Safety and Health Administration.
PBT: Persistent, Bioaccumulative and Toxic
PGK: Packaging Instruction
PNEC: Predicted No Effect Concentration.
PSG: Passengers
RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
vPvB: Very Persistent, Very Bioaccumulative.
WGK: German Water Hazard Class.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

Paragraphs modified from the previous revision:

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 16. OTHER INFORMATION

Fac-simile label

White ACR EXT Sealer

Regulation (EC) No 1272/2008 (CLP):

Pictograms and Signal Words



Danger

Hazard statements

H225	Highly flammable liquid and vapour.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...
P370+P378	In case of fire: Use CO2, Foam, Chemical powders For extinction.
P403+P235	Store in a well-ventilated place. Keep cool.

Contains

n-butyl acetate	
butanone	
maleic anhydride	
toluene	
Fatty acids, C14-18 and C16-18-unsatd., maleated	May produce an allergic reaction.
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	May produce an allergic reaction.
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	May produce an allergic reaction.

QUANTITY:

SUPPLIER: