

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Mixture identification:  
Trade name: Clear ACR AS Matt topcoat  
Trade code: **TA79G10C00**  
UFI: V94E-2068-K00S-SK46

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Recommended use: Surface coating  
Uses advised against: N.A.

**1.3. Details of the supplier of the safety data sheet**

Company: Sirca S.p.A.  
Viale Roma, 85  
35010 Sandono di Massanzago (PD) - ITALY  
Tel. +39 0499322311  
Email: safety@sirca.it

**1.4. Emergency telephone number**

National Poisons Information Service - Medical Toxicology Unit - London - Tel. 0171/6359191  
Scottish Poisons Information Bureau - The Royal Infirmary - Edinburgh - Tel. 01/315362298  
Welsh National Poisons Unit - Ward West 5 - Llandough Hospital Penarth - Cardiff - Tel. 012/22709901  
Poisons Information Centre - Royal Victoria Hospital - Belfast - Tel. 012/32240503  
Poisons Information centre - Beaumont Hospital - Dublin - Tel. 0103531/8379964  
CAV Policlinico "Umberto I". Roma V.le del Policlinico, 155 161 Telefono 06-49978000  
Osp. Niguarda Ca' Granda. Milano Piazza Ospedale Maggiore,3 20162 Telefono 02-66101029

**SECTION 2: Hazards identification**



**2.1. Classification of the substance or mixture**

**Regulation (EC) n. 1272/2008 (CLP)**

Flam. Liq. 2	Highly flammable liquid and vapour.
Skin Irrit. 2	Causes skin irritation.
Eye Irrit. 2	Causes serious eye irritation.
Repr. 2	Suspected of damaging fertility or the unborn child.
STOT SE 3	May cause drowsiness or dizziness.
STOT RE 2	May cause damage to organs through prolonged or repeated exposure.

Adverse physicochemical, human health and environmental effects:  
No other hazards

**2.2. Label elements**

**Regulation (EC) No 1272/2008 (CLP):**

**Pictograms and Signal Words**



Danger

**Hazard statements**

H225 Highly flammable liquid and vapour.

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

#### Precautionary statements

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...
P370+P378	In case of fire: Use CO2, Foam, Chemical powders For extinction.
P403+P235	Store in a well-ventilated place. Keep cool.

#### Contains

toluene	
n-butyl acetate	
ethyl acetate	
butanone	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	May produce an allergic reaction.
Fatty acids, C18-unsatd., trimers, compds. with oleylamine	May produce an allergic reaction.

#### Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

#### 2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration  $\geq 0.1\%$ .

Other Hazards: No other hazards

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

N.A.

### 3.2. Mixtures

Mixture identification: Clear ACR AS Matt topcoat

#### Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
25-48 %	toluene	CAS:108-88-3 EC:203-625-9 Index:601-021-00-3	Flam. Liq. 2, H225; Repr. 2, H361d; Asp. Tox. 1, H304; STOT RE 2, H373; Skin Irrit. 2, H315; STOT SE 3, H336	01-2119471310-51-xxxx
12.5-20 %	n-butyl acetate	CAS:123-86-4 EC:204-658-1 Index:607-025-00-1	Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	01-2119485493-29-xxxx
9.9-12.5 %	xylene [isomer mixture]	CAS:1330-20-7 EC:215-535-7 Index:601-022-00-9	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Eye Irrit. 2, H319; STOT SE 3, H335; STOT RE 2, H373; Skin Irrit. 2, H315; Acute Tox. 4, H312; Acute Tox. 4, H332	01-2119488216-32-xxxx
9.9-12.5 %	ethyl acetate	CAS:141-78-6 EC:205-500-4 Index:607-022-00-5	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	01-2119475103-46-xxxx
3-5 %	butanone	CAS:78-93-3 EC:201-159-0 Index:606-002-00-3	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	01-2119457290-43-xxxx

2.5-3 %	ethylbenzene	CAS:100-41-4 EC:202-849-4 Index:601-023-00-4	Flam. Liq. 2, H225; Acute Tox. 4, H332, H373; STOT RE 2, H304; Asp. Tox. 1, H304	01-2119489370-35-xxx
0.5-1 %	2-methoxy-1-methylethyl acetate	CAS:108-65-6 EC:203-603-9 Index:607-195-00-7	Flam. Liq. 3, H226	01-2119475791-29-xxxx
0.2-0.25 %	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	CAS:80-62-6 EC:201-297-1 Index:607-035-00-6	Flam. Liq. 2, H225; STOT SE 3, H335; Skin Irrit. 2, H315; Skin Sens. 1, H317	01-2119452498-28-xxxx
0.1-0.2 %	Neodecanoic acid, zinc salt, basic	CAS:84418-68-8 EC:282-780-4	Aquatic Acute 1, H400; Aquatic Chronic 1, H410	01-2120770060-67
0.0015-0.05 %	Fatty acids, C18-unsatd., trimers, compds. with oleylamine	CAS:85711-55-3 EC:288-315-1	Eye Dam. 1, H318, H317; Skin Sens. 1A, H373; STOT RE 2, H373	01-2119974148-28-xxxx

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

In case of skin contact:

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

Do not use eyewash or ointment of any kind (before obtaining an examination or advice from an eye specialist).

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

Eye damages

Skin Irritation

Contact a poisons centre

### 4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media:

In case of fire: Use CO<sub>2</sub>, Foam, Chemical powders For extinction.

Extinguishing media which must not be used for safety reasons:

None in particular.

### 5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Cool the containers exposed to the fire with water.

### 5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

Wear personal protection equipment.

Remove all sources of ignition.

Collect the spilled product with no-sparking tools.

Remove persons to safety.

See protective measures under point 7 and 8.

For emergency responders:

Wear personal protection equipment.

## 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

## 6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Eliminate all unguarded flames and possible sources of ignition. Do not smoke.

Collect spilled material with non-sparking equipment.

Wash with plenty of water.

## 6.4. Reference to other sections

See also section 8 and 13

---

# SECTION 7: Handling and storage

## 7.1. Precautions for safe handling

Keep away from flame and sparks. Avoid accumulating electrostatic charge.

Place recipients on the ground whilst decanting, and wear anti-static clothing and shoes.

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

Do not smoke while working.

See also section 8 for recommended protective equipment.

## 7.2. Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.

Store at below 30 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

## 7.3. Specific end use(s)

No further recommendations. Refer to point 1.2

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

---

# SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

### Community Occupational Exposure Limits (OEL)

	OEL Type	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Notes
toluene CAS: 108-88-3	ACGIH	50	20			A4, BEI - Visual impair, female repro, pregnancy loss
xylene [isomer mixture] CAS: 1330-20-7	ACGIH	50	100	100	150	A4, BEI - URT and eye irr, CNS impair
ethyl acetate CAS: 141-78-6	EU	734,000	200	1468,000	400,000	
butanone CAS: 78-93-3	ACGIH	300	200	600	300	
ethylbenzene CAS: 100-41-4	ACGIH	100,000	20,000	150,000		A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair
	EU					Skin
2-methoxy-1-methylethyl	EU	275	50	550	100	Skin

acetate  
CAS: 108-65-6

methyl methacrylate; methyl 2-methylprop-2- enoate; methyl 2- methylpropenoate CAS: 80-62-6	EU	50	100
---	----	----	-----

	ACGIH	50	100
--	-------	----	-----

# **Predicted No Effect Concentration (PNEC) values**

	PNEC Limit	Exposure Route	Exposure Frequency	Remark
toluene CAS: 108-88-3	0,68 mg/l	Fresh Water		
	0,68 mg/l	Marine water		
	2,89 mg/kg	Soil (agricultural)		
	16,39 mg/l	Marine water sediments		
	16,39 mg/l	Freshwater sediments		
	13,61 mg/l	STP		
n-butyl acetate CAS: 123-86-4	0,18 mg/l	Fresh Water		
	0,018 mg/l	Marine water		
	0,981 mg/kg	Freshwater sediments		
	0,098 mg/kg	Marine water sediments		
	0,09 mg/kg	Soil (agricultural)		
	35,6 mg/l	STP		
xylene [isomer mixture] CAS: 1330-20-7	0,327 mg/l	Fresh Water		
	0,327 mg/l	Fresh Water		
	0,327 mg/l	occasional emission		
	6,58 mg/l	Microorganisms in sewage treatments		
	2,31 mg/kg	Soil (agricultural)		dry
	12,46 mg/kg	Marine water sediments		dry
	12,46 mg/kg	Freshwater sediments		dry
ethyl acetate CAS: 141-78-6	0,26 mg/l	Fresh Water		
	0,026 mg/l	Marine water		
	1,25 mg/kg	Freshwater sediments		
	0,125 mg/kg	Marine water sediments		
	0,24 mg/kg	Soil (agricultural)		
	200 mg/kg	orally (secondary poisoning)		
	650 mg/l	STP		
butanone CAS: 78-93-3	55,8 mg/l	Marine water		
	55,8 mg/l	Fresh Water		
	55,8 mg/l	occasional emission		
	709 mg/l	STP		
	284,7 mg/kg dwt	Freshwater sediments		
	284,7 mg/kg dwt	Marine water sediments		
	22,5 mg/kg	Soil (agricultural)		
	1000 mg/kg	orally (secondary poisoning)		
ethylbenzene CAS: 100-41-4	0,1 mg/l	Fresh Water		
	0,01 mg/l	Marine water		
	13,7 mg/l	Freshwater sediments		

	13,7 mg/l	Marine water sediments	
	0,1 mg/l	occasional emission	
2-methoxy-1-methylethyl acetate CAS: 108-65-6	0,635 mg/l	Fresh Water	
	0,064 mg/l	Marine water	
	0,329 mg/kg	Marine water sediments	dry
	3,29 mg/kg	Freshwater sediments	dry
	0,29 mg/kg	Soil (agricultural)	dry
	100 mg/l	STP	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate CAS: 80-62-6	0,94 mg/l	Fresh Water	
	0,094 mg/l	Marine water	
	5,74 mg/kg	Freshwater sediments	
	1,47 mg/kg	Soil (agricultural)	
	0,94 mg/l	occasional emission	
	10 mg/l	Microorganisms in sewage treatments	
Fatty acids, C18-unsatd., trimers, compds. with oleylamine CAS: 85711-55-3	0,47 mg/kg	Food chain	

#### Derived No Effect Level (DNEL) values

	Worker Industry	Worker Professional	Consumer	Exposure Route	Exposure Frequency	Remark
toluene CAS: 108-88-3			226 mg/m3	Human Inhalation	Short Term, systemic effects	
			226 mg/m3	Human Inhalation	Short Term, local effects	
			226 mg/m3	Human Dermal	Long Term, systemic effects	
			56,5 mg/m3	Human Inhalation	Long Term, systemic effects	
			8,13 mg/Kg-bw/day	Human Oral	Long Term, systemic effects	
	384 mg/kg/day			Human Dermal	Long Term, systemic effects	
	384 mg/m3			Human Inhalation	Short Term, systemic effects	
	192 mg/m3			Human Inhalation	Long Term, systemic effects	
n-butyl acetate CAS: 123-86-4		600 mg/m3		Human Inhalation	Short Term, local effects	
		300 mg/m3		Human Inhalation	Long Term, local effects	
		11 mg/kg		Human Dermal	Long Term, systemic effects	
		11 mg/kg		Human Dermal	Short Term, systemic effects	
			300 mg/kg	Human Inhalation	Short Term, local effects	
			35,7 mg/m3	Human Inhalation	Long Term, local effects	
			6 mg/kg	Human Dermal	Short Term, systemic effects	
			2 mg/kg	Human Oral	Long Term, systemic effects	
			2 mg/kg	Human Oral	Short Term, systemic effects	
xylene [isomer mixture] CAS: 1330-20-7	180 mg/Kg-bw/day			Human Dermal	Long Term, systemic effects	
	77 mg/m3			Human Inhalation	Long Term, systemic effects	
			108 mg/Kg-bw/day	Human Dermal	Long Term, systemic effects	
			1872 mg/m3	Human Inhalation	Long Term, local effects	
			12,5 mg/Kg-bw/day	Human Oral	Long Term, systemic effects	

ethyl acetate CAS: 141-78-6	1468 mg/m3	734 mg/m3	Human Inhalation	Short Term, systemic effects
	1468 ppm		Human Inhalation	Short Term (acute)
	63 mg/Kg- bw/day		Human Dermal	Long Term, systemic effects
	734 mg/m3		Human Inhalation	Long Term, local effects
	734 mg/m3		Human Inhalation	Long Term, systemic effects
		4,5 mg/Kg- bw/day	Human Oral	Long Term, systemic effects
		734 mg/m3	Human Inhalation	Short Term (acute)
		734 mg/m3	Human Inhalation	Long Term, systemic effects
		37 mg/Kg- bw/day	Human Dermal	Long Term, local effects
		367 mg/m3	Human Inhalation	Short Term, local effects
		367 mg/m3	Human Inhalation	Long Term, systemic effects
			Human Dermal	Long Term, systemic effects
butanone CAS: 78-93-3	1161 mg/Kg- bw/day			
	600 mg/m3		Human Inhalation	Long Term, systemic effects
		412 mg/Kg- bw/day	Human Dermal	Long Term, systemic effects
		106 mg/m3	Human Inhalation	Long Term, systemic effects
ethylbenzene CAS: 100-41-4	180 mg/kg/day			
	293 mg/m3		Human Inhalation	Short Term, local effects
	77 mg/m3		Human Inhalation	Long Term, systemic effects
2-methoxy-1- methylethyl acetate CAS: 108-65-6		153,5 mg/kg	Human Dermal	Long Term, systemic effects
		275 mg/m3		
			Human Inhalation	Long Term, systemic effects
		54,8 mg/kg/day	Human Dermal	Long Term, systemic effects
		33 mg/m3	Human Inhalation	Long Term, systemic effects
methyl methacrylate; methyl 2- methylprop-2- enoate; methyl 2- methylpropenoate CAS: 80-62-6	210 mg/m3		Human Oral	Long Term, systemic effects
			Human Inhalation	Long Term, local effects
	1,5 mg/cm2			
	210 mg/m3		Human Dermal	Long Term, local effects
	13,67 mg/Kg- bw/day		Human Inhalation	Long Term, systemic effects
	1,5 mg/cm2		Human Dermal	Long Term, systemic effects
			Human Dermal	Short Term, local effects
		74,3 mg/m3	Human Inhalation	Long Term, systemic effects
		105 mg/m3	Human Inhalation	Long Term, local effects
		1,5 mg/cm2	Human Inhalation	Short Term, local effects
		8,2 mg/Kg- bw/day	Human Dermal	Long Term, systemic effects
Fatty acids, C18- unsatd., trimers, compds. with oleylamine CAS: 85711-55-3	0,024 mg/kg		Human Dermal	Long Term, systemic effects

0,012 mg/kg	Human Dermal	Long Term, systemic effects
0,012 mg/kg	Human Oral	Long Term, systemic effects

## 8.2. Exposure controls

### Eye protection:

Use eye protection devices. Example: closed safety visors, goggles with side protection. Do not wear contact lenses.

### Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

### Protection for hands:

Due to the synergistic effect of the substances contained in the formulation it is not possible to identify a single material capable of resisting their combination. Multilayer protective gloves for mixtures of substances may be suitable. Always refer to the protection degree and permeation rate data provided by the glove manufacturer with regard to the substances listed in point 3 of this sheet.

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

### Respiratory protection:

Use adequate protective respiratory equipment.

Use adequate protective respiratory equipment, e.g. A2 or A2P2 or A2P3.

### Thermal Hazards:

N.A.

### Environmental exposure controls:

None known

### Hygienic and Technical measures

N.A.

---

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical State Liquid

Appearance and colour: Liquid whitish

Odour: characteristic

pH: Not Relevant

Kinematic viscosity: N.A.

Melting point / freezing point: > 1 °C / < 0 °C

Initial boiling point and boiling range: > 55 °C

Flash point: < 23°C

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.

Vapour pressure: N.A.

Relative density: 0.95 kg/l

Solubility in water: N.A.

Solubility in oil: N.A.

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: 250 °C

Decomposition temperature: N.A.

Flammability: The product is classified Flam. Liq. 2 H225

#### Particle characteristics:

Particle size: N.A.

### 9.2. Other information

Viscosity: 35.00 s ( " Din cup # 4 )

No other relevant information

---

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Stable under normal conditions

### 10.2. Chemical stability

Stable under normal conditions

### 10.3. Possibility of hazardous reactions

None.

### 10.4. Conditions to avoid

Avoid accumulating electrostatic charge.

Vapours can form explosive mixtures with air.

### 10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

### 10.6. Hazardous decomposition products



None.  
vapours potentially dangerous to health may be released.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Toxicological Information of the Preparation

a) acute toxicity	Not classified Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin Irrit. 2(H315)
c) serious eye damage/irritation	The product is classified: Eye Irrit. 2(H319)
d) respiratory or skin sensitisation	Not classified Based on available data, the classification criteria are not met
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met
g) reproductive toxicity	The product is classified: Repr. 2(H361)
h) STOT-single exposure	The product is classified: STOT SE 3(H336)
i) STOT-repeated exposure	The product is classified: STOT RE 2(H373)
j) aspiration hazard	Not classified Based on available data, the classification criteria are not met

#### Toxicological information on main components of the mixture:

toluene	a) acute toxicity	LD50 Oral Rat 5000 mg/kg 24h LD50 Skin Rabbit 12267 mg/kg LC50 Inhalation Rat 25,7 mg/l 4h	
n-butyl acetate	a) acute toxicity	LC50 Inhalation Rat > 21 mg/l 4h LD50 Oral Rat = 10736 mg/kg LD50 Skin Rabbit > 14000 mg/kg	Method OECD linee guide 402
xylene [isomer mixture]	a) acute toxicity	LD50 Inhalation Rat = 27 mg/l 4h LD50 Oral Rat = 3523 mg/kg LD50 Skin Rabbit = 12126 mg/kg	
ethyl acetate	a) acute toxicity	LD50 Skin Rabbit > 20000 mg/kg LD50 Oral Rat = 5620 mg/kg LC50 Inhalation Rat > 29,3 mg/l 4h LD50 Oral Rabbit = 4934 mg/kg body weight	
	b) skin corrosion/irritation	Skin Irritant Skin Rabbit Negative	
	e) germ cell mutagenicity	Genotoxicity Negative	
	j) aspiration hazard	Respiratory Tract Corrosive Inhalation Positive	
butanone	a) acute toxicity	LD50 Oral Rat = 2737 mg/kg LD50 Skin Rabbit = 6480 mg/kg LC50 Inhalation Rat = 23,5 mg/l 8h	
	b) skin corrosion/irritation	Skin Corrosive Rabbit Negative	moderatamente irritante
ethylbenzene	a) acute toxicity	LD50 Oral Rat = 3500 mg/kg LD50 Oral Rat = 4710 mg/kg body weight LD50 Skin Rabbit = 15400 mg/kg DZSR_004 Inhalation Rat = 4000 Ppm 4h	
	d) respiratory or skin sensitisation	Skin Sensitization Skin Cavia porcellus Negative	

2-methoxy-1-methylethyl acetate	a) acute toxicity	LD50 Oral Rat = 8532 mg/kg
		LC50 Skin Rat > 5000 mg/kg
		LC50 Inhalation Mist Rat > 23,8 mg/l 6h
	b) skin corrosion/irritation	Skin Irritant Skin Rabbit Negative
	c) serious eye damage/irritation	Eye Irritant Rabbit Negative
	d) respiratory or skin sensitisation	Skin Sensitization Skin Cavia porcellus Negative
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	a) acute toxicity	LD50 Oral Rat > 7900 mg/kg
		LC50 Inhalation Rat = 29,8 mg/l 4h
		LD50 Skin Rabbit = 5000 mg/kg
Fatty acids, C18-unsatd., trimers, compds. with oleylamine	a) acute toxicity	LD50 Oral Rat Female > 2000 mg/kg
	b) skin corrosion/irritation	Skin Irritant No
		Eye Irritant Rabbit Yes

#### Endocrine disrupting properties:

No endocrine disruptor substances present in concentration >= 0.1%

#### 11.2 Information on other hazards

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar preparations, this preparation may be a skin sensitiser and an irritant.

It contains low molecular epoxy constituents which are irritating to eyes, mucous me

## SECTION 12: Ecological information

### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

#### List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

No data available for the product

#### List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
toluene	CAS: 108-88-3 - EINECS: 203-625-9 - INDEX: 601-021-00-3	a) Aquatic acute toxicity : LC50 Fish = 5,5 ml/l 96 a) Aquatic acute toxicity : EC50 Algae > 134 ml/l 72 b) Aquatic chronic toxicity : EC50 Daphnia = 3,78 mg/l 48
n-butyl acetate	CAS: 123-86-4 - EINECS: 204-658-1 - INDEX: 607-025-00-1	a) Aquatic acute toxicity : LC50 Fish = 64 mg/l 48 a) Aquatic acute toxicity : EC50 Daphnia = 73 mg/l 24 a) Aquatic acute toxicity : EC50 Algae = 674 mg/l 72
xylene [isomer mixture]	CAS: 1330-20-7 - EINECS: 215-535-7 - INDEX: 601-022-00-9	a) Aquatic acute toxicity : EC50 Daphnia = 1 mg/l 48 a) Aquatic acute toxicity : LC50 Fish = 3,2 mg/l 96

ethyl acetate	CAS: 141-78-6 - EINECS: 205-500-4 - INDEX: 607-022-00-5	a) Aquatic acute toxicity : LC50 Algae = 2,6 mg/l 73
		a) Aquatic acute toxicity : LC50 Fish = 454,7 mg/l 96
butanone	CAS: 78-93-3 - EINECS: 201-159-0 - INDEX: 606-002-00-3	a) Aquatic acute toxicity : EC50 Daphnia = 154 mg/l 48
		a) Aquatic acute toxicity : EC50 Algae = 3300 mg/l 48
		b) Aquatic chronic toxicity : NOEC Algae > 100 mg/l 72
		a) Aquatic acute toxicity : LC50 Fish > 3220 mg/l 96
ethylbenzene	CAS: 100-41-4 - EINECS: 202-849-4 - INDEX: 601-023-00-4	a) Aquatic acute toxicity : EC50 Daphnia > 520 mg/l 48
		a) Aquatic acute toxicity : LC50 Fish = 42,3 mg/l 96
2-methoxy-1-methylethyl acetate	CAS: 108-65-6 - EINECS: 203-603-9 - INDEX: 607-195-00-7	a) Aquatic acute toxicity : LC50 Fish > 100 ml/l 96 - Method OECD linee guide 203
		a) Aquatic acute toxicity : EC50 Daphnia > 500 mg/l 48 - „Method Direttiva 67/548CEE allegato V,C.2
		a) Aquatic acute toxicity : ErC50 Algae > 1000 mg/l 72 - Method OECD TG 209
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	CAS: 80-62-6 - EINECS: 201-297-1 - INDEX: 607-035-00-6	a) Aquatic acute toxicity : LC50 Fish = 191 mg/l 96
		a) Aquatic acute toxicity : EC50 Daphnia = 69 mg/l 48
Fatty acids, C18-unsatd., trimers, compds. with oleylamine	CAS: 85711-55-3 - EINECS: 288-315-1	a) Aquatic acute toxicity : EC50 Algae > 110 mg/l 72
		a) Aquatic acute toxicity : LC50 Fish > 100 mg/l 96
		a) Aquatic acute toxicity : EC50 Daphnia = 15,2 mg/l 48
		a) Aquatic acute toxicity : ErC50 Algae = 7,43 mg/l 72
		a) Aquatic acute toxicity : NOEC Fish 150 mg/l 48
		a) Aquatic acute toxicity : EC50 Active mud > 1000 mg/l 3
No endocrine disruptor substances present in concentration >= 0.1%		

## 12.2. Persistence and degradability

None known

N.A.

## 12.3. Bioaccumulative potential

N.A.

## 12.4. Mobility in soil

N.A.

## 12.5. Results of PBT and vPvB assessment

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%.

## 12.6 Endocrine disrupting properties

## 12.6 Endocrine disrupting properties

## 12.7 Other adverse effects

N.A.

# SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

---

## SECTION 14: Transport information

### 14.1. UN number or ID number

1263

### 14.2. UN proper shipping name

ADR-Shipping Name: PAINT

IATA-Technical name: PAINT

IMDG-Technical name: PAINT

### 14.3. Transport hazard class(es)

ADR-Class: 3

IATA-Class: 3

IMDG-Class: 3

### 14.4. Packing group

ADR-Packing Group: II

IATA-Packing group: II

IMDG-Packing group: II

### 14.5. Environmental hazards

Toxic Ingredients Qty: 0.00

High Toxicity Ingredients Qty: 0.00

Marine pollutant: No

Environmental Pollutant: No

### 14.6. Special precautions for user

Road and Rail ( ADR-RID ) :

ADR exempt: No

ADR-Label: 3

ADR - Hazard identification number: 33

ADR-Special Provisions: 163 367 640C 650

ADR-Transport category (Tunnel restriction code): 2 (D/E)

Air ( IATA ) :

IATA-Passenger Aircraft: 353

IATA-Cargo Aircraft: 364

IATA-Label: 3

IATA-Subsidiary hazards: -

IATA-Erg: 3L

IATA-Special Provisioning: A3 A72 A192

Sea ( IMDG ) :

IMDG-Stowage Code: Category B

IMDG-Stowage Note: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisioning: 163 367

IMDG-Page: N/A

IMDG-Label: N/A

IMDG-MFAG: N/A

### 14.7. Maritime transport in bulk according to IMO instruments

N.A.

---

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)  
Regulation (EU) n. 944/2013 (ATP 5 CLP)  
Regulation (EU) n. 605/2014 (ATP 6 CLP)  
Regulation (EU) n. 2015/1221 (ATP 7 CLP)  
Regulation (EU) n. 2016/918 (ATP 8 CLP)  
Regulation (EU) n. 2016/1179 (ATP 9 CLP)  
Regulation (EU) n. 2017/776 (ATP 10 CLP)  
Regulation (EU) n. 2018/699 (ATP 11 CLP)  
Regulation (EU) n. 2018/1480 (ATP 13 CLP)  
Regulation (EU) n. 2019/521 (ATP 12 CLP)  
Regulation (EU) n. 2020/217 (ATP 14 CLP)  
Regulation (EU) n. 2020/1182 (ATP 15 CLP)  
Regulation (EU) n. 2021/643 (ATP 16 CLP)  
Regulation (EU) n. 2020/878

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3, 40 3, 40

Restrictions related to the substances contained: 28, 29, 30, 48, 75 28, 29, 30, 48, 75

Provisions related to directive EU 2012/18 (Seveso III):

N.A.

Regulation (EU) No 649/2012 (PIC regulation)

No substances listed

German Water Hazard Class.

Class 3: extremely hazardous.

SVHC Substances:

No data available

**Dir. 2010/75/EC (VOC directive) ; Dir. 2004/42/EC (VOC directive)**

Total solid content: 25 - 26 %

Volatile Organic compounds - VOCs = 75 %

Volatile Organic compounds - VOCs = 711 g/L

Of which reactive monomers: 0 %

Total Volatile Organic Carbon (typical value): 59 %

Of which reactive monomers: 0 %

**15.2. Chemical safety assessment**

No Chemical Safety Assessment has been carried out for the mixture.

---

**SECTION 16: Other information**

Code	Description
EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

<b>Code</b>	<b>Hazard class and hazard category</b>	<b>Description</b>
2.6/2	Flam. Liq. 2	Flammable liquid, Category 2
2.6/3	Flam. Liq. 3	Flammable liquid, Category 3
3.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4
3.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
3.10/1	Asp. Tox. 1	Aspiration hazard, Category 1
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/1	Eye Dam. 1	Serious eye damage, Category 1
3.3/2	Eye Irrit. 2	Eye irritation, Category 2
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.4.2/1A	Skin Sens. 1A	Skin Sensitisation, Category 1A
3.7/2	Repr. 2	Reproductive toxicity, Category 2
3.8/3	STOT SE 3	Specific target organ toxicity — single exposure, Category 3
3.9/2	STOT RE 2	Specific target organ toxicity — repeated exposure, Category 2
4.1/A1	Aquatic Acute 1	Acute aquatic hazard, category 1
4.1/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1

**Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:**

<b>Classification according to Regulation (EC) Nr. 1272/2008</b>	<b>Classification procedure</b>
--	---------------------------------

2.6/2	On basis of test data
3.2/2	Calculation method
3.3/2	Calculation method
3.7/2	Calculation method
3.8/3	Calculation method
3.9/2	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.  
 ES: Exposure Scenario  
 GefStoffVO: Ordinance on Hazardous Substances, Germany.  
 GHS: Globally Harmonized System of Classification and Labeling of Chemicals.  
 IARC: International Agency for Research on Cancer  
 IATA: International Air Transport Association.  
 IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).  
 IC50: half maximal inhibitory concentration  
 ICAO: International Civil Aviation Organization.  
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).  
 IMDG: International Maritime Code for Dangerous Goods.  
 INCI: International Nomenclature of Cosmetic Ingredients.  
 IRCCS: Scientific Institute for Research, Hospitalization and Health Care  
 KAFH: KAFH  
 KSt: Explosion coefficient.  
 LC50: Lethal concentration, for 50 percent of test population.  
 LD50: Lethal dose, for 50 percent of test population.  
 LDLo: Leathal Dose Low  
 N.A.: Not Applicable  
 N/A: Not Applicable  
 N/D: Not defined/ Not available  
 NA: Not available  
 NIOSH: National Institute for Occupational Safety and Health  
 NOAEL: No Observed Adverse Effect Level  
 OSHA: Occupational Safety and Health Administration.  
 PBT: Persistent, Bioaccumulative and Toxic  
 PGK: Packaging Instruction  
 PNEC: Predicted No Effect Concentration.  
 PSG: Passengers  
 RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.  
 STEL: Short Term Exposure limit.  
 STOT: Specific Target Organ Toxicity.  
 TLV: Threshold Limiting Value.  
 TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).  
 vPvB: Very Persistent, Very Bioaccumulative.  
 WGK: German Water Hazard Class.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

**Paragraphs modified from the previous revision:**

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 16. OTHER INFORMATION

## Fac-simile label

# Clear ACR AS Matt topcoat

Regulation (EC) No 1272/2008 (CLP):

## Pictograms and Signal Words



Danger

## Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

## Precautionary statements

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...
P370+P378	In case of fire: Use CO <sub>2</sub> , Foam, Chemical powders For extinction.
P403+P235	Store in a well-ventilated place. Keep cool.

## Contains

toluene

n-butyl acetate

ethyl acetate

butanone

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate

May produce an allergic reaction.

Fatty acids, C18-unsatd., trimers, compds. with oleylamine

May produce an allergic reaction.

**QUANTITY:**

**SUPPLIER:**