

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:
Trade name: White ACR EXT Matt topcoat
Trade code: **TA93G20C01**
UFI: 2J99-20M8-000C-XF6Y

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Surface coating
Uses advised against: N.A.

1.3. Details of the supplier of the safety data sheet

Company: Sirca S.p.A.
Viale Roma, 85
35010 Sandono di Massanzago (PD) - ITALY
Tel. +39 0499322311
Email: safety@sirca.it

1.4. Emergency telephone number

National Poisons Information Service - Medical Toxicology Unit - London - Tel. 0171/6359191
Scottish Poisons Information Bureau - The Royal Infirmary - Edinburgh - Tel. 01/315362298
Welsh National Poisons Unit - Ward West 5 - Llandough Hospital Penarth - Cardiff - Tel. 012/22709901
Poisons Information Centre - Royal Victoria Hospital - Belfast - Tel. 012/32240503
Poisons Information centre - Beaumont Hospital - Dublin - Tel. 0103531/8379964
CAV Policlinico "Umberto I". Roma V.le del Policlinico, 155 161 Telefono 06-49978000
Osp. Niguarda Ca' Granda. Milano Piazza Ospedale Maggiore,3 20162 Telefono 02-66101029

SECTION 2: Hazards identification



2.1. Classification of the substance or mixture

Regulation (EC) n. 1272/2008 (CLP)

Flam. Liq. 2	Highly flammable liquid and vapour.
Skin Irrit. 2	Causes skin irritation.
Eye Irrit. 2	Causes serious eye irritation.
Skin Sens. 1A	May cause an allergic skin reaction.
STOT RE 2	May cause damage to organs through prolonged or repeated exposure.

Adverse physicochemical, human health and environmental effects:
No other hazards

2.2. Label elements

Regulation (EC) No 1272/2008 (CLP):

Pictograms and Signal Words



Danger

Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.

H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...
P370+P378	In case of fire: Use CO2, Foam, Chemical powders For extinction.
P403+P235	Store in a well-ventilated place. Keep cool.

Contains

reaction mass of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydrox

xylene [isomer mixture]

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate

May produce an allergic reaction.

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate.

May produce an allergic reaction.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None.

2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%.

Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Mixture identification: White ACR EXT Matt topcoat

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb.	Classification	Registration Number
12.5-20 %	n-butyl acetate	CAS:123-86-4 EC:204-658-1 Index:607-025-00-1	Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	01-2119485493-29-xxxx
12.5-20 %	xylene [isomer mixture]	CAS:1330-20-7 EC:215-535-7 Index:601-022-00-9	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Eye Irrit. 2, H319; STOT SE 3, H335; STOT RE 2, H373; Skin Irrit. 2, H315; Acute Tox. 4, H312; Acute Tox. 4, H332	01-2119488216-32-xxxx
3-5 %	2-butoxyethyl acetate; butylglycol acetate	CAS:112-07-2 EC:203-933-3 Index:607-038-00-2	Acute Tox. 4, H312; Acute Tox. 4, H332	
3-5 %	ethylbenzene	CAS:100-41-4 EC:202-849-4 Index:601-023-00-4	Flam. Liq. 2, H225; Acute Tox. 4, H332; Asp. Tox. 1, H304; STOT RE 2, H373	01-2119489370-35-xxx
1-2 %	2-methoxy-1-methylethyl acetate	CAS:108-65-6 EC:203-603-9 Index:607-195-00-7	Flam. Liq. 3, H226	01-2119475791-29-xxxx

0.5-1 %	reaction mass of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydrox	EC:400-830-7 Index:607-176-00-3	Skin Sens. 1A, H317; Aquatic Chronic 2, H411	01-0000015075-76-xxxx
0.25-0.5 %	toluene	CAS:108-88-3 EC:203-625-9 Index:601-021-00-3	Flam. Liq. 2, H225; Repr. 2, H361d; Asp. Tox. 1, H304; STOT RE 2, H373; Skin Irrit. 2, H315; STOT SE 3, H336	01-2119471310-51-xxxx
0.25-0.5 %	methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	CAS:80-62-6 EC:201-297-1 Index:607-035-00-6	Flam. Liq. 2, H225; STOT SE 3, H335; Skin Irrit. 2, H315; Skin Sens. 1, H317	01-2119452498-28-xxxx
0.1-0.2 %	Hexanoic acid, 2-ethyl-, zinctsalt, basic	CAS:85203-81-2 EC:286-272-3	Eye Irrit. 2, H319, H361d; Repr. 2, H412; Aquatic Chronic 3, H412	01-2119979093-30-xxxx
0.1-0.2 %	Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate.	EC:915-687-0	Skin Sens. 1, H317, H400; Aquatic Acute 1, H400; Aquatic Chronic 1, H410, M-Chronic:1, M-Acute:1	01-2119491304-40-xxxx
0.1-0.2 %	propylidynetrimethanol	CAS:77-99-6 EC:201-074-9	Repr. 2, H361fd	01-2119486799-10-xxxx
0.0015-0.05 %	phosphoric acid ... %, orthophosphoric acid ... %	CAS:7664-38-2 EC:231-633-2 Index:015-011-00-6	Met. Corr. 1, H290, H314 Skin Corr. 1B, H314 Eye Dam. 1, H318 Specific Concentration Limits: 10% ≤ C < 25%: Skin Irrit. 2 H315 10% ≤ C < 25%: Eye Irrit. 2 H319 25% ≤ C < 100%: Skin Corr. 1B H314	

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap.

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

Do not use eyewash or ointment of any kind (before obtaining an examination or advice from an eye specialist).

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and label hazardous.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Eye damages

Skin Irritation

Contact a poisons centre

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

In case of fire: Use CO₂, Foam, Chemical powders For extinction.

Extinguishing media which must not be used for safety reasons:

None in particular.

5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.
Cool the containers exposed to the fire with water.

5.3. Advice for firefighters

Use suitable breathing apparatus .
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:
Wear personal protection equipment.
Remove all sources of ignition.
Collect the spilled product with no-sparking tools.
Remove persons to safety.
See protective measures under point 7 and 8.
For emergency responders:
Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
Retain contaminated washing water and dispose it.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand
Eliminate all unguarded flames and possible sources of ignition. Do not smoke.
Collect spilled material with non-sparking equipment.
Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep away from flame and sparks. Avoid accumulating electrostatic charge.
Place recipients on the ground whilst decanting, and wear anti-static clothing and shoes.
Avoid contact with skin and eyes, inhalation of vapours and mists.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contaminated clothing should be changed before entering eating areas.
Do not eat or drink while working.
Do not smoke while working.
See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Always keep in a well ventilated place.
Store at below 30 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

7.3. Specific end use(s)

No further recommendations. Refer to point 1.2

Recommendation(s)

None in particular

Industrial sector specific solutions:

None in particular

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Community Occupational Exposure Limits (OEL)

OEL Type	Long Term mg/m3	Long Term ppm	Short Term mg/m3	Short Term ppm	Notes
-------------	--------------------	------------------	---------------------	-------------------	-------

xylene [isomer mixture] CAS: 1330-20-7	ACGIH	50	100	100	150	A4, BEI - URT and eye irr, CNS impair
2-butoxyethyl acetate; butylglycol acetate CAS: 112-07-2	EU	133	20	333	50	Skin
	ACGIH		20			A3 - Hemolysis
ethylbenzene CAS: 100-41-4	ACGIH	100,000	20,000	150,000		A3, BEI - URT irr, kidney dam (nephropathy), cochlear impair
	EU					Skin
2-methoxy-1-methylethyl acetate CAS: 108-65-6	EU	275	50	550	100	Skin
toluene CAS: 108-88-3	ACGIH	50	20			A4, BEI - Visual impair, female repro, pregnancy loss
methyl methacrylate; methyl 2-methylprop-2- enoate; methyl 2- methylpropenoate CAS: 80-62-6	EU		50		100	
	ACGIH		50		100	
phosphoric acid ... %, orthophosphoric acid ... % CAS: 7664-38-2	EU	1		2		
	ACGIH	1		3		

Predicted No Effect Concentration (PNEC) values

	PNEC Limit	Exposure Route	Exposure Frequency	Remark
n-butyl acetate CAS: 123-86-4	0,18 mg/l	Fresh Water		
	0,018 mg/l	Marine water		
	0,981 mg/kg	Freshwater sediments		
	0,098 mg/kg	Marine water sediments		
	0,09 mg/kg	Soil (agricultural)		
	35,6 mg/l	STP		
xylene [isomer mixture] CAS: 1330-20-7	0,327 mg/l	Fresh Water		
	0,327 mg/l	Fresh Water		
	0,327 mg/l	occasional emission		
	6,58 mg/l	Microorganisms in sewage treatments		
	2,31 mg/kg	Soil (agricultural)		dry
	12,46 mg/kg	Marine water sediments		dry
	12,46 mg/kg	Freshwater sediments		dry
2-butoxyethyl acetate; butylglycol acetate CAS: 112-07-2	0,304 mg/l	Fresh Water		
	0,03 mg/l	Marine water		
	2,03 mg/kg	Freshwater sediments		
	0,203 mg/kg	Marine water sediments		
	90 mg/l	STP		
	0,68 mg/kg	Soil		
ethylbenzene CAS: 100-41-4	0,1 mg/l	Fresh Water		
	0,01 mg/l	Marine water		
	13,7 mg/l	Freshwater sediments		
	13,7 mg/l	Marine water sediments		

	0,1 mg/l	occasional emission	
2-methoxy-1-methylethyl acetate CAS: 108-65-6	0,635 mg/l	Fresh Water	
	0,064 mg/l	Marine water	
	0,329 mg/kg	Marine water sediments	dry
	3,29 mg/kg	Freshwater sediments	dry
	0,29 mg/kg	Soil (agricultural)	dry
	100 mg/l	STP	
reaction mass of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydrox	0,0023 mg/l	Fresh Water	
	0,00023 mg/l	Marine water	
	0,028 mg/l	occasional emission	
	10 mg/l	STP	
	3,06 mg/kg	Freshwater sediments	
	0,306 mg/kg	Marine water sediments	
	2 mg/kg	Soil (agricultural)	
toluene CAS: 108-88-3	0,68 mg/l	Fresh Water	
	0,68 mg/l	Marine water	
	2,89 mg/kg	Soil (agricultural)	
	16,39 mg/l	Marine water sediments	
	16,39 mg/l	Freshwater sediments	
	13,61 mg/l	STP	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate CAS: 80-62-6	0,94 mg/l	Fresh Water	
	0,094 mg/l	Marine water	
	5,74 mg/kg	Freshwater sediments	
	1,47 mg/kg	Soil (agricultural)	
	0,94 mg/l	occasional emission	
	10 mg/l	Microorganisms in sewage treatments	
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate.	0,0022 mg/l	Fresh Water	
	0,00022 mg/l	Marine water	
	0,009 mg/l	occasional emission	
	1,05 mg/kg	Freshwater sediments	
	0,11 mg/kg	Marine water sediments	
	0,21 mg/kg	Soil (agricultural)	
	1 mg/l	STP	
propylidynetrimethanol CAS: 77-99-6	1 mg/l	Fresh Water	
	0,1 mg/l	Marine water	
	10 mg/l	occasional emission	

100 mg/l	Microorganisms in sewage treatments
0,351 mg/kg	Marine water sediments
3,505 mg/kg	Freshwater sediments
0,241 mg/kg	Soil (agricultural)
100 mg/l	STP

Derived No Effect Level (DNEL) values

	Worker Industry	Worker Professional	Consumer	Exposure Route	Exposure Frequency	Remark
n-butyl acetate CAS: 123-86-4		600 mg/m3		Human Inhalation	Short Term, local effects	
		300 mg/m3		Human Inhalation	Long Term, local effects	
		11 mg/kg		Human Dermal	Long Term, systemic effects	
		11 mg/kg		Human Dermal	Short Term, systemic effects	
			300 mg/kg	Human Inhalation	Short Term, local effects	
			35,7 mg/m3	Human Inhalation	Long Term, local effects	
			6 mg/kg	Human Dermal	Short Term, systemic effects	
			2 mg/kg	Human Oral	Long Term, systemic effects	
			2 mg/kg	Human Oral	Short Term, systemic effects	
				Human Dermal	Long Term, systemic effects	
xylene [isomer mixture] CAS: 1330-20-7	180 mg/Kg-bw/day					
		77 mg/m3		Human Inhalation	Long Term, systemic effects	
			108 mg/Kg-bw/day	Human Dermal	Long Term, systemic effects	
			1872 mg/m3	Human Inhalation	Long Term, local effects	
			12,5 mg/Kg-bw/day	Human Oral	Long Term, systemic effects	
2-butoxyethyl acetate; butylglycol acetate CAS: 112-07-2	4,3 mg/kg/day			Human Oral	Long Term, systemic effects	
		333 mg/m3	166 mg/m3	Human Inhalation	Short Term, local effects	
		133 mg/m3		Human Inhalation	Long Term, systemic effects	
		102 mg/kg/day	36	Human Dermal	Short Term, systemic effects	
ethylbenzene CAS: 100-41-4	180 mg/kg/day			Human Dermal	Long Term, systemic effects	
		293 mg/m3		Human Inhalation	Short Term, local effects	
		77 mg/m3		Human Inhalation	Long Term, systemic effects	
2-methoxy-1-methylethyl acetate CAS: 108-65-6		153,5 mg/kg		Human Dermal	Long Term, systemic effects	
		275 mg/m3		Human Inhalation	Long Term, systemic effects	
			54,8 mg/kg/day	Human Dermal	Long Term, systemic effects	
			33 mg/m3	Human Inhalation	Long Term, systemic effects	
			1,67 mg/kg/day	Human Oral	Long Term, systemic effects	
reaction mass of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl) propionyl-omega-hydroxypoly (oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydrox	0,35 mg/m3			Human Inhalation	Long Term, systemic effects	
	0,5 mg/kg			Human Dermal	Long Term, systemic effects	

toluene CAS: 108-88-3		0,085 mg/m3	Human Inhalation	Long Term, systemic effects
		0,25 mg/kg	Human Dermal	Long Term, systemic effects
		0,025 mg/kg	Human Oral	Long Term, systemic effects
		226 mg/m3	Human Inhalation	Short Term, systemic effects
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate CAS: 80-62-6		226 mg/m3	Human Inhalation	Short Term, local effects
		226 mg/m3	Human Dermal	Long Term, systemic effects
		56,5 mg/m3	Human Inhalation	Long Term, systemic effects
		8,13 mg/Kg-bw/day	Human Oral	Long Term, systemic effects
	384 mg/kg/day		Human Dermal	Long Term, systemic effects
	384 mg/m3		Human Inhalation	Short Term, systemic effects
	192 mg/m3		Human Inhalation	Long Term, systemic effects
	210 mg/m3		Human Inhalation	Long Term, local effects
	1,5 mg/cm2		Human Dermal	Long Term, local effects
	210 mg/m3		Human Inhalation	Long Term, systemic effects
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate.	13,67 mg/Kg-bw/day		Human Dermal	Long Term, systemic effects
	1,5 mg/cm2		Human Dermal	Short Term, local effects
		74,3 mg/m3	Human Inhalation	Long Term, systemic effects
		105 mg/m3	Human Inhalation	Long Term, local effects
		1,5 mg/cm2	Human Dermal	Short Term, local effects
		8,2 mg/Kg-bw/day	Human Dermal	Long Term, systemic effects
	3,53 mg/m3		Human Inhalation	Long Term, systemic effects
	2 mg/kg		Human Dermal	Long Term, systemic effects
		1 mg/kg	Human Dermal	Long Term, systemic effects
		0,87 mg/m3	Human Inhalation	Long Term, systemic effects
propylidynetrimethanol CAS: 77-99-6		0,5 mg/kg	Human Oral	Long Term, systemic effects
	138,8 mg/kg		Human Dermal	Short Term, systemic effects
	3037,3 mg/m3		Human Inhalation	Short Term, systemic effects
	0,67 mg/kg		Human Dermal	Long Term, systemic effects
	6,61 mg/m3		Human Inhalation	Long Term, systemic effects
		83,3 mg/kg	Human Dermal	Short Term, systemic effects
		925 mg/kg	Human Inhalation	Short Term, systemic effects
		50 mg/kg	Human Oral	Short Term, systemic effects
		1,68 mg/kg	Human Dermal	Long Term, systemic effects
		5,03 mg/m3	Human Inhalation	Long Term, systemic effects
phosphoric acid ... %, orthophosphoric acid ... % CAS: 7664-38-2		1,68 mg/kg	Human Oral	Long Term, systemic effects
	1 mg/m3		Human Inhalation	Long Term, local effects
	2 mg/m3		Human Inhalation	Short Term, local effects

8.2. Exposure controls

Eye protection:

Use eye protection devices. Example: closed safety visors, goggles with side protection. Do not wear contact lenses.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Due to the synergistic effect of the substances contained in the formulation it is not possible to identify a single material capable of resisting their combination. Multilayer protective gloves for mixtures of substances may be suitable. Always refer to the protection degree and permeation rate data provided by the glove manufacturer with regard to the substances listed in point 3 of this sheet.

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use adequate protective respiratory equipment, e.g. A2 or A2P2 or A2P3.

Thermal Hazards:

N.A.

Environmental exposure controls:

None known

Hygienic and Technical measures

N.A.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical State Liquid

Appearance and colour: Liquid white

Odour: characteristic

pH: Not Relevant

Kinematic viscosity: N.A.

Melting point / freezing point: > 1 °C / < 0 °C

Initial boiling point and boiling range: > 55 °C

Flash point: < 23°C

Upper/lower flammability or explosive limits: N.A.

Vapour density: N.A.

Vapour pressure: N.A.

Relative density: 1.32 kg/l

Solubility in water: N.A.

Solubility in oil: N.A.

Partition coefficient (n-octanol/water): N.A.

Auto-ignition temperature: 250 °C

Decomposition temperature: N.A.

Flammability: The product is classified Flam. Liq. 2 H225

Particle characteristics:

Particle size: N.A.

9.2. Other information

Viscosity: 90.00 s (" Din cup # 6)

No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Avoid accumulating electrostatic charge.

Vapours can form explosive mixtures with air.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

None.

vapours potentially dangerous to health may be released.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological Information of the Preparation

a) acute toxicity	Not classified Based on available data, the classification criteria are not met
b) skin corrosion/irritation	The product is classified: Skin Irrit. 2(H315)
c) serious eye damage/irritation	The product is classified: Eye Irrit. 2(H319)
d) respiratory or skin sensitisation	The product is classified: Skin Sens. 1A(H317)
e) germ cell mutagenicity	Not classified Based on available data, the classification criteria are not met
f) carcinogenicity	Not classified Based on available data, the classification criteria are not met
g) reproductive toxicity	Not classified Based on available data, the classification criteria are not met
h) STOT-single exposure	Not classified Based on available data, the classification criteria are not met
i) STOT-repeated exposure	The product is classified: STOT RE 2(H373)
j) aspiration hazard	Not classified Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

n-butyl acetate	a) acute toxicity	LC50 Inhalation Rat > 21 mg/l 4h LD50 Oral Rat = 10736 mg/kg LD50 Skin Rabbit > 14000 mg/kg	Method OECD linee guide 402
xylene [isomer mixture]	a) acute toxicity	LD50 Inhalation Rat = 27 mg/l 4h LD50 Oral Rat = 3523 mg/kg LD50 Skin Rabbit = 12126 mg/kg	
2-butoxyethyl acetate; butylglycol acetate	a) acute toxicity	LD50 Oral Rat 1880 mg/kg body weight LD50 Skin Rabbit 1500 mg/kg body weight LC50 Inhalation Rat > 400 Ppm 4h	
ethylbenzene	a) acute toxicity d) respiratory or skin sensitisation	LD50 Oral Rat = 3500 mg/kg LD50 Oral Rat = 4710 mg/kg body weight LD50 Skin Rabbit = 15400 mg/kg DZSR_004 Inhalation Rat = 4000 Ppm 4h Skin Sensitization Skin Cavia porcellus Negative	
2-methoxy-1-methylethyl acetate	a) acute toxicity b) skin corrosion/irritation c) serious eye damage/irritation d) respiratory or skin sensitisation	LD50 Oral Rat = 8532 mg/kg LC50 Skin Rat > 5000 mg/kg LC50 Inhalation Mist Rat > 23,8 mg/l 6h Skin Irritant Skin Rabbit Negative Eye Irritant Rabbit Negative Skin Sensitization Skin Cavia porcellus Negative	
reaction mass of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-	a) acute toxicity	LD50 Oral Rat > 5000 mg/kg	

omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydrox

		LD50 Skin Rat > 2000 mg/kg
		LC50 Inhalation Rat > 5,8 mg/l 4h
	b) skin corrosion/irritation	Skin Irritant Rabbit Negative
	c) serious eye damage/irritation	Eye Irritant Negative
	d) respiratory or skin sensitisation	Skin Sensitization Positive
	e) germ cell mutagenicity	Mutagenesis Negative
	g) reproductive toxicity	Reproductive Toxicity Negative
toluene	a) acute toxicity	LD50 Oral Rat 5000 mg/kg 24h LD50 Skin Rabbit 12267 mg/kg LC50 Inhalation Rat 25,7 mg/l 4h
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	a) acute toxicity	LD50 Oral Rat > 7900 mg/kg LC50 Inhalation Rat = 29,8 mg/l 4h LD50 Skin Rabbit = 5000 mg/kg
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate.	a) acute toxicity	LD50 Oral Rat > 3230 mg/kg
	b) skin corrosion/irritation	Skin Irritant Rabbit Negative
	c) serious eye damage/irritation	Eye Irritant Rabbit Negative
	d) respiratory or skin sensitisation	Skin Sensitization Cavia porcellus Positive
propylidynetrimethanol	a) acute toxicity	LD50 Oral Rat 14700 mg/kg LC50 Inhalation Rat > 0,85 mg/l 4h LD50 Skin Rabbit > 10000 mg/kg

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration >= 0.1%

11.2 Information on other hazards

Based on the properties of the epoxy constituent(s) and considering toxicological data on similar preparations, this preparation may be a skin sensitiser and an irritant.

It contains low molecular epoxy constituents which are irritating to eyes, mucous me

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

Not classified for environmental hazards.

No data available for the product

List of Eco-Toxicological properties of the components

Component	Ident. Numb.	Ecotox Data
n-butyl acetate	CAS: 123-86-4 - EINECS: 204- 658-1 - INDEX: 607-025-00-1	a) Aquatic acute toxicity : LC50 Fish = 64 mg/l 48 a) Aquatic acute toxicity : EC50 Daphnia = 73 mg/l 24 a) Aquatic acute toxicity : EC50 Algae = 674 mg/l 72
xylene [isomer mixture]	CAS: 1330-20-7 - EINECS: 215- 535-7 - INDEX: 601-022-00-9	a) Aquatic acute toxicity : EC50 Daphnia = 1 mg/l 48 a) Aquatic acute toxicity : LC50 Fish = 3,2 mg/l 96 a) Aquatic acute toxicity : LC50 Algae = 2,6 mg/l 73
2-butoxyethyl acetate; butylglycol acetate	CAS: 112-07-2 - EINECS: 203- 933-3 - INDEX: 607-038-00-2	a) Aquatic acute toxicity : LC50 Fish 28 mg/l 96 a) Aquatic acute toxicity : EC50 Daphnia 37 mg/l 48 a) Aquatic acute toxicity : EC50 Algae 1570 mg/l 72
ethylbenzene	CAS: 100-41-4 - EINECS: 202- 849-4 - INDEX: 601-023-00-4	a) Aquatic acute toxicity : LC50 Fish = 42,3 mg/l 96
2-methoxy-1-methylethyl acetate	CAS: 108-65-6 - EINECS: 203- 603-9 - INDEX: 607-195-00-7	a) Aquatic acute toxicity : LC50 Fish > 100 ml/l 96 - Method OECD linee guide 203 a) Aquatic acute toxicity : EC50 Daphnia > 500 mg/l 48 - „Method Direttiva 67/548CEE allegato V,C.2 a) Aquatic acute toxicity : ErC50 Algae > 1000 mg/l 72 - Method OECD TG 209
reaction mass of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydrox	EINECS: 400- 830-7 - INDEX: 607-176-00-3	a) Aquatic acute toxicity : LC50 Fish = 2,8 mg/l 96 a) Aquatic acute toxicity : EC50 Daphnia = 4 mg/l 96 a) Aquatic acute toxicity : EC50 Algae > 100 mg/l 72 a) Aquatic acute toxicity : CE10 Algae > 10 mg/l 72 a) Aquatic acute toxicity : EC50 Active mud > 1000 mg/l 3 b) Aquatic chronic toxicity : NOEC Daphnia 0,78 mg/l 504
toluene	CAS: 108-88-3 - EINECS: 203- 625-9 - INDEX: 601-021-00-3	a) Aquatic acute toxicity : LC50 Fish = 5,5 ml/l 96 a) Aquatic acute toxicity : EC50 Algae > 134 ml/l 72 b) Aquatic chronic toxicity : EC50 Daphnia = 3,78 mg/l 48
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	CAS: 80-62-6 - EINECS: 201- 297-1 - INDEX: 607-035-00-6	a) Aquatic acute toxicity : LC50 Fish = 191 mg/l 96 a) Aquatic acute toxicity : EC50 Daphnia = 69 mg/l 48 a) Aquatic acute toxicity : EC50 Algae > 110 mg/l 72
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate.	EINECS: 915- 687-0	a) Aquatic acute toxicity : LC50 Fish = 0,97 mg/l a) Aquatic acute toxicity : EC50 Daphnia = 20 mg/l

propylidynetrimehtanol	CAS: 77-99-6 - EINECS: 201-074-9	a) Aquatic acute toxicity : EC50 Algae = 1,68 mg/l f) Effects in sewage plants : EC50 Active mud > 100 mg/l b) Aquatic chronic toxicity : NOEC Daphnia = 1 mg/kg - (21d)
		a) Aquatic acute toxicity : LC50 Fish > 1000 mg/l 96
phosphoric acid ... %, orthophosphoric acid ... %	CAS: 7664-38-2 - EINECS: 231-633-2 - INDEX: 015-011-00-6	a) Aquatic acute toxicity : EC50 Daphnia = 13000 mg/l 24 a) Aquatic acute toxicity : EC50 Algae > 1000 ml/l 72 b) Aquatic chronic toxicity : NOEC Daphnia 1000 ml/l 500
		a) Aquatic acute toxicity : EC50 Daphnia > 100 mg/l 48 a) Aquatic acute toxicity : ErC50 Algae > 100 mg/l 72

No endocrine disruptor substances present in concentration >= 0.1%

12.2. Persistence and degradability

None known

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1%.

12.6 Endocrine disrupting properties

12.6 Endocrine disrupting properties

12.7 Other adverse effects

N.A.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

14.1. UN number or ID number

1263

14.2. UN proper shipping name

ADR-Shipping Name: PAINT

IATA-Technical name: PAINT

IMDG-Technical name: PAINT

14.3. Transport hazard class(es)

ADR-Class: 3

IATA-Class: 3

IMDG-Class: 3

14.4. Packing group

ADR-Packing Group: II

IATA-Packing group: II

IMDG-Packing group: II

14.5. Environmental hazards

Toxic Ingredients Qty: 0.00

High Toxicity Ingredients Qty: 0.00

Marine pollutant: No

Environmental Pollutant: No

14.6. Special precautions for user

Road and Rail (ADR-RID) :

ADR exempt: No

ADR-Label: 3

ADR - Hazard identification number: 33

ADR-Special Provisions: 163 367 640C 650

ADR-Transport category (Tunnel restriction code): 2 (D/E)

Air (IATA) :

IATA-Passenger Aircraft: 353

IATA-Cargo Aircraft: 364

IATA-Label: 3

IATA-Subsidiary hazards: -

IATA-Erg: 3L

IATA-Special Provisioning: A3 A72 A192

Sea (IMDG) :

IMDG-Stowage Code: Category B

IMDG-Stowage Note: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisioning: 163 367

IMDG-Page: N/A

IMDG-Label: N/A

IMDG-MFAG: N/A

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)

Dir. 2000/39/EC (Occupational exposure limit values)

Regulation (EC) n. 1907/2006 (REACH)

Regulation (EC) n. 1272/2008 (CLP)

Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013

Regulation (EU) n. 286/2011 (ATP 2 CLP)

Regulation (EU) n. 618/2012 (ATP 3 CLP)

Regulation (EU) n. 487/2013 (ATP 4 CLP)

Regulation (EU) n. 944/2013 (ATP 5 CLP)

Regulation (EU) n. 605/2014 (ATP 6 CLP)

Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Regulation (EU) n. 2016/918 (ATP 8 CLP)

Regulation (EU) n. 2016/1179 (ATP 9 CLP)

Regulation (EU) n. 2017/776 (ATP 10 CLP)

Regulation (EU) n. 2018/699 (ATP 11 CLP)

Regulation (EU) n. 2018/1480 (ATP 13 CLP)

Regulation (EU) n. 2019/521 (ATP 12 CLP)

Regulation (EU) n. 2020/217 (ATP 14 CLP)

Regulation (EU) n. 2020/1182 (ATP 15 CLP)

Regulation (EU) n. 2021/643 (ATP 16 CLP)

Regulation (EU) n. 2020/878

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product: 3, 40 3, 40

Restrictions related to the substances contained: 28, 29, 30, 48, 75 28, 29, 30, 48, 75

Provisions related to directive EU 2012/18 (Seveso III):

N.A.

Regulation (EU) No 649/2012 (PIC regulation)

No substances listed

German Water Hazard Class.

Class 3: extremely hazardous.

SVHC Substances:

No data available

Dir. 2010/75/EC (VOC directive) ; Dir. 2004/42/EC (VOC directive)

Total solid content: 57 - 59 %

Volatile Organic compounds - VOCs = 42 %

Volatile Organic compounds - VOCs = 558 g/L

Of which reactive monomers: 0 %

Total Volatile Organic Carbon (typical value): 31 %

Of which reactive monomers: 0 %

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information**Code Description**

EUH066	Repeated exposure may cause skin dryness or cracking.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H290	May be corrosive to metals.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Code	Hazard class and hazard category	Description
2.16/1	Met. Corr. 1	Substance or mixture corrosive to metals, Category 1
2.6/2	Flam. Liq. 2	Flammable liquid, Category 2
2.6/3	Flam. Liq. 3	Flammable liquid, Category 3
3.1/4/Dermal	Acute Tox. 4	Acute toxicity (dermal), Category 4
3.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
3.10/1	Asp. Tox. 1	Aspiration hazard, Category 1
3.2/1B	Skin Corr. 1B	Skin corrosion, Category 1B
3.2/2	Skin Irrit. 2	Skin irritation, Category 2
3.3/1	Eye Dam. 1	Serious eye damage, Category 1
3.3/2	Eye Irrit. 2	Eye irritation, Category 2
3.4.2/1	Skin Sens. 1	Skin Sensitisation, Category 1
3.4.2/1A	Skin Sens. 1A	Skin Sensitisation, Category 1A
3.7/2	Repr. 2	Reproductive toxicity, Category 2
3.8/3	STOT SE 3	Specific target organ toxicity — single exposure, Category 3
3.9/2	STOT RE 2	Specific target organ toxicity — repeated exposure, Category 2
4.1/A1	Aquatic Acute 1	Acute aquatic hazard, category 1
4.1/C1	Aquatic Chronic 1	Chronic (long term) aquatic hazard, category 1

4.1/C2	Aquatic Chronic 2	Chronic (long term) aquatic hazard, category 2
4.1/C3	Aquatic Chronic 3	Chronic (long term) aquatic hazard, category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008

[CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
--	---------------------------------

2.6/2	On basis of test data
3.2/2	Calculation method
3.3/2	Calculation method
3.4.2/1A	Calculation method
3.9/2	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

Legend to abbreviations and acronyms used in the safety data sheet:

ACGIH: American Conference of Governmental Industrial Hygienists

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AND: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

BCF: Biological Concentration Factor

BEI: Biological Exposure Index

BOD: Biochemical Oxygen Demand

CAS: Chemical Abstracts Service (division of the American Chemical Society).

CAV: Poison Center

CE: European Community

CLP: Classification, Labeling, Packaging.

CMR: Carcinogenic, Mutagenic and Reprotoxic

COD: Chemical Oxygen Demand

COV: Volatile Organic Compound

CSA: Chemical Safety Assessment

CSR: Chemical Safety Report

DMEL: Derived Minimal Effect Level

DNEL: Derived No Effect Level.

DPD: Dangerous Preparations Directive

DSD: Dangerous Substances Directive

EC50: Half Maximal Effective Concentration

ECHA: European Chemicals Agency

EINECS: European Inventory of Existing Commercial Chemical Substances.

ES: Exposure Scenario

GefStoffVO: Ordinance on Hazardous Substances, Germany.

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

IARC: International Agency for Research on Cancer

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

IC50: half maximal inhibitory concentration

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

IMDG: International Maritime Code for Dangerous Goods.

INCI: International Nomenclature of Cosmetic Ingredients.

IRCCS: Scientific Institute for Research, Hospitalization and Health Care

KAFH: KAFH

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

LDLo: Leathal Dose Low

N.A.: Not Applicable

N/A: Not Applicable

N/D: Not defined/ Not available

NA: Not available

NIOSH: National Institute for Occupational Safety and Health

NOAEL: No Observed Adverse Effect Level

OSHA: Occupational Safety and Health Administration.

PBT: Persistent, Bioaccumulative and Toxic

PGK: Packaging Instruction

PNEC: Predicted No Effect Concentration.

PSG: Passengers

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

vPvB: Very Persistent, Very Bioaccumulative.

WGK: German Water Hazard Class.

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

Paragraphs modified from the previous revision:

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 16. OTHER INFORMATION

Fac-simile label

White ACR EXT Matt topcoat

Regulation (EC) No 1272/2008 (CLP):

Pictograms and Signal Words



Danger

Hazard statements

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...
P370+P378	In case of fire: Use CO ₂ , Foam, Chemical powders For extinction.
P403+P235	Store in a well-ventilated place. Keep cool.

Contains

reaction mass of alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-omega-hydroxypoly(oxyethylene) and alpha-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydrox

xylene [isomer mixture]

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate

May produce an allergic reaction.

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate.

May produce an allergic reaction.

QUANTITY:

SUPPLIER: