

	KAYALAR KIMYA SAN.VE TIC.A.S.	Revision nr. 3 Dated 18/12/2023 Printed on 26/02/2024
	EMP2013.25.0001 POLYURETHANE PAINT MATT WHITE	Page n. 1/17 Replaced revision:2 (Printed on: 06/05/2021)

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier Code: Product name	EMP2013.25.0001 POLYURETHANE PAINT MATT WHITE
1.2. Relevant identified uses of the substance or mixture and uses advised against Intended use	Wood coatings
1.3. Details of the supplier of the safety data sheet Name Full address District and Country e-mail address of the competent person responsible for the Safety Data Sheet Supplier:	KAYALAR KIMYA SAN.VE TIC.A.S. Tepeören Kimya Sanayicileri O.S.B, Tem Yanyol F1 Blok 34956 İstanbul (Tuzla) TURKEY Tel. +90 216-5930727 Fax +90 216-5931850 help@kayalarkimya.com.tr Kayalar Kimya San. Ve Tic. A.S.
1.4. Emergency telephone number For urgent inquiries refer to	HEADQUARTERS: KAYALAR KIMYA SAN.VE TIC. A.Ş. TURKEY TEL:+90 216-5930727

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet. Hazard classification and indication: Flammable liquid, category 3 Skin irritation, category 2	H226 H315	Flammable liquid and vapour. Causes skin irritation.
2.2. Label elements Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.		

	KAYALAR KIMYA SAN.VE TIC.A.S.	Revision nr. 3
	EMP2013.25.0001 POLYURETHANE PAINT MATT WHITE	Dated 18/12/2023 Printed on 26/02/2024 Page n. 2/17 Replaced revision:2 (Printed on: 06/05/2021)

Hazard pictograms:



Signal words: Warning

Hazard statements:

- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Precautionary statements:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P280 Wear protective gloves/ protective clothing / eye protection / face protection.
- P370+P378 In case of fire: use foam, fire-extinguishing powder, carbonsioxide to extinguish.
- P264 Wash hands thoroughly after handling.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
XYLENE		
INDEX 601-022-00-9	20 ≤ x < 30	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Irrit. 2 H315, Classification note according to Annex VI to the CLP Regulation: C
EC 215-535-7		ATE Dermal: 1100 mg/kg, ATE Inhalation vapours: 11 mg/l
CAS 1330-20-7		
REACH Reg. 01-2119488216-32-XXXX		
TITANIUM DIOXIDE [in powder form contain ing 1 % or more of particles with aerodynamic dia meter ≤ 10 µm]		
INDEX 022-006-00-2	10 ≤ x < 20	Carc. 2 H351, Classification note according to Annex VI to the CLP

	KAYALAR KIMYA SAN.VE TIC.A.S.	Revision nr. 3 Dated 18/12/2023 Printed on 26/02/2024
	EMP2013.25.0001 POLYURETHANE PAINT MATT WHITE	Page n. 3/17 Replaced revision:2 (Printed on: 06/05/2021)

Regulation: 10, V, W		
EC 236-675-5		
CAS 13463-67-7		
REACH Reg. 01-2119489379-17-XXXX		
N-BUTYL ACETATE		
INDEX 607-025-00-1	1 ≤ x < 3	Flam. Liq. 3 H226, STOT SE 3 H336, EUH066
EC 204-658-1		
CAS 123-86-4		
REACH Reg. 01-2119485493-29-XXXX		
HYDROCARBONS, C9, AROMATICS		
INDEX -	1 ≤ x < 3	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H335, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066
EC 918-668-5		
CAS 64742-95-6		
2-METHOXY-1-METHYLETHYL ACETATE		
INDEX 607-195-00-7	0,5 ≤ x < 1	Flam. Liq. 3 H226
EC 203-603-9		
CAS 108-65-6		
REACH Reg. 01-2119475791-29-XXXX		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.
SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.
INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.
INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT
Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

	KAYALAR KIMYA SAN.VE TIC.A.S.	Revision nr. 3 Dated 18/12/2023 Printed on 26/02/2024
	EMP2013.25.0001 POLYURETHANE PAINT MATT WHITE	Page n. 4/17 Replaced revision:2 (Printed on: 06/05/2021)

UNSUITABLE EXTINGUISHING EQUIPMENT
Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE
Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION
Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS
Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.
Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.
Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the

product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

2-METHOXY-1-METHYLETHYL ACETATE
Store in an inert atmosphere, sheletered from moisture because it hydrolises easily.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
EST	Eesti	Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoiu ja tööohutuse nõuded ning töökeskkonna keemiliste ohutegurite piirnormid [RT I, 17.10.2019, 1 - jõust. 17.01.2020]
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
TUR	Türkiye	Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2022

XYLENE Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	221	50	442	100	SKIN
VLA	ESP	221	50	442	100	SKIN
TLV	EST	200	50	450	100	SKIN
VLEP	ITA	221	50	442	100	SKIN
VLE	PRT	221	50	442	100	SKIN
NDS/NDSCh	POL	100		200		SKIN
TLV	ROU	221	50	442	100	SKIN

ESD	TUR	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH			20			
2-METHOXY-1-METHYLETHYL ACETATE						
Threshold Limit Value						
Type	Country	TWA/8h	STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	275	50	550	100	SKIN
VLA	ESP	275	50	550	100	SKIN
TLV	EST	275	50	550	100	SKIN
VLEP	ITA	275	50	550	100	SKIN
VLE	PRT	275	50	550	100	SKIN
NDS/NDSch	POL	260		520		SKIN
TLV	ROU	275	50	550	100	SKIN
ESD	TUR	275	50	550	100	SKIN
WEL	GBR	274	50	548	100	SKIN
OEL	EU	275	50	550	100	SKIN
N-BUTYL ACETATE						
Threshold Limit Value						
Type	Country	TWA/8h	STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	710		950		
VLA	ESP	241	50	724	150	
TLV	EST	500	100	700	150	
VLEP	ITA	241	50	723	150	
VLE	PRT	241	50	723	150	
NDS/NDSch	POL	240		720		
TLV	ROU	241	50	723	150	
WEL	GBR	724	150	966	200	
OEL	EU	241	50	723	150	
TLV-ACGIH			50		150	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

	KAYALAR KIMYA SAN.VE TIC.A.S.	Revision nr. 3 Dated 18/12/2023 Printed on 26/02/2024
	EMP2013.25.0001 POLYURETHANE PAINT MATT WHITE	Page n. 7/17 Replaced revision:2 (Printed on: 06/05/2021)

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.
When choosing personal protective equipment, ask your chemical substance supplier for advice.
Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.
The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.
The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type AX filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).
If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	white	
Odour	characteristic of solvent	
Melting point / freezing point	not available	
Initial boiling point	not available	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	

	KAYALAR KIMYA SAN.VE TIC.A.S.	Revision nr. 3
	EMP2013.25.0001 POLYURETHANE PAINT MATT WHITE	Dated 18/12/2023 Printed on 26/02/2024 Page n. 8/17 Replaced revision:2 (Printed on: 06/05/2021)

Flash point	23 ≤ T ≤ 60 °C
Auto-ignition temperature	not available
Decomposition temperature	not available
pH	not available
Kinematic viscosity	>20,5 mm2/sec (40°C)
Solubility	not available
Partition coefficient: n-octanol/water	not available
Vapour pressure	not available
Density and/or relative density	1,38 ± 0,03 Kg/l
Relative vapour density	not available
Particle characteristics	not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2004/42/EC) : 27,96 % - 385,81 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

2-METHOXY-1-METHYLETHYL ACETATE

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

N-BUTYL ACETATE

Decomposes on contact with: water.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

	KAYALAR KIMYA SAN.VE TIC.A.S.	Revision nr. 3
	EMP2013.25.0001 POLYURETHANE PAINT MATT WHITE	Dated 18/12/2023 Printed on 26/02/2024 Page n. 9/17 Replaced revision:2 (Printed on: 06/05/2021)

XYLENE

Stable in normal conditions of use and storage.Reacts violently with: strong oxidants,strong acids,nitric acid,perchlorates.May form explosive mixtures with: air.

2-METHOXY-1-METHYLETHYL ACETATE

May react violently with: oxidising substances,strong acids,alkaline metals.

N-BUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents.May react dangerously with: alkaline hydroxides,potassium tert-butoxide.Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

N-BUTYL ACETATE

Avoid exposure to: moisture,sources of heat,naked flames.

10.5. Incompatible materials

2-METHOXY-1-METHYLETHYL ACETATE

Incompatible with: oxidising substances,strong acids,alkaline metals.

N-BUTYL ACETATE

Incompatible with: water,nitrates,strong oxidants,acids,alkalis,zinc.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.
It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

Metabolism, toxicokinetics, mechanism of action and other information

2-METHOXY-1-METHYLETHYL ACETATE
The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

	KAYALAR KIMYA SAN.VE TIC.A.S.	Revision nr. 3 Dated 18/12/2023 Printed on 26/02/2024 Page n. 10/17 Replaced revision:2 (Printed on: 06/05/2021)
	EMP2013.25.0001 POLYURETHANE PAINT MATT WHITE	

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

XYLENE
WORKERS: inhalation; contact with the skin.
POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

2-METHOXY-1-METHYLETHYL ACETATE
WORKERS: inhalation; contact with the skin.

N-BUTYL ACETATE
WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

XYLENE
Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

2-METHOXY-1-METHYLETHYL ACETATE
Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

N-BUTYL ACETATE
In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

Interactive effects

XYLENE
Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

N-BUTYL ACETATE
A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

ACUTE TOXICITY ATE (Inhalation - vapours) of the mixture: > 20 mg/l
ATE (Oral) of the mixture: Not classified (no significant component)
ATE (Dermal) of the mixture: >2000 mg/kg

HYDROCARBONS, C9, AROMATICS
LD50 (Oral): 8400 mg/kg RAT

XYLENE
LD50 (Dermal): 4350 mg/kg Rabbit
ATE (Dermal): 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)

LD50 (Oral): 3523 mg/kg Rat
LC50 (Inhalation vapours): 26 mg/l/4h Rat
ATE (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP

	KAYALAR KIMYA SAN.VE TIC.A.S.	Revision nr. 3 Dated 18/12/2023 Printed on 26/02/2024
	EMP2013.25.0001 POLYURETHANE PAINT MATT WHITE	Page n. 11/17 Replaced revision:2 (Printed on: 06/05/2021)

(figure used for calculation of the acute toxicity estimate of the mixture)

TITANIUM DIOXIDE [in powder form contain
ing 1 % or more of particles with aerodynamic dia
meter ≤ 10 µm]
LD50 (Oral): > 10000 mg/kg Rat

2-METHOXY-1-METHYLETHYL ACETATE
LD50 (Dermal): > 5000 mg/kg Rat
LD50 (Oral): 8530 mg/kg Rat

N-BUTYL ACETATE
LD50 (Dermal): > 5000 mg/kg Rabbit
LD50 (Oral): > 6400 mg/kg Rat
LC50 (Inhalation vapours): 21,1 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

XYLENE
Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

TITANIUM DIOXIDE [in powder form contain
ing 1 % or more of particles with aerodynamic dia
meter ≤ 10 µm]
The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1% or more of titanium dioxide which is in the form of
or incorporated in particles with aerodynamic diameter ≤ 10 µm.

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

	KAYALAR KIMYA SAN.VE TIC.A.S.	Revision nr. 3 Dated 18/12/2023 Printed on 26/02/2024
	EMP2013.25.0001 POLYURETHANE PAINT MATT WHITE	Page n. 12/17 Replaced revision:2 (Printed on: 06/05/2021)

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class Viscosity: >20,5 mm2/sec (40°C)

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

Information not available

12.2. Persistence and degradability

XYLENE		
Solubility in water		100 - 1000 mg/l
Rapidly degradable		
TITANIUM DIOXIDE [in powder form contain ing 1 % or more of particles with aerodynamic dia meter ≤ 10 µm]		
Solubility in water		< 0,001 mg/l
Degradability: information not available		
2-METHOXY-1-METHYLETHYL ACETATE		
Solubility in water		> 10000 mg/l
Rapidly degradable		
N-BUTYL ACETATE		
Solubility in water		1000 - 10000 mg/l

12.3. Bioaccumulative potential

XYLENE		
Partition coefficient: n-octanol/water		3,12
BCF		25,9
2-METHOXY-1-METHYLETHYL ACETATE		
Partition coefficient: n-octanol/water		1,2
N-BUTYL ACETATE		

	KAYALAR KIMYA SAN.VE TIC.A.S.	Revision nr. 3 Dated 18/12/2023 Printed on 26/02/2024
	EMP2013.25.0001 POLYURETHANE PAINT MATT WHITE	Page n. 13/17 Replaced revision:2 (Printed on: 06/05/2021)

Partition coefficient: n-octanol/water	2,3
BCF	15,3

12.4. Mobility in soil

XYLENE	
Partition coefficient: soil/water	2,73
N-BUTYL ACETATE	
Partition coefficient: soil/water	< 3

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.
Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.
Waste transportation may be subject to ADR restrictions.
CONTAMINATED PACKAGING
Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA:	1263
------------------------	------

14.2. UN proper shipping name

ADR / RID:	PAINT or PAINT RELATED MATERIAL
------------	---------------------------------

	KAYALAR KIMYA SAN.VE TIC.A.S.	Revision nr. 3 Dated 18/12/2023 Printed on 26/02/2024
	EMP2013.25.0001 POLYURETHANE PAINT MATT WHITE	Page n. 14/17 Replaced revision:2 (Printed on: 06/05/2021)

IMDG: PAINT or PAINT RELATED MATERIAL
IATA: PAINT or PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3
IMDG: Class: 3 Label: 3
IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: NO
IMDG: NO
IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 30 Special provision: 163, 367, 650	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
IMDG:	EMS: F-E, <u>S-E</u>	Limited Quantities: 5 L	
IATA:	Cargo: Passengers: Special provision:	Maximum quantity: 220 L Maximum quantity: 60 L A3, A72, A192	Packaging instructions: 366 Packaging instructions: 355

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

	KAYALAR KIMYA SAN.VE TIC.A.S.	Revision nr. 3 Dated 18/12/2023 Printed on 26/02/2024
	EMP2013.25.0001 POLYURETHANE PAINT MATT WHITE	Page n. 15/17 Replaced revision:2 (Printed on: 06/05/2021)

Product
Point 3 - 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage $\geq$ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

	KAYALAR KIMYA SAN.VE TIC.A.S.	Revision nr. 3
	EMP2013.25.0001 POLYURETHANE PAINT MATT WHITE	Dated 18/12/2023 Printed on 26/02/2024 Page n. 16/17 Replaced revision:2 (Printed on: 06/05/2021)

Flam. Liq. 3	Flammable liquid, category 3
Carc. 2	Carcinogenicity, category 2
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
H226	Flammable liquid and vapour.
H351	Suspected of causing cancer.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

- LEGEND:
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
 - ATE: Acute Toxicity Estimate
 - CAS: Chemical Abstract Service Number
 - CE50: Effective concentration (required to induce a 50% effect)
 - CE: Identifier in ESIS (European archive of existing substances)
 - CLP: Regulation (EC) 1272/2008
 - DNEL: Derived No Effect Level
 - EmS: Emergency Schedule
 - GHS: Globally Harmonized System of classification and labeling of chemicals
 - IATA DGR: International Air Transport Association Dangerous Goods Regulation
 - IC50: Immobilization Concentration 50%
 - IMDG: International Maritime Code for dangerous goods
 - IMO: International Maritime Organization
 - INDEX: Identifier in Annex VI of CLP
 - LC50: Lethal Concentration 50%
 - LD50: Lethal dose 50%
 - OEL: Occupational Exposure Level
 - PBT: Persistent bioaccumulative and toxic as REACH Regulation
 - PEC: Predicted environmental Concentration
 - PEL: Predicted exposure level
 - PNEC: Predicted no effect concentration
 - REACH: Regulation (EC) 1907/2006
 - RID: Regulation concerning the international transport of dangerous goods by train
 - TLV: Threshold Limit Value
 - TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
 - TWA: Time-weighted average exposure limit
 - TWA STEL: Short-term exposure limit
 - VOC: Volatile organic Compounds
 - vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
 - WGK: Water hazard classes (German).

	KAYALAR KIMYA SAN.VE TIC.A.S.	Revision nr. 3 Dated 18/12/2023 Printed on 26/02/2024
	EMP2013.25.0001 POLYURETHANE PAINT MATT WHITE	Page n. 17/17 Replaced revision:2 (Printed on: 06/05/2021)

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2019/521 (XII Atp. CLP)
 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
 17. Regulation (EU) 2019/1148
 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
 23. Delegated Regulation (UE) 2023/707
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

02 / 03 / 04 / 07 / 08 / 09 / 10 / 11 / 12 / 14 / 15 / 16.