

BA93C00**Clear Acrylic TX Exterior Sealer**

Color	Clear	
Area of use	The product is specifically designed for exterior applications	
Application	Spray	
Mixing	Product BA93C00 JA055 Thinner	Weight 100 15 20-40

TECHNICAL CHARACTERISTICS:

Specific gravity (kg/l)	0.990 ± 0.020
Solids content (%)	52 ± 2
Viscosity component A (DIN4 at 20°C)	55 ± 5"

GENERAL CHARACTERISTICS:

Pot-life at 20°C	3 h
Recommended application weight (g/m²)	100-110
Number of layers	1-2 maximum
Drying time (100 g/m² at 20°C)	Dust free: 30-40' Touch dry: 60' Sandable: 18 h

GENERAL CHARACTERISTICS:

Substrate preparation	Sanding with P180-P240 abrasive
Shelf-life (months)	12

FEATURES:

- great sandability, transparency and good appearance on wood's grain
- contains UV filter to prevent the natural yellowing of the wood in time
- product shows excellent reactivity and elasticity
- it is highly recommended to start the painting system using coloured impregnating agent

SUBSTRATE PREPARATION:

The substrate must be properly prepared and cleaned of all kinds of dirt and dust.

WARNING:

Use only hardeners and thinners recommended by the company's technologists.

TRANSPORTATION AND STORAGE:

The product should be stored in a tightly closed can, protected from moisture and direct sunlight. After opening the package, the product should be used as quickly as possible. More detailed information on handling the product please find in the safety data sheet.

HEALTH & SAFETY:

For full Health and Safety information, please refer to Safety Data Sheet.

Suitable protective equipment (glasses, gloves, mask etc.) must be worn while using these products. Good ventilation must be provided in the working environment.