

BE30C01**White polyester basecoat**

Color	White	
Area of use	The product is suitable for doors and flat items	
Application	Spray	
Mixing	Product BE30C01 JE001 JE002 Thinner	Weight 100 2 2 5-20

TECHNICAL CHARACTERISTICS:

Specific gravity (kg/l)	1.400 ± 0.010
Solids content (%)	91 ± 1
Viscosity (DIN8 at 20°C)	35" ± 3

GENERAL CHARACTERISTICS:

Pot-life at 20°C	13 ± 2 min
Recommended application weight (g/m²)	150 - 250
Number of layers	2-3
Interval between layers	40-60 min
Drying time (100 g/m² at 20°C)	Dust free: 50-70 min Touch dry: 2-3 h Stackable: 12 h minimum Sandable after 16 h

GENERAL CHARACTERISTICS:

Substrate preparation	Sanding with P240 abrasive
Shelf-life (months)	6

FEATURES:

- great hiding power
- good sandability

SUBSTRATE PREPARATION:

The substrate must be properly prepared and cleaned of all kinds of dirt and dust.

WARNING:

Use only hardeners and thinners recommended by the company's technologists.

TRANSPORTATION AND STORAGE:

The product should be stored in a tightly closed can, protected from moisture and direct sunlight. After opening the package, the product should be used as quickly as possible. More detailed information on handling the product please find in the safety data sheet.

HEALTH & SAFETY:

For full Health and Safety information, please refer to Safety Data Sheet.

Suitable protective equipment (glasses, gloves, mask etc.) must be worn while using these products. Good ventilation must be provided in the working environment.