

TP77GXXC00**Polyurethane topcoat clear matte**

Color	Clear	
Gloss	10, 20, 30, 50, 80	
Area of use	Furniture, doors	
Application	Spray	
Mixing	Product TP77GXXC00 JP023 Thinner	Weight 100 50 10-30

TECHNICAL CHARACTERISTICS:

Specific gravity (kg/l)	0.985 ± 0.020
Solids content (%)	46 ± 2
Viscosity (DIN4 at 20°C)	70" ± 5

GENERAL CHARACTERISTICS:

Pot-life at 20°C	2 h
Recommended application weight (g/m²)	Min 90 - Max 150
Number of layers	1
Drying time (100 g/m² at 20°C)	Dust free: 30-35' Touch dry: 50-60' Stackable: 24 h

GENERAL CHARACTERISTICS:

Substrate preparation	Sanding with P320-P400 abrasive
Shelf-life (months)	12

FEATURES:

- good scratch resistance
- uniform matte finish
- smooth and pleasant to the touch

SUBSTRATE PREPARATION:

The substrate must be properly prepared and cleaned of all kinds of dirt and dust.

WARNING:

Use only hardeners and thinners recommended by the company's technologists.

TRANSPORTATION AND STORAGE:

The product should be stored in a tightly closed can, protected from moisture and direct sunlight. After opening the package, the product should be used as quickly as possible. More detailed information on handling the product please find in the safety data sheet.

HEALTH & SAFETY:

For full Health and Safety information, please refer to Safety Data Sheet.

Suitable protective equipment (glasses, gloves, mask etc.) must be worn while using these products. Good ventilation must be provided in the working environment.