

BP16C00**Polyurethane basecoat clear**

Color	Clear	
Area of use	Product is suitable for the finishing of wooden elements and accessories including doors and furniture. The product is specifically designed for exterior applications.	
Application	Spray	
Mixing	Product BP16C00 JP003 Thinner	Weight 100 50 10-30

TECHNICAL CHARACTERISTICS:

Specific gravity (kg/l)	0.920 ± 0.010
Solids content (%)	34 ± 1
Viscosity component A (DIN4 at 20°C)	20 ± 2"

GENERAL CHARACTERISTICS:

Pot-life at 20°C	2 h
Recommended application weight (g/m²)	100-150
Number of layers	1-2
Drying time (100 g/m² at 20°C)	Dust free: 20-25' Touch dry: 40-50' Stackable: 12 h Sandable after 6-8 h

GENERAL CHARACTERISTICS:

Substrate preparation	Sanding with P180-P240 abrasive
Shelf-life (months)	12

FEATURES:

- interior applications (chairs, furniture and windows frames)
- exterior applications
- suitable for vertical and horizontal applications
- fast drying
- good sandability
- good overcoating resistance

SUBSTRATE PREPARATION:

The substrate must be properly prepared and cleaned of all kinds of dirt and dust.

WARNING:

Use only hardeners and thinners recommended by the company's technologists.

TRANSPORTATION AND STORAGE:

The product should be stored in a tightly closed can, protected from moisture and direct sunlight. After opening the package, the product should be used as quickly as possible. More detailed information on handling the product please find in the safety data sheet.

HEALTH & SAFETY:

For full Health and Safety information, please refer to Safety Data Sheet.

Suitable protective equipment (glasses, gloves, mask etc.) must be worn while using these products. Good ventilation must be provided in the working environment.