

KVP5015.XX.0001**Polyurethane converter (base for tinting) white**

Color	White	
Gloss	25	
Area of use	Tintable topcoat	
Application	Spray	
Mixing	Product KVP5013.XX.0001 HHP5013.00.0000 Thinner	Weight 100 50 20-30

TECHNICAL CHARACTERISTICS:

Specific gravity (kg/l)	1.370 ± 0.03
Solids content (%)	70 ± 2
Viscosity (KU at 25°C)	90-100

GENERAL CHARACTERISTICS:

Pot-life at 20°C	3-4
Recommended application weight (g/m²)	Min 100 - Max 120
Number of layers	1-2
Drying time (100 g/m² at 20°C)	Dust free: 10-15' Touch dry: 25-35' Stackable: 20-24h

GENERAL CHARACTERISTICS:**Shelf-life (months)**

12

FEATURES:

- fast drying
- good levelling
- uniform matt appearance
- smooth to touch

SUBSTRATE PREPARATION:

The substrate must be properly prepared and cleaned of all kinds of dirt and dust.

WARNING:

Use only hardeners and thinners recommended by the company's technologists.

TRANSPORTATION AND STORAGE:

The product should be stored in a tightly closed can, protected from moisture and direct sunlight. After opening the package, the product should be used as quickly as possible. More detailed information on handling the product please find in the safety data sheet.

HEALTH & SAFETY:

For full Health and Safety information, please refer to Safety Data Sheet.

Suitable protective equipment (glasses, gloves, mask etc.) must be worn while using these products. Good ventilation must be provided in the working environment.