

**BP21C01****Polyurethane basecoat white**

<b>Color</b>	White	
<b>Area of use</b>	Doors, furniture. Suitable for horizontal and vertical surfaces	
<b>Application</b>	Spray	
<b>Mixing</b>	<b>Product</b> BP21C01 JP073 Thinner	<b>Weight</b> 100 40 20-40

**TECHNICAL CHARACTERISTICS:**

<b>Specific gravity (kg/l)</b>	1.500 ± 0.03
<b>Solids content (%)</b>	76 ± 2
<b>Viscosity component A (DIN8 at 20°C)</b>	40 ± 5"

**GENERAL CHARACTERISTICS:**

<b>Pot-life at 20°C</b>	2h
<b>Recommended application weight (g/m<sup>2</sup>)</b>	Min 100 - Max 150
<b>Number of layers</b>	1-3
<b>Drying time (100 g/m<sup>2</sup> at 20°C)</b>	Dust free: 35' Touch dry: 60' Stackable: 16 hours minimum

**GENERAL CHARACTERISTICS:**

<b>Substrate preparation</b>	Sanding with P240 abrasive
------------------------------	----------------------------

**Shelf-life (months)**

12

**FEATURES:**

- Perfect levelling, recommended for large surfaces
- Good hiding power
- Easy to sand

**SUBSTRATE PREPARATION:**

The substrate must be properly prepared and cleaned of all kinds of dirt and dust.

**WARNING:**

Use only hardeners and thinners recommended by the company's technologists.

**TRANSPORTATION AND STORAGE:**

The product should be stored in a tightly closed can, protected from moisture and direct sunlight. After opening the package, the product should be used as quickly as possible. More detailed information on handling the product please find in the safety data sheet.

**HEALTH & SAFETY:**

For full Health and Safety information, please refer to Safety Data Sheet.

Suitable protective equipment (glasses, gloves, mask etc.) must be worn while using these products. Good ventilation must be provided in the working environment.