

LKP3059.XX.0000**Clear polyurethane matt topcoat**

Color	Clear	
Gloss level	10, 20, 30	
Area of use	It can be used on all kinds of wooden surfaces for indoor furniture and decoration works in order to provide protection and decorative appearance.	
Application	Spray	
Mixing	Product LKP3059.XX.0000 HHP3059.00.0000 Thinner	Weight 100 50 40

TECHNICAL CHARACTERISTICS:

Specific gravity (kg/l)	0.995 ± 0.03
Solids content (%)	43 ± 3
Viscosity component A (DIN4 at 20°C)	60-70"
Viscosity (DIN4 at 20°C)	13-16"

GENERAL CHARACTERISTICS:

Pot-life at 20°C	4
Recommended application weight (g/m²)	100 - 120
Number of layers	1-2
Interval between coats: (at 20°C)	Min: 10' Max: 15'
Drying time (100 g/m² at 20°C)	Dust free: 10' Touch dry: 20' Stackable: 180'

GENERAL CHARACTERISTICS:

Substrate preparation	To be applied on surfaces precoated with basecoat and sanded with 240-320 abrasive. Surface must be clean and dust free, remove all dirt
Shelf-life (months)	24

FEATURES:

- Homogeneous matt appearance
- High transparency
- Good levelling
- Easy to apply

SUBSTRATE PREPARATION:

The substrate must be properly prepared and cleaned of all kinds of dirt and dust.

WARNING:

Use only hardeners and thinners recommended by the company's technologists.

TRANSPORTATION AND STORAGE:

The product should be stored in a tightly closed can, protected from moisture and direct sunlight. After opening the package, the product should be used as quickly as possible. More detailed information on handling the product please find in the safety data sheet.

HEALTH & SAFETY:

For full Health and Safety information, please refer to Safety Data Sheet.

Suitable protective equipment (glasses, gloves, mask etc.) must be worn while using these products. Good ventilation must be provided in the working environment.