

EMP2017.99.0001**Polyurethane high gloss topcoat white**

Color	White	
Gloss	High gloss	
Area of use	Surfaces for polishing	
Application	Spray	
Mixing	Product EMP2017.99.0001 HHP2017.00.0000 Thinner	Weight 100 50 30-50

TECHNICAL CHARACTERISTICS:

Specific gravity (kg/l)	1.350 ± 0.05
Solids content (%)	73 ± 2
Viscosity (Brookfield at 20C Pa.s)	4000-10000

GENERAL CHARACTERISTICS:

Pot-life at 20°C	3
Recommended application weight (g/m²)	Min 100 - Max 200
Number of layers	1-3
Drying time (100 g/m² at 20°C)	Dust free: 90' Touch dry: 120' Stackable: 36h

GENERAL CHARACTERISTICS:**Shelf-life (months)**

12

FEATURES:

- Fast drying
- Easy and quick polishability
- High yellowing resistance
- Very good levelling and surface hardness
- High and permeable brightness

SUBSTRATE PREPARATION:

The substrate must be properly prepared and cleaned of all kinds of dirt and dust.

WARNING:

Use only hardeners and thinners recommended by the company's technologists.

TRANSPORTATION AND STORAGE:

The product should be stored in a tightly closed can, protected from moisture and direct sunlight. After opening the package, the product should be used as quickly as possible. More detailed information on handling the product please find in the safety data sheet.

HEALTH & SAFETY:

For full Health and Safety information, please refer to Safety Data Sheet.

Suitable protective equipment (glasses, gloves, mask etc.) must be worn while using these products. Good ventilation must be provided in the working environment.