

TA17G03C00**Acrylic Zero Gloss matt topcoat**

Color	Clear	
Gloss	0-3	
Area of use	Furniture. Suitable for vertical surfaces, shelves.	
Application	Spray	
Mixing	Product TA17G03C00 JA052 Thinner	Weight 100 20 30-40

TECHNICAL CHARACTERISTICS:

Specific gravity (kg/l)	0.950 ± 0.010
Solids content (%)	27 ± 1
Viscosity (DIN4 at 20°C)	120" ± 5

GENERAL CHARACTERISTICS:

Pot-life at 20°C	3-4 h
Recommended application weight (g/m²)	130
Drying time (100 g/m² at 20°C)	Dust free: 40' Touch dry: 60' Stackable: 24 h

GENERAL CHARACTERISTICS:

Substrate preparation	Suitable for interior applications (furniture) and has to be applied on polyester or polyurethane basecoat after sanding or, otherwise, without sanding on an overcoatable pigmented polyurethane topcoat. In this latter case TA17G03C00 must be applied on the pigmented within 8 hours.
Shelf-life (months)	12

FEATURES:

- great scratch and abrasion resistance
- good light fastness
- smooth to the touch thanks to the use of special additives
- the coating is overcoatable after accurate sanding

SUBSTRATE PREPARATION:

The substrate must be properly prepared and cleaned of all kinds of dirt and dust.

WARNING:

Use only hardeners and thinners recommended by the company's technologists.

TRANSPORTATION AND STORAGE:

The product should be stored in a tightly closed can, protected from moisture and direct sunlight. After opening the package, the product should be used as quickly as possible. More detailed information on handling the product please find in the safety data sheet.

HEALTH & SAFETY:

For full Health and Safety information, please refer to Safety Data Sheet.

Suitable protective equipment (glasses, gloves, mask etc.) must be worn while using these products. Good ventilation must be provided in the working environment.