

LKA3053.XX.0000**Clear acrylic matt topcoat**

Color	Clear	
Gloss level	5, 10, 25	
Area of use	It can be used on all kinds of wooden surfaces for indoor furniture	
Application	Spray	
Mixing	Product LKA3053.XX.0000 HHA3053.00.0000 Thinner	Weight 100 10 35-50

TECHNICAL CHARACTERISTICS:

Specific gravity (kg/l)	0.920 ± 0.03
Solids content (%)	20 ± 2
Viscosity component A (DIN4 at 20°C)	35-50"

GENERAL CHARACTERISTICS:

Pot-life at 20°C	7
Recommended application weight (g/m²)	100 - 130
Drying time (100 g/m² at 20°C)	Dust free: 25-30' Touch dry: 40-50' Stackable: 6h
Shelf-life (months)	12

FEATURES:

- High performance in open pore applications
- Fast drying
- Transparent homogeneous matt distribution
- Soft touch and flexible film
- Resistance to yellowing

SUBSTRATE PREPARATION:

The substrate must be properly prepared and cleaned of all kinds of dirt and dust.

WARNING:

Use only hardeners and thinners recommended by the company's technologists.

TRANSPORTATION AND STORAGE:

The product should be stored in a tightly closed can, protected from moisture and direct sunlight. After opening the package, the product should be used as quickly as possible. More detailed information on handling the product please find in the safety data sheet.

HEALTH & SAFETY:

For full Health and Safety information, please refer to Safety Data Sheet.

Suitable protective equipment (glasses, gloves, mask etc.) must be worn while using these products. Good ventilation must be provided in the working environment.