

TA63G20C01**Polyurethane topcoat white matte**

Color	White	
Gloss	20	
Area of use	Suitable for furniture, kids' furniture and kids' bedroom furniture applications, doors and wooden items in general	
Application	Spray (also airmix or airless), curtain coater	
Mixing	Product TA63G20C01 JA052 Thinner	Weight 100 25 20-50

TECHNICAL CHARACTERISTICS:

Specific gravity (kg/l)	1.300 ± 0.020
Solids content (%)	59 ± 1
Viscosity (DIN4 at 20°C)	160" ± 5

GENERAL CHARACTERISTICS:

Pot-life at 20°C	2 h
Recommended application weight (g/m²)	Min 100 - Max 150
Drying time (100 g/m² at 20°C)	Dust free: 15-20' Touch dry: 30-40' Stackable: 6 hours minimum
Shelf-life (months)	12

FEATURES:

- good hiding power
- smooth to the touch
- product is especially designed to paint kitchen cabinets, both open and closed grain
- small amount of pigmented pastes at maximum 3% dosage can be used for color adjustment

SUBSTRATE PREPARATION:

The substrate must be properly prepared and cleaned of all kinds of dirt and dust.

WARNING:

Use only hardeners and thinners recommended by the company's technologists.

TRANSPORTATION AND STORAGE:

The product should be stored in a tightly closed can, protected from moisture and direct sunlight. After opening the package, the product should be used as quickly as possible. More detailed information on handling the product please find in the safety data sheet.

HEALTH & SAFETY:

For full Health and Safety information, please refer to Safety Data Sheet.

Suitable protective equipment (glasses, gloves, mask etc.) must be worn while using these products. Good ventilation must be provided in the working environment.