

**TA79GXXC00****Clear acrylic self-sealer matte**

<b>Color</b>	Clear	
<b>Gloss</b>	5, 10	
<b>Area of use</b>	Furniture, doors. Product suitable for parquet coatings	
<b>Application</b>	Spray	
<b>Mixing</b>	<b>Product</b> TA79GXXC00 JA052 Thinner	<b>Weight</b> 100 20 30-50

**TECHNICAL CHARACTERISTICS:**

<b>Specific gravity (kg/l)</b>	0.950 ± 0.010
<b>Solids content (%)</b>	24 ± 2
<b>Viscosity (DIN4 at 20°C)</b>	35" ± 3

**GENERAL CHARACTERISTICS:**

<b>Pot-life at 20°C</b>	>3 h
<b>Recommended application weight (g/m<sup>2</sup>)</b>	Min 80 - Max 120
<b>Number of layers</b>	1-3
<b>Drying time (100 g/m<sup>2</sup> at 20°C)</b>	Dust free: 10-15' Touch dry: 25-30' Stackable: 8 h

**GENERAL CHARACTERISTICS:**

<b>Substrate preparation</b>	The surface must be clean and dust free; remove all dirt (dust, wax etc.)
<b>Shelf-life (months)</b>	12

**FEATURES:**

- The product is suitable as topcoat on acrylic basecoats or, otherwise, as self-sealer by applying two or more layers
- The product is characterised by high abrasion resistance and resistance to spots in general

**WARNING:**

Use only hardeners and thinners recommended by the company's technologists.

**TRANSPORTATION AND STORAGE:**

The product should be stored in a tightly closed can, protected from moisture and direct sunlight. After opening the package, the product should be used as quickly as possible. More detailed information on handling the product please find in the safety data sheet.

**HEALTH & SAFETY:**

For full Health and Safety information, please refer to Safety Data Sheet.

Suitable protective equipment (glasses, gloves, mask etc.) must be worn while using these products. Good ventilation must be provided in the working environment.