

TA93GXXC00**Clear Acrylic Exterior Matt topcoat**

Color	Clear	
Gloss	10, 20	
Area of use	Specifically designed for exterior applications	
Application	Spray	
Mixing	Product TA93GXXC00 JA055 Thinner	Weight 100 15 10-30

TECHNICAL CHARACTERISTICS:

Specific gravity (kg/l)	1.010 ± 0.020
Solids content (%)	46 ± 2
Viscosity (DIN6 at 20°C)	100" ± 5

GENERAL CHARACTERISTICS:

Pot-life at 20°C	3 h
Recommended application weight (g/m²)	100-110
Drying time (100 g/m² at 20°C)	Dust free: 30-35' Touch dry: 60-70' Stackable: 24 h
Shelf-life (months)	12

FEATURES:

- Acrylic topcoat for exterior with high weathering resistance and great resistance to water
- Product shows excellent reactivity and elasticity

SUBSTRATE PREPARATION:

The substrate must be properly prepared and cleaned of all kinds of dirt and dust.

WARNING:

Use only hardeners and thinners recommended by the company's technologists.

TRANSPORTATION AND STORAGE:

The product should be stored in a tightly closed can, protected from moisture and direct sunlight. After opening the package, the product should be used as quickly as possible. More detailed information on handling the product please find in the safety data sheet.

HEALTH & SAFETY:

For full Health and Safety information, please refer to Safety Data Sheet.

Suitable protective equipment (glasses, gloves, mask etc.) must be worn while using these products. Good ventilation must be provided in the working environment.