

# JOINTBOY

## Spezial

The perfect tool  
for every elastic joint!

Because of the special active ingredient,  
JOINTBOY can be used without  
parting agents.

4 special tools for  
professionals!

For all types of  
silicon and acrylic!



↑ 10 mm groove: For all finished edges  
with an angle of approx. 90°.



↑ 6 mm: For all sealing  
joints on windows  
(17° angle for all standard  
windows).

Joint tool with special  
angles and grooves



↑ 17.5 mm groove: For all built-up joints on  
flush-fitting tiles and window panes  
(e.g. conservatories etc.).

← Extra-thin special tool



5 / 8 mm:  
For hard-to-reach areas  
(e.g. windows/corners,  
wash hand basin  
fittings).

← Joint tool with round cutting edge



6 mm: For all standard joints not subject  
to traction or pressure stresses  
(e.g. mirrors, wash hand basins).

8 / 10 mm: For all standard joints  
subject to traction or pressure stresses  
(e.g. baths, showers, kitchen worktops,  
corners on floors/walls with tiles).

14 mm: For wide to extremely wide  
joints subject to traction or pressure  
stresses (e.g. corners on floors/walls  
with tiles, masonry, refurbishment etc.).

For **expansion joints** (e.g. on floors) with  
rounded tiles and for joints that are to be  
recessed a round tool should be used.



← Joint tool with straight cutting edge

JOINTBOY SPECIAL works  
without parting agents. There is  
no need to dampen in the sealing  
compound with a detergent  
solution.

You will also be able to produce  
perfect seals on connecting joints  
and expansion joints without  
masking or time-consuming  
follow-up work.

JOINTBOY SPECIAL is a special  
tool in tested craftsman quality: it  
is resistant to acids and friction  
and is extremely flexible.



**FUGEN-ASS**  
Made in Baden-Württemberg  
Schneider Messertechnik