

C&I Air-Cooled Hybrid Cabinet

Z BOX-C 100/120 2H



The Z BOX-C 100/120 2H series is a professional PV-plus ESS solution, designed on ESS integration and digital monitoring technologies. The cabinet integrates components such as lithium battery, HVAC, fire suppression system (FSS), and EMS. With compact structure, it enables easy installation and flexible capacity expansion. Paired with hybrid inverter, the ESS supports multiple work modes and various operation strategies



Economical & Efficient

RTE up to 90%, DOD up to 100%.



Safe & Reliable

IP55, optimized ventilation design, temperature difference within 6°C.



Compact & Convenient

0.96m² Footprint, easy to transport and install.



Expandable & Modular

Easy modular design supports parallel connection for convenient system expansion.



Versatile

Support multiple brands of hybrid inverter, with higher selectivity.



PV Pluggable

Support PV connection, with higher integration.



Self-Developed

LFP314Ah battery cell system integration, leading cost advantage, 3S fusion.



Easy O&M

Support multiple ways of operation and maintenance, including onsite, cloud.

Parameters

Battery Cabinet	Z BOX-C 100 2H		Z BOX-C 120 2H
Cell Type	LFP/314Ah		LFP/314Ah
Pack Configuration	20.096kWh/1P20S		20.096kWh/1P20S
System Configuration	100.48kWh/1P100S		120.576kWh/1P120S
Rated DC Voltage	320V		384V
DC Voltage Range	280~360V		336~432V
Max. Charge/Discharge Rate	0.5P		
Max. Depth of Discharge	100%(25±2℃)		
Cycle Life	≥8,000		
PV Input			
Max. Input Power	60kW	80kW	100kW
PV Votage Range	150~850V	150~850V	150~850V
MPPT	3	4	4
Max. Input Current	40A*3	40A*4	40A*4
AC Side			
Rated Output Power	30kW	40kW	50kW
Rated AC Voltage	400V		
AC Voltage Range	±15%		
Grid Type	3W+N+PE		
Rated Frequency	50Hz/60Hz		
Power Factor	0.99/-0.8~+0.8		
THDi	≤3%		
DC Ratio	< 0.5%I _{pn}		
General			
Max. Round Trip Efficiency	90%		
Communication	Modbus TCP/IP		
Fire Suppression System	Aerosol		
Ingress Rating	IP55		
Cooling	Air Cooling		
Operating Temperature	-25℃~55℃(Derating After 45℃)		
Anticorrosion Rating	C4(C5 optional)		
Humidity	0~95%RH(Non-Condensing)		
Altitude	3000m(Derating above 2000m)		
Dimensions (W*D*H)	800*1,200*2,100mm		
Weight	1200kg		
Safety/EMC	UN38.3, IEC62619, IEC63056, IEC62477-1, IEC61000-6-2/4		
Grid Code	EN50549-1/-10, EN50549-2/-10, G99, VDE4105, NRS097, C10/11		